INCH-POUND

MIL-W-71069(AR)
AMENDMENT 2
30 September 1996
SUPERSEDING
AMENDMENT 1
2l June l994

MILITARY SPECIFICATION

WARHEAD, 2.75 INCH ROCKET, FLECHETTE: XM255El

This amendment forms a part of MIL-W-71069(AR), dated 19 March 1992, and is approved for use by the U.S. Army Armament Research, Development, and Engineering Center and is available for use by all Departments and Agencies of the Department of Defense.

Delete "XM255El" and substitute "M255Al" wherever it appears in this document.

PAGE 4

Add paragraph 3.3.10 as follows:

"3.3.10 Environmental protector push-off test. The environmental protector shall withstand a push-off test of 4.0 lbs. minimum and 17.0 lbs. maximum. The push-off test fixture shall simulate the umbilical lead connector with the push-off force applied through the fixture to the closed end of the environmental protector. Testing shall be as specified in 4.5.11."

PAGE 6

4.3.1, Under parts description, Add:

"Protector, Environmental	9349897	15"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-W-71069(AR)
AMENDMENT 2

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.25	Protector, Environmental		9349897
			NEXT HIGHER ASSEMBLY
			9333825/9345168

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined.			
Major 101.	Push-off test	Level III	3.3.10	4.5.11
Minor 201.	Evidence of poor workmanship	Level IV	3.5	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89

Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

2. (37a)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:19Z
Check the source to verify that this is the current version before use.

PAGE 11

TABLE I, Add:

"Protector, Environmental (Dwg. 9349897)			
Push-off test	15	3.3.10	4.5.11
Examination for defects	15	3.1	4.4.2.25"

PAGE 37

Add 4.4.2.25, included Page 3 (37a).

PAGE 43

Add paragraph 4.5.11 as follows:

"4.5.11 Push-off test. A push-off test shall be set up to simulate the removal of the environmental protector. The dimensions of the simulated umbilical cable connector, where the environmental protector fits on, shall have 0.368 ± 0.001 inch large outside diameter, 0.273 ± 0.001 inch small outside diameter, and 0.157 ± 0.001 inch width of the large outside diameter. The surface shall have a 32 microinch finish all over. A steady load shall be applied with a hemispherical (180 ± 0.005 inch radius) plunger against the inside surface of the environmental protector. Any environmental protector that does not meet the required load shall be classified defective."

The margin of this amendment is marked with a vertical line to indicate where a change to the previous amendment was made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1340-A991)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:19Z
Check the source to verify that this is the current version before use.