INCH-POUND

MS24143W
AMENDMENT 3
14 February 2001
AMENDMENT 2
15 April 1994

DETAIL SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, 25 AMPERES, 3PST-(N.O.),
TYPE I, HERMETICALLY SEALED

This amendment forms a part of MS26143W, dated 24 November 1993, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

ELECTRICAL CHARACTERISTICS, Dielectric strength (altitude), add footnote 4/.

At bottom of page, add:

"4/ Use MS27243-1 terminal cover during dielectric testing at altitude."

PAGE 4

TABLE I: Delete and substitute:

" TABLE I. Vibration levels.

Dash number	5-10 Hz	10-55 Hz	55-250 Hz	250-500 Hz	500-1500 Hz
D1	.06 DA	.06 DA	10 g's	6 g's	6 g's
D2				4 g's	3 g's
D3				4 g's	3 g's
A3, A4				4 g's	3 g's

PAGE 5

* TABLE III: delete “Intermediate current” and substitute “Mixed loads”.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:48Z
Check the source to verify that this is the current version before use.

* Qualification by similarity, delete and substitute: “Qualification by similarity: See MIL-PRF-6106.”

The margins of this amendment are marked with asterisks to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Navy - AS
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5945-1119-14)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:48Z
Check the source to verify that this is the current version before use.