
INCH-POUND
MIL-DTL-24251/6E
11 July 2013
SUPERSEDING
MIL-DTL-24251/6D
15 February 2008

DETAIL SPECIFICATION SHEET

SHIELD, ELECTRON TUBE, HEAT DISSIPATING, 7 AND 9 PIN, MINIATURE (RETROFIT TYPE ONLY)

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-24251.

This specification is approved for use by all Departments and Agencies of the Department of Defense.



NOTES:
1. All dimensions are in inches.
2. Millimeters are in parentheses.
3. Metric equivalents (to the nearest 0.01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
4. Unless otherwise specified, tolerance is 2 places ± .010 (0.25 mm); 3 places ± .005 (0.13 mm).

FIGURE 1. Dimensions and configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:43Z
Check the source to verify that this is the current version before use.

TABLE 1. Characteristics.

Dash no.	Heat dissipation temp. reduction in °C (minimum)	A -.062 (1.57)	B Max	C dia ±.015 (0.38)	Weight grams max	Tube envelope		Tube socket ref 2/
						Style	Length nom	
1	25	1.500 (38.10)	1.625 (41.28)	.875 (22.23)	11.0	T-5 1/2	1.125 (28.58)	MIL-DTL-12883/2
2	40	2.000 (50.80)	2.125 (53.98)	.875 (22.23)	15.0	T-5 1/2	1.500 (38.10)	
3	45	2.500 (63.50)	2.625 (66.68)	.875 (22.23)	19.0	T-5 1/2	2.000 (50.80)	
4	25	1.500 (38.10)	1.625 (41.28)	1.000 (25.40)	12.0	T-6 1/2	1.125 (28.58)	MIL-DTL-12883/3
5	55	2.000 (50.80)	2.125 (53.98)	1.000 (25.40)	16.0	T-6 1/2	1.562 (39.67)	
6	45	2.500 (63.50)	2.625 (66.68)	1.000 (25.40)	20.0	T-6 1/2	2.000 (50.80)	
7 1/	45	2.750 (69.85)	2.875 (73.03)	1.000 (25.40)	22.0	T-6 1/2	2.812 (71.42)	

1/ This shield is for use with noval tubes which are longer than usual tubes.

2/ Not recommended for new design.

REQUIREMENTS:

The shield, locking mechanism, liner, and other parts shall be designed to meet the requirements in MIL-DTL-24251, and to fit the tube envelope and tube socket specified in table I.

Dimensions and configuration: See figure 1 and table I. No special retainer (base) or adapter will be permitted.

Material:

Spring (when used): Beryllium copper, ASTM-B194, ASTM-B196/B196M and ASTM-B197/B197M.
Shell: Aluminum alloy, SAE-AMS-QQ-A-250 (aerospace and unspecified applications), or ASTM-B209 (non-aerospace applications).
Liner: Beryllium copper, ASTM-B194.

Finish:

Spring (when used): Black cadmium plate, SAE-AMS-QQ-P-416, class 1, type II.
Shell: Black anodize, type II in accordance with MIL-A-8625, black matte in accordance with MIL-DTL-5541, optional finish: Henderlube or equal.
Liner: Black cadmium plate, SAE-AMS-QQ-P-416, class 3, type II, optional finish: Henderlube or equal.

Construction: The spring shall be held in place by friction or by mechanical means if the maximum diameter is smaller than the inside diameter of the shield. The tension shall be such as will insure maximum compression of .125 inch (3.18 mm) over seated tube. The force required to compress spring to .375 inch (9.53 mm) shall be within 1.5 to 2.5 pounds. Spirals shall not touch each other. The end of the coil spring shall not contact the electron tube envelope.


Installation force shall not exceed 20 pounds.

Engaging torque: 20 inch-pounds maximum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:43Z
Check the source to verify that this is the current version before use.

The Part or Identifying Number (PIN) consists of the basic number of this specification sheet, preceded by the letter "M", and a dash number taken from table I.

Example:



Referenced Documents: In addition to MIL-DTL-24251, this document references the following:

MIL-DTL-5541
MIL-A-8625
MIL-DTL-12883/2
MIL-DTL-12883/3
ASTM-B194
ASTM-B196/B196M
ASTM-B197/B197M
ASTM-B209
SAE-AMS-QQ-A-250
SAE-AMS-QQ-P-416

The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5960-2013-020)

Review activities:
Army - AR, AV, MI
Navy - AS, CG, MC, OS, SH
Air Force - 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:43Z
Check the source to verify that this is the current version before use.