INCH-POUND

A-A-52090
March 11, 1991

COMMERCIAL ITEM DESCRIPTION

Bread Slicing Machine, Electric Operated, Multiple Knife

The General Services Administration has authorized the use of this commercial item description in perference to Type I, styles 1 and 2 of MIL-B-43866C.

1. CLASSIFICATION

1.1 Classification. This commercial item description covers one type of bread slicing machine with a gravity feed chute in the following styles (see 5.2).

Style 1 - With stand
Style 2 - Without stand

1.2 CID based part identification number (PIN). A document based PIN to identify types of items is included in section 5. This identification numbering procedure is for Government purposes and does not constitute a requirement for the contractor.

2. SALIENT CHARACTERISTICS

2.1 Design and construction. The bread slicing machine shall be electrically operated and be designed to have the knife frames rapidly reciprocated in opposite directions. Each loaf shall be completely sliced as it moves across the knives. Slices shall be cleanly cut and be 1/2 inch nominal in thickness. There shall be no marked change in the shape of the loaf after being sliced. A crumb tray shall be situated for catching all crumbs that fall from the slicer. The machine shall be designed to transversely slice loaves, which are a minimum of 12 inches long and 4-5/8 inches square, at a rate of not less than seven loaves per minute. The bread slicing machine shall consist of knives, knife frames (reciprocating powered type), loaf guides, crumb tray, back and front chute, stand (when required), motor, and control assembly. All food contact areas shall be made from commercially available Type 304 or 303 stainless steel. The body of the machine shall be fabricated from Type 1018

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data which may improve this document should be sent by letter to: Commander, U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-WEE, Natick, MA 01760-5018.

AMSC N/A FSC 7320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.

or 1020 commercial quality steel. The bread-slicing machine shall have a chute equipped with loaf guides fixed at such an angle or angles that when the back chute is maintained fully loaded with loaves of bread, the loaves shall move by gravity to the knives, be sliced, and move by gravity to the bread stop at the front chute. The bread-slicing machine drives and mechanisms shall be enclosed to the maximum feasible to minimize potential for operator contact with moving parts.

2.2 Knives. The slicing knives shall be heat treated high carbon steel having a Rockwell hardness of C58 to C60 per ASTM E 18 when tested as specified in 3.4.

2.3 Knife frames. The knife frames shall be fabricated from low carbon steel. The knife frames shall have the knives set to slice nominal 1/2 inch thick slices. The frame shall provide for each knife to be independently mounted under balanced tension.

2.4 Loaf guides. Loaf guides shall consist of two full length rails, one on each side of the chute. The position of each rail shall be readily and easily adjustable from 6 inches to a maximum of 16 inches, and able to be securely locked by hand in the desired position.

2.5 Crumb tray. The bread slicing machine shall be provided with a crumb tray. It shall be a pan or drawer attached to the machine which can be easily removed for cleaning.

2.6 Chutes. The bread-slicing machine shall be provided with a back chute and a front chute. The back chute shall be at least 32 inches in length measured from the knives to the back edge of the back chute. The front chute shall be provided with a loaf stop. The front chute shall be at least 8 inches in length measured from the knives to the front edge of the front chute. Chutes shall be fabricated of stainless steel type 304 or 303.

2.7 Style 1 bread slicers. The stand shall be of a frame type construction with four legs and fabricated from commercial quality Type 1018 or 1020 steel. The frame shall be welded to the legs to form a rigid assembly and be at least 20 inches in height. Stands shall be provided with means for bolting the stand to the bread-slicing machine. The stands shall have holes for hold down bolts at the floor level. Structural members shall be arranged so as not to form traps, recesses or pockets. If made of hollow stock, frame members shall have the ends closed. All joints and edges where two members are permanently joined shall be joined in such a manner as to minimize horizontal ledges, cracks, crevices and protusions.

2.8 Electrical characteristics. The bread slicing machine shall be designed to operate on a 120 volt, single phase, 60 hertz power source. When 50 hertz operation is specified (see 5.2), the voltage and phase shall be specified by the contracting officer. Provisions for grounding shall be included in each bread slicer. Access to controls and connections shall be gained from the front of the slicing machine.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:06Z
Check the source to verify that this is the currentversion before use.

2.8.1 Motor. The motor for the bread slicing machine shall be 1/2 hp, 120 volt, 60 hertz, single phase power source, and totally enclosed. When 50 hertz operation is specified (see 5.2), the voltage and phase shall be specified by the contracting officer. The motor shall comply with National Electrical Manufactures Association (NEMA) Standard MG-1.

2.8.2 Motor switch. The bread-slicing machine shall have a readily accessible double-pole, single-throw switch provided for starting and stopping the motor. The switch shall be recessed into the body structure of the bread-slicing machine or shielded to prevent inadvertent activation.

2.8.3 Cord and attachment plug. The cord shall be type SO or SJO and measure at least 8 feet in length with a NEMA approved 3-prong grounding plug.

2.9 Lubrication. Bearings located on surfaces requiring lubrication in the product zone shall be smooth, readily accessible and nontoxic. Bearings requiring other than edible lubrication shall be sealed or self lubricated, located outside the product zone and their design and construction shall be such that lubricants cannot leak, drip or be forced into the product zone.

2.10 Tools. Each bread-slicing machine shall be provided with a knife removing tool.

2.11 Finish. Exterior surfaces and parts not specified shall be neatly finished with a durable enamel in accordance with standard commercial practice.

2.12 Data name plate (Government unique requirement (see 5.4)). The slicing machines shall be furnished with a data name plate in accordance with the applicable requirements of MIL-STD-130 except the requirements for: (a) Methods of applying, (b) Identification tags, (c) Information not required, and (d) Optional marking information shall not apply. The data name plate shall be made of minimum 20 gauge corrosion-resisting metal and attached to the slicing machine by rivets, screws, or by welding in such a manner as to meet the applicable sanitary requirements for this equipment. The plate shall contain the following information which shall be stamped, engraved, or applied by photosensitive means:

National Stock Number
Procurement Contract Number
Specification Data
Manufacturer's Name, Address, and Telephone Number
Supplier's Name, Address, and Telephone Number (List only if different from Manufacturer)
Manufacturer's Model Number
Government Approved Manual Number (when specified see 5.2)

Each plate shall be placed so that is readily visible to the operator during normal operating use and so as to not adversely affect the life and utility of the slicing machine.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.

2.13 Standards compliance. The bread slicing machines shall conform to Underwriters Laboratories (UL) Standard No. 73 Motor-Operated Commercial Food Preparing Machines.

2.14 Workmanship. All components and assemblies of the bread slicing machine shall be free from dirt and other harmful extraneous material, burrs, slivers, rough die, tool and grind marks, dents and cracks.

3. QUALITY ASSURANCE

3.1 Certification. The contractor shall certify, and maintain objective quality evidence, that the product offered meets this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

3.2 Responsiblity for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all examination, and test requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections, examination, and tests deemed necessary to assure that supplies and services conform to prescribed requirements.

3.3 Examination. Five bread slicing machines shall be examined for the defects listed in table I. The finding of any defect shall be cause for rejection of the lot.

TABLE I End item visual defects

Examine	Defect
Design	Characteristic not in accordance with the specified requirements
Construction and workmanship (general)	Any component missing or not as specified Any visible component fractured, split, or malformed Adjustable assembly that cannot be adjusted Casting miscast, cracked, porous, or contains blowholes Assembly or component improperly located (for example, gasket improperly fitted to provide seal)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.

TABLE I End item visual defects (cont'd)

Examine	Defect
Construction and workmanship (general) (cont'd)	Functioning components that require abnormal force to operate Crack or crevice not filled and sealed to prevent entrance of dust, liquid, and dirt Floor stand not provided with holes for holddown bolts Crumb tray not attached to the machine by mechanical means Crumb tray not readily removable for cleaning Any sharp edge, corner, sliver, burr, rough die and grind marks, dent or crack
Threaded fasteners	Threaded fasteners missing, broken, stripped, fractured, or loose
Welding and brazing (where required)	Not type specified, missing, incomplete, burn holes, cracked, fractured, or otherwise not fused
Tools	Missing

3.4 Knife hardness test. The slicing knives shall be tested to determine compliance with 2.2. The sample unit shall be one knife. The inspection lot shall be all the knives submitted for inspection at one time. Five bread slicing machines shall be examined. The hardness of the slicing knives shall be determined within 1/8 inch of the cutting edge in accordance with ASTM E 18. Three hardness determinations shall be made on each sample unit with an average of the three determinations shall be recorded. Any sample unit with an average hardness not falling within the range specified in 2.2 shall cause rejection of the lot.

3.5 UL. Acceptable evidence of meeting the applicable requirements of UL 73 shall be the UL listing mark, or a certified test report from a recognized independent testing laboratory, acceptable to the Government, indicating that the fryers offered conform to the applicable requirements of UL 73.

3.6 Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing suppliers' employees

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.

to undue hazards from the recovered materials. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this commercial item description unless otherwise specified.

3.7 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch/pound units, provided they fall within the tolerances specified using conversion tables contained in the latest revision of FED-STD-376, and all other requirements of this commercial item description are met.

4. PACKAGING

4.1 Packaging and packing. Packaging and packing shall be commercial or export as specified (see 5.2).

4.2 Commercial packaging and packing. Each bread slicing machine shall be cleaned, preserved, packaged, packed and unitized in accordance with ASTM D 3951.

4.3 Export packaging and packing.

4.3.1 Export packaging. Each bread slicing machine shall be cleaned, preserved and cushioned to protect against corrosion, deterioration and physical damage during shipping and storage. Disassembled parts and accessories shall be packaged in a fiberboard box conforming to type CF or SF, class domestic, style optional of PPP-B-636.

4.3.2 Export packing. Each bread slicing machine with its parts package shall be packed in a nailed and lock-corner wood box conforming to class II, style 2 or 4, type 2 load of PPP-B-621, or in a cleated-plywood box conforming to overseas type, style optional, type 2 load of PPP-B-601. Each box shall be waterproofed with a sealed case liner conforming to type I, II or IV, grade optional of MIL-L-10547. Each box shall be closed, strapped, and skidded if the shipping weight exceeds 200 pounds, in accordance with PPP-B-621 or PPP-B-601, as applicable.

4.3.3 Palletization. When specified (see 5.2), shipping containers shall be palletized in accordance with MIL-STD-147.

4.4 Labeling (commercial and export). Commercial labeling shall be acceptable.

4.5 Marking (commercial and export). Marking of shipping container and unit load shall be in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.

5. NOTES

5.1 Intended use. The bread slicing machine covered by this commercial item description is intended for use in garrison fixed baking installations.

5.2 Ordering data. Acquisition documents should specify the following:

a. Title, number and date of this document.
b. Style required (see 1.1 and 2.7).
c. When 50 hertz operation is required (see 2.8 and 2.8.1).
d. Government approved manual number to be included on the data name plate when manuals are purchased under the contract (see 2.12).
e. Type of packaging and packing required (see 4.1).
f. When palletization of shipping containers is required (see 4.3.3).

5.3 Sources of documents.

5.3.1 Sources of nongovernment association documents.

ASTM D 3951 - Standard Practice for Commercial Packaging, and

ASTM E 18 - Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials

These methods are available from:

The American Society for Testing and Materials
1916 Race Street,
Philadelphia, PA 19103

Standard MG-1 and NEMA 3 prong grounding plugs are available from:

National Electrical Manufacturers Association (NEMA)
155 East 44th Street
New York, NY 10017

UL Standard No. 73 - Motor Operated Commercial Food Preparing Machines, is available from:

Underwriters Laboratories, Inc. (UL)
333 Pfingsten Road,
Northbrook, IL 60062


Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.

5.3.2 Source of governmental documents. Copies of military and Federal documents are available from:

Standardization Documents Order Desk
Bldg. 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

5.4 Government unique requirements. Whenever "(Government unique requirements)" is included in the title of a paragraph under "salient characteristics" it is meant that the requirement is something that is not normally offered to the commercial marketplace by the manufacturer.

5.5 Part identification number (PIN). The PIN's to be used for items required by this CID are created as follows:



MILITARY INTERESTS:

Custodians

Army - GL
Air Force - 99

Review activities

Army - MD
Navy - MC
Air Force - 84, 50
DLA - GS

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project 7320-0812

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:06Z
Check the source to verify that this is the current version before use.