INCH-POUND
MS21251J
30 October 1999
Superseding
MS21251H
22 FEBRUARY 1999

MILITARY SPECIFICATION SHEET

TURNBUCKLE BODY, CLIP LOCKING

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-DTL-8878.



(J) Entire document revised

DISTRIBUTION STATEMENT A. Approved for public release; distribution is limited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:29Z
Check the source to verify that this is the current version before use.

J

DASH NO.			WIRE ROPE DIA.		MINIMUM BREAKING	THREAD	L	ØB	N	ØD	ØE	K		ØS	ØP	ØBB	APPLI-CABLE
STEEL	BRASS	AL	NOM. REF.	MIN.	STRENGTH LB	T UNF-3B	±.031	±.005	±.031	±.005	± .005	MIN.	MAX.		±.005		LOCKING CLIP MS21256
2S	B2S	A2S	1/16	.062	800	.1380 (#6)-40	2.250	.250	.156	.219	.188	.0749	.0807				-1
2L	B2L	A2L					4.000										-2
3S	B3S	A3S	3/32	.093	1600	.1900 (#10)-32	2.250	.344	.188	.281	.250	.1009	.1048				-1
3L	B3L	A3L					4.000									.020	-2
5S	B5S	A5S	5/32	.156	3200	.2500 (1/4)-28	2.250	.438	.312	.391	.328	.1294	.1334	.187	.125	FIM	-1
5L	B5L	A5L	1/				4.000										-2
6S	B6S	A6S	3/16	.187	4600	.3125 (5/16)-24	2.250	.500	.375	.438	.406	.1587	.1627				-1
6L	B6L	A6L					4.000										-2
8L	B8L	A8L	1/4	.250	8000	.3750 (3/8)-24		.625	.500	.594	.469	.1900	.1939			.025	-2
9L	B9L	A9L	9/32	.281	12750	.4375 (7/16)-20	4.250	.750	.594	.688	.563	.2185	.2225			FIM	
10L	B10L	A10L	5/16	.312	17500	.5000 (1/2)-20		.875	.656	.813	.625	.2498	.2537	.250	.188		-3

1/ See note 5.

REQUIREMENTS:

1. Material and protective treatment: See MIL-DTL-8878.

2. Finish: Surface finish shall be RMS 125 or better.

3. Threads: Threads shall be in accordance with FED-STD-H28/20.

4. Barrels shall be marked with the year of manufacture.

5. Marking by impression stamping (or any other stress inducing method), if used, shall be done before stress relieving.

6. Part number: Part Identifying Number (PIN) shall consist of the basic MS number, followed by a dash number, first letter following dash number indicates material, second number refers to the size, letter following size indicates length (short or long).

Example of part number: MS21251-B5L-barrel, turnbuckle, brass, .2500 (1/4)-28 thread, long.

7. Tolerances: Unless otherwise specified, tolerances: decimals ±.010, angles ± 3° .

NOTES:

1. Dimensions are in inches.

2. Remove burrs and break sharp edges (see procurement specification for definition).

3. Interpret drawing in accordance with ASME Y14.5M.

4. For clip locking of terminals and turnbuckles see MS33736.

5. For .125 (1/8) inch diameter wire rope use -5 parts, minimum breaking strength 2200 lb (ref).

6. A turnbuckle with a manufacturing date of 1978 or older shall not be used for replacement repairs since stress relieving was not required prior to this date.

7. In the event of a conflict between the text of this document and the references cited herein the text of this document takes precedence.

8. Unless otherwise specified, issues of referenced documents are those in effect at the time of solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:29Z
Check the source to verify that this is the current version before use.

MILITARY INTEREST

Custodians:
Army - AV
Navy - AS
Air Force – 99

Review activities:
Navy – MC
Air Force - 82

J

Preparing Activity:
DLA-GS

(Project 1560-0259)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:29Z
Check the source to verify that this is the current version before use.