[INCH-POUND]
A-A-246B
August 12, 1998
SUPERSEDING
A-A-246A
February 21, 1991

COMMERCIAL ITEM DESCRIPTION

FLOAT, VALVE (WATER CLOSET)

The General Services Administration has authorized the use of this commercial item description by all federal agencies.

1. SCOPE

1.1 Scope. This commercial item description (CID) covers copper and plastic valve floats intended for use in water closet tanks.

2. CLASSIFICATION

2.1 Classification. The valve float shall be of the following type, as specified (see 7.2).

Type 1 - Copper

Type 2 - Plastic

3. SALIENT CHARACTERISTICS

3.1 Construction. Valve floats shall be fabricated of corrosion-resistant materials throughout. Floats shall be ellipsoidal in shape with a minimum diameter of 4 inches (101.6 mm) and a maximum diameter of 6-1/2 inches (165.1 mm). Copper floats shall be constructed with a double reinforced, crimped seam.

3.1.1 Buoyancy. Buoyancy of floats shall be sufficient to shut off a standard commercial inlet valve, which utilizes the float and an 8-inch (803.2 mm) float rod, and is connected to a 125 psi (862 kPa) water supply.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: General Services Administration, Engineering Branch (7FXEE), 819 Taylor St., Fort Worth, TX 76102

FSC 4510

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:06Z
Check the source to verify that this is the current version before use.

3.2 Type 1. Copper floats shall be equipped with metallic receptors 0.250-20 UNC-2B internal threads in accordance with ANSI Y14.6 for acceptance of float rods with 0.250-20 UNC-2A external threads.

3.3 Type 2. Plastic floats shall be equipped with plastic receptors 0.250-20 UNC-2B internal threads in accordance with ANSI Y14.6 for acceptance of float rods with 0.250-20 UNC-2A external threads, or shall be self-threading at the manufacturer's option.

3.4 Workmanship. The valve floats shall have no sharp edges, slivers, burrs, deep scratches or tool marks. Hollow floats shall not leak. The floats shall have no defect which affects the serviceability, durability, or appearance.

3.5 Measurement system. The values stated in inch-pound units are to be regarded as the standard. The metric values stated in parentheses are for information purposes only.

3.6 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, providing they fall within the tolerances specified and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

4. REGULATORY REQUIREMENTS

4.1 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

5. QUALITY ASSURANCE PROVISIONS

5.1 Product Conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:06Z
Check the source to verify that this is the currentversion before use.

6. PACKAGING

6.1 Packaging. Preservation, packing, and marking shall be as specified in the contract or order.

7. NOTES

7.1 Referenced Document. The document referenced in this CID shall be the issue in effect on the date of issuance of the invitation for bids or request for proposals unless otherwise specified. The document forms a part of this CID to the extent specified. In the event of a conflict between this CID and the document referenced herein, this CID shall take precedence.

ANSI Standard.

Y14.6 - Screw Thread Representation

Application for copies of ANSI standards should be addressed to the American National Standards Institute, 11 West 42nd Street, 13th Floor, New York, NY 10036.

7.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents (if applicable).

a. Title, number and date of this commercial item description.
b. Type.
c. Preservation, packing, and marking desired.

7.3 National Stock Numbers (NSNs): The following is a list of NSNs assigned which correspond to this CID. The list may not be indicative of all possible NSNs associated with the CID.

NSN	Type
4510-00-242-4185	1 - Copper
4510-00-684-6101	2 - Plastic

MILITARY INTERESTS:

Review Activities:

DLA - CC
Air Force - 99

CIVIL AGENCY COORDINATING ACTIVITY:
GSA - FSS

PREPARING ACTIVITY:
GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:06Z
Check the source to verify that this is the current version before use.