A-A-501
October 26, 1979

COMMERCIAL ITEM DESCRIPTION

COUNTERBORE SET

The General Services Administration has authorized the use of this commercial item description.

Salient characteris..cs:

Consists of 2 counterbore holders, 13 cutters for counterboring and spotfacing, and 17 pilots for guiding the cutters. The two holders shall be interchangeable with their respective cutters and pilot subassemblies. The cutter and pilot subassemblies shall be hand detachable. A means shall be provided for securing the pilots to the cutters.

Counterbore holders. Each set shall be provided with one straight shank counterbore holder and one taper shank counterbore holder. The holders shall be of the following nominal dimensions:

Range of cutters (inches)	Shank (inches)	Diameter of body (inches)	Overall length (inches)
1/4 to 1/2	1/2 inch diameter	3/4	4-7/8
1/2 to 1	No. 2 Morse Taper	1	5-1/16

Material for holders shall be steel, heat treated to Rockwell C 50-60.

Cutters. Set shall be provided with five cutters for use with the No. 1 holder and eight cutters for use with the No. 2 holder. Cutters shall have a minimum of three helical flutes and shall be of the following nominal dimensions:

No. 1 holder.

Diameter of cutter (inches)	Diameter of hole for pilot shank (inches)	Overall length (inches)	Length of cutter (inches)
1/4	1/8	2-1/4	1-1/8
5/16	1/8	2-1/4	1-1/8
3/8	1/8	2-1/4	1-1/8
7/16	1/8	2-1/4	1-1/8
1/2	1/8	2-1/4	1-1/8
	No. 2 holder.		
9/16	1/4	2-1/2	1-3/8
5/8	1/4	2-1/2	1-3/8
11/16	1/4	2-1/2	1-3/8
3/4	1/4	2-1/2	1-3/8
13/16	1/4	2-1/2	1-3/8
7/8	1/4	2-1/2	1-3/8
15/16	1/4	2-1/2	1-3/8
1	1/4	2-1/2	1-3/8

Material for cutters shall be high speed steel, heat treated to Rockwell C 63-66.

Pilots. Set shall contain one each of the following 17 pilots:

Diameter of pilot (inches)	Diameter of shank (inches)	Length of head (inches)
1/8	1/8	3/8
5/32	1/8	3/8
3/16	1/8	3/8
7/32	1/8	3/8
1/4	1/8	3/8
9/32	1/8	3/8
5/16	1/8	3/8
3/8	1/8	3/8
7/16	1/8	3/8
1/4	1/4	1/2
5/16	1/4	1/2
3/8	1/4	1/2
7/16	1/4	1/2
1/2	1/4	5/8
9/16	1/4	5/8
5/8	1/4	5/8
3/4	1/4	3/4

FSC 5133

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.

Material for pilots shall be steel, heat treated to Rockwell C 50-60.

Marking. All holders, cutters, and pilots shall be legibly and permanently marked with the applicable size a with the manufacturer's name or trademark of such known character that the source of manufacturer may be reac determined.

Each counterbore set shall be furnished in a well-constructed box with cover and a separate compartment each item.

Workmanship. All components of the set shall be free from rust, burrs, fins, scale, or any defects which m affect serviceability, durability, or appearance.

Certification. The contractor shall certify that the product offered meets the salient characteristics of t description and that the product conforms to the producer's own drawings, specifications, standards, and qual assurance practices and is the same product offered for sale in the commercial marketplace. The Governm reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherw provided for under the provisions of the contract.

Recovered materials. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Preservation, packaging, packing, and marking. Each set, with accessory parts, shall be preserved and packagec accordance with normal commercial practice and packed to assure acceptance by common carrier and prov product protection against loss and damage during multiple shipments, handling, and storage. The shipping contai shall be in compliance with National Motor Freight Classification and Uniform Freight Classification. Marking sh be in accordance with the contract or order.

Note: Assigned National Stock Number (NSN) 5133-00-378-3813.

GSA DC-01001765

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.