
USER SYMBOLS:

REVIEWER SYMBOLS:
NAVY - SH
AF - 99
ARMY -
DLA - JS

"Review/user information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS."

This military standard is approved for use by all Departments & Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

FED. SUP CLASS
5310



REQUIREMENTS:

1. MATERIAL:	CORROSION RESISTANT STEEL PER MIL-S-5059 OR MIL-S-6721	-C CODE
	ALUMINUM ALLOY PER QQ-A-250/5, CONDITION T3 OR T4	-D CODE
2. COATING:	PASSIVATION PER QQ-P-35 (FOR UNCOATED CRES)	-NO CODE
	BLACK OXIDE COAT PER MIL-C-13924 (FOR CRES)	-Y CODE
	CHEMICAL CONVERSION PER MIL-C-5541, CLASS 3 (ALUMINUM ALLOY)	-J CODE
	ANODIZE PER MIL-A-8625 (ALUMINUM ALLOY)	-K CODE

APPROVED 24 SEPT 1987 REVISED

P.A.
NAVY — AS
Other Cust
AF-11
ARMY-AV

PROCUREMENT SPECIFICATION
FF-W-92

TITLE
WASHERS, FLAT, FOR OVERSIZE FASTENERS AND FASTENER SLEEVES

SUPERSEDES:

MILITARY STANDARD
MS14226
SHEET 1 OF 3

DD FORM 1 MAR 72 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

PLATE NO. 27000

PROJECT NO. 5310-1223

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:37Z
Check the source to verify that this is the current version before use.

REVIEWER SYMBOLS:
NAVY - SH
AF - 99
ARMY - MI
DLA - IS

USER SYMBOLS:

Review/user information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS.

This military standard is approved for use by all Departments & Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

TABLE I. WASHERS FOR 1/64 OVERSIZE FASTENERS AND FASTENER SLEEVES

SIZE PIN (OR SLEEVE)	A DIA. +.005 -.000	D DIA. +.020 -.005	T	DASH NUMBERS			
				COR. RESIST. STEEL		ALUMINUM ALLOY	
				UNCOATED	COATED	CHEM. CONV. COATING	ANODIZED SURFACES
NO. 8 (.185)	.190	.375	.032	L64C8	L64YC8	L64JD8	L64KD8
NO. 10 (.210)	.215	.438	.032 .063	L64C10 64C10	L64YC10 64YC10	64JD10	64KD10
1/4 (.270)	.275	.500	.032 .063	L64C416 64C416	L64YC416 64YC416	64JD416	64KD416
5/16 (.333)	.338	.562	.032 .063	L64C516 64C516	L64YC516 64YC516	64JD516	64KD516
3/8 (.395)	.400	.625	.032 .063	L64C616 64C616	L64YC616 64YC616	64JD616	64KD616
7/16 (.458)	.463	.750	.032 .063	L64C716 64C716	L64YC716 64YC716	64JD716	64KD716
1/2 (.520)	.525	.875	.032 .063	L64C816 64C816	L64YC816 64YC816	64JD816	64KD816

TABLE II. WASHERS FOR 1/32 OVERSIZE FASTENERS AND FASTENER SLEEVES

SIZE PIN (OR SLEEVE)	A DIA. +.005 -.000	D DIA. +.020 -.005	T	DASH NUMBERS			
				COR. RESIST. STEEL		ALUMINUM ALLOY	
				UNCOATED	COATED	CHEM. CONV. COATING	ANODIZED SURFACES
NO. 8 (.200)	.205	.375	.032	L32C8	L32YC8	L32JD8	L32KD8
NO. 10 (.226)	.231	.438	.032 .063	L32C10 32C10	L32YC10 32YC10	32JD10	32KD10
1/4 (.286)	.291	.500	.032 .063	L32C416 32C416	L32YC416 32YC416	32JD416	32KD416
5/16 (.348)	.353	.562	.032 .063	L32C516 32C516	L32YC516 32YC516	32JD516	32KD516
3/8 (.411)	.416	.625	.032 .063	L32C616 32C616	L32YC616 32YC616	32JD616	32KD616
7/16 (.474)	.479	.750	.032 .063	L32C716 32C716	L32YC716 32YC716	32JD716	32KD716
1/2 (.536)	.541	.875	.032 .063	L32C816 32C816	L32YC816 32YC816	32JD816	32KD816

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:37Z
Check the source to verify that this is the current version before use.

REVIEWER SYMBOLS:
NAVY - SH
AF - 99
ARMY - IS
DLA - IS

USER SYMBOLS:

"Review/user information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS."

This military standard is approved for use by all Departments & Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

FED. SUP CLASS
5310

NOTES:

1. REMOVE ALL BURRS AND SHARP EDGES.
2. DIMENSIONS IN INCHES.
3. TOLERANCES ON:

   THICKNESS: .032 ± .004; .063 ± .006

   ALL OTHER DIMENSIONS: ± .010
4. SURFACE CHARACTERISTICS:

   WASHER FACES SHALL BE PARALLEL WITHIN .002 INCH.

   WASHER FACES SHALL BE FLAT WITHIN .007 INCH.
5. "J" CODE WASHERS WHEN LOW ELECTRICAL RESISTANCE REQUIRED.
6. "K" CODE WASHERS WHERE CORROSION PROTECTION PRIME CONSIDERATION.
7. EXAMPLE OF PART NUMBER:

MS14226 L 64 Y C 516 = WASHER, FLAT, LIGHT SERIES, 1/64 OVERSIZE, BLACK OXIDE COAT, CRES, FOR 5/16 DIA PIN (OR SLEEVE)

- 516 — PIN SIZE (5/16 DIA. PIN)
- C — MATERIAL CODE (SEE REQ. 1 AND TABLE 1)
- Y — COATING CODE (SEE REQ. 2)
- 64 — OVERSIZE (64 DENOTES 1/64 OVERSIZE) (32 DENOTES 1/32 OVERSIZE)
- L — "-" DENOTES REGULAR SERIES; "L" DENOTES LIGHT SERIES
- MS14226 — MS NUMBER

8. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BIDS, OR REQUEST FOR PROPOSAL EXCEPT THAT REFERENCED ADOPTED INDUSTRY DOCUMENTS SHALL GIVE THE DATE OF THE ISSUE ADOPTED.
9. FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.

REVISED

APPROVED

P.A. NAVY — AS Other Cust AF-11 ARMY-AV	TITLE: WASHERS, FLAT, FOR OVERSIZE FASTENERS AND FASTENER SLEEVES	MILITARY STANDARD MS14226
PROCUREMENT SPECIFICATION FF-W-92	SUPERSEDES:	SHEET 3 OF 3

DD FORM 1 MAR 72 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

PLATE NO. 23000

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:37Z
Check the source to verify that this is the current version before use.