INCH-POUND
MS21434C
5 October 2011
SUPERSEDING
MS21434B
10 December 1981

DETAIL SPECIFICATION SHEET

SWITCHES, TOGGLE, POSITIVE BREAK, MINIATURE, TOGGLE SEALED, DOUBLE POLE, PRINTED CIRCUIT BOARD TERMINALS, RIGHT ANGLE MOUNT

Inactive for new design after 5 October 2011

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the products described herein shall consist of this specification sheet and MIL-DTL-8834.




FIGURE 1. Dimensions and configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:39Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm		
.003	0.08	.024	0.61	.110	2.79	.250	6.35
.004	0.10	.025	0.64	.150	3.81	.319	8.10
.005	0.13	.045	1.14	.160	4.06	.420	10.67
.010	0.25	.067	1.70	.170	4.32	.440	11.18
.015	0.38	.093	2.36	.200	5.08	.500	12.70
.020	0.51	.100	2.54	.220	5.59	.556	14.12
						.572	14.53

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are ±.010 (0.25 mm) on decimals and ±5° on angles.
4. Terminals need not be marked. Terminal identification is shown for reference purposes only.

FIGURE 1. Dimensions and configuration - Continued.

REQUIREMENTS:

For design feature purposes, this specification sheet takes precedence over acquisition documents referenced herein.

115 V ac 60 hertz electrical endurance tests are to be performed at room temperature and pressure.

Switches shall be rigidly mounted to the shock test equipment by means of their terminals and subjected to shock tests, method 207, of MIL-STD-202. The switch shall be electrically and mechanically operative at the conclusion of the test and there shall be no mechanical transfer during the test.

Terminals: Gold plated.

Weight: .0234 pound maximum (8.75 grams).

Terminal strength: Terminals shall be subjected to a five-pound pull for 5 to 10 seconds with the long dimension of the terminal contact vertical. The force shall be applied to the terminal at a point .06 inch (1.5 mm) below the bottom of the switch base, and in a direction parallel to the axis of the toggle lever in its center position. Two outboard terminals shall be tested. However, a terminal shall be tested only once in one direction.

Altitude: 50,000 feet.

Strength of actuator. Lever pivot and lever stop 6 pounds.

Mounting bracket: Brass, tin plated, or coated.

For hardware detail specifications, see appendix of MIL-DTL-8834.

MS dash number -321, -331, -341, and -351, dielectric withstanding voltage: 1,200 V rms at sea level.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:39Z
Check the source to verify that this is the current version before use.

TABLE I. Detail requirements.

MS dash no.	Circuit made between terminals as indicated with the toggle lever in these positions: 2/			Current capacity in amperes						Life, low current level switching 5 mV
				Resistive load			Inductive load			
				28 volts dc	115 volts		28 volts dc	115 volts		
	Opposite locking tab side 5/	Center position	Locking tab side 5/		60 Hertz ac	400 Hertz ac		60 Hertz ac	400 Hertz ac	
-211	on 2-3, 5-6	off	on 1-2, 4-5	5	2	3	1 3/	1	2	25 µA 3/
-221		none	off							
-231			on 1-2, 4-5							
-241		off	none							
-271	mom-on 2-3, 5-6		mom-on 1-2, 4-5							
-281	none									
-311	on 2-3, 5-6									
-331 1/	on 2-3, 5-6	on 2-3, 4-5	on 1-2, 4-5							
-341 1/	mom-on 2-3, 5-6	on 2-3, 4-5	mom-on 1-2, 4-5							
-321 1/	none	on 2-3. 5-6	mom-on 1-2, 4-5							
-351 1/	on 2-3, 5-6	on 2-3, 4-5	mom-on 1-2, 4-5							

1/ Delayed action of the switch toggle lever may cause circuit to close or open before snap action mechanism trips.
2/ Direction of movement of internal mechanism is opposite to the direction of the toggle movement.
3/ With time constant of .020 ±.002 second.
4/ Contact resistance not to exceed 50Ω during life, low current level switching.
5/ Non-functional terminals shall not be supplied.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:39Z
Check the source to verify that this is the current version before use.

Referenced documents:
MIL-DTL-8834
MIL-STD-202

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - CR
Navy - AS
Air Force - 85
DLA - CC

Review activities:
Army - AR, AT, AV, MI
Navy - EC
Air Force - 99

Preparing activity:
DLA – CC

(Project 5930-2011-080)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:39Z
Check the source to verify that this is the current version before use.