
FED. SUP CLASS
5305



NOMINAL SIZE	D		2 (.086)	4 (.112)	6 (.138)	8 (.164)
THREADS PER INCH			56NC	40NC	32NC	32NC
BODY DIAMETER	D_e	Max	.0860	.1120	.1380	.1640
		Min	.0717	.0925	.1141	.1399
HEAD DIAMETER	A	Max	.140	.183	.226	.270
		Min	.124	.166	.208	.250
HEAD HEIGHT	H	Max	.062	.079	.096	.113
		Min	.055	.072	.089	.106
TOTAL HEAD HEIGHT	O	Max	.083	.107	.132	.156
		Min	.070	.094	.118	.141
SLOT WIDTH	J	Max	.031	.039	.048	.054
		Min	.023	.031	.039	.045
SLOT DEPTH	T	Max	.030	.038	.045	.065
		Min	.022	.030	.035	.054
NOMINAL DRILL LOCATION	E		.026	.035	.043	.043
NOMINAL DRILL SIZE			.031	.037	.046	.046
RADIUS	R	Max	.013	.018	.023	.023

LENGTH	L	Tolerance	Dash Number	Dash Number	Dash Number	Dash Number
THREADS SHALL EXTEND TO WITHIN 2 THREADS OF THE BEARING SURFACE OF THE HEAD, OR CLOSER IF PRACTICABLE.	1/8	+0 -1/32	1	11	24	39
	3/16		2	12	25	40
	1/4		3	13	26	41
	5/16		4	14	27	42
	3/8		5	15	28	43
	7/16		6	16	29	44
	1/2		7	17	30	45
	5/8		8	18	31	46
	3/4		9	19	32	47
	7/8		10	20	33	48
	1			21	34	49
	1-1/4	+0 -1/16		22	35	50
	1-1/2			23	36	51
	1-3/4				37	52
	2				38	53
Minimum Complete Thread Length of 1-3/4.	2-1/4	+0 -3/32				54
	2-1/2					55
	2-3/4					56
	3					57

MATERIAL: Brass, Specification QQ-B-611 or QQ-W-321.

FINISH: Plain (untreated).

THREADS: The threads shall be in accordance with Screw-Thread Standards for Federal Services Handbook H-28.

NOTES: (1) Referenced documents of issue in effect on date of invitation for bids shall apply.
(2) In case of conflict with any referenced document, this standard will govern.
(3) The MS part number consists of the MS sheet number, plus the dash number. Example: MS 35271-1.
(4) Drilled hole to be on center approximately at right angle to the slot but must not break through the base or top (spherical portion) of the head.
(5) Screws shall be free of all loose or hanging burrs or slivers which might become dislodged under usage.
(6) All dimensions in inches.

Ⓐ CANCELLED
SEE SHEET 2

Ⓐ For changes see sheets 1 and 2.

APPROVED FEB 9, 1954 REVISED Ⓐ 29 JULY 1965

NOTICE.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This military standard is approved by the Department of Defense and is mandatory on all activities. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A.	WC
Other Cust	SH 69

TITLE: SCREW, MACHINE, DRILLED FILLISTER HEAD, SLOTTED, BRASS, PLAIN FINISH, NC-2A AND UNC-2A

MILITARY STANDARD
MS 35271

PROCUREMENT SPECIFICATION: FF-S-92

SUPERSEDES:

SHEET 1 OF 2

DD FORM SEP 67 672-1 (Coordinated)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:12Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS 5305

NOMINAL SIZE	D		10 (.190)	1/4	5/16	3/8
THREADS PER INCH			24NC	20UNC	18UNC	16UNC
BODY DIAMETER	D_e	Max	.1900	.2500	.3125	.3750
		Min	.1586	.2127	.2712	.3287
HEAD DIAMETER	A	Max	.313	.414	.518	.622
		Min	.292	.389	.490	.590
HEAD HEIGHT	H	Max	.130	.170	.211	.253
		Min	.123	.161	.201	.242
TOTAL HEAD HEIGHT	O	Max	.180	.237	.295	.355
		Min	.165	.219	.276	.333
SLOT WIDTH	J	Max	.060	.075	.084	.094
		Min	.050	.064	.072	.081
SLOT DEPTH	T	Max	.075	.102	.130	.154
		Min	.064	.087	.110	.134
NOMINAL DRILL LOCATION	E		.043	.062	.078	.094
NOMINAL DRILL SIZE			.046	.062	.070	.070
RADIUS	R	Max	.031	.025	.027	.031
LENGTH	L	Tolerance	Dash Number	Dash Number	Dash Number	Dash Number
THREADS SHALL EXTEND TO WITHIN 2 THREADS OF THE BEARING SURFACE OF THE HEAD, OR CLOSER IF PRACTICABLE	1/8	+0 -1/32	58			
	3/16		59			
	1/4		60	76		
	5/16		61	77	92	
	3/8		62	78	93	
	7/16		63	79	94	107
	1/2		64	80	95	108
	5/8		65	81	96	109
	3/4		66	82	97	110
	7/8		67	83	98	111
	1		68	84	99	112
	1-1/4	+0 -1/16	69	85	100	113
	1-1/2		70	86	101	114
	1-3/4		71	87	102	115
	2		72	88	103	116
Minimum Complete Thread Length of 1-3/4.	2-1/4	+0 -3/32	73	89	104	117
	2-1/2		74	90	105	118
	2-3/4		75	91	106	119
	3					

NOTE: For illustration, material, finish, and other pertinent data, see sheet 1.

(A) CANCELLED AFTER 29 JULY 1965. USE MS35273. INTERCHANGEABILITY RELATIONSHIP - MS35273 can replace the cancelled screws of the same size. The cancelled MS35271 cannot always replace MS35273 and should be used until existing stock is depleted. Then use only the superseding MS screws of the same size for design and replacement.

(A) CANCELLED
SEE NOTE

APPROVED FEB 9, 1954 REVISED (A) FOR CHANGES SEE SHEETS 1 AND 2.

NOTICE—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This military standard is approved by the Department of Defense and is mandatory on all activities. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A.	WC
Other Cust	SH 69

TITLE: SCREW, MACHINE, DRILLED FILLISTER HEAD, SLOTTED, BRASS, PLAIN FINISH, NC-2A AND UNC-2A

MILITARY STANDARD

MS 35271

PROCUREMENT SPECIFICATION: FF-S-92

SUPERSEDES:

SHEET 2 OF

DD FORM 672-1 (SEP 67) (Coordinated)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:12Z
Check the source to verify that this is the current version before use.