
FED. SUP CLASS
4730



DASH NUMBER		TUBE OD	B	D		M
BODY	ASSY	NOM	STRAIGHT THREAD	DIAMETER BASIC	DIAMETER TOLERANCE	±.030
B2	A2	1/8	5/16-24 UNF-2A	.062	±.003	.770
B3	A3	3/16	3/8 -24 UNF-2A	.125		.830
B4	A4	1/4	7/16-20 UNF-2A	.172		.890
B5	A5	5/16	1/2 -20 UNF-2A	.234		.950
B6	A6	3/8	9/16-18 UNF-2A	.297	±.004	1.060
B8	A8	1/2	3/4 -16 UNF-2A	.391		1.250
B10	A10	5/8	7/8 -14 UNF-2A	.484		1.450
B12	A12	3/4	1-1/16-12 UN-2A	.609	±.005	1.660
B14	A14	7/8	1-3/16-12 UN-2A	.718		1.730
B16	A16	1	1-5/16-12 UN-2A	.844	+.007-.005	1.810
B20	A20	1-1/4	1-5/8 -12 UN-2A	1.078	+.008-.005	2.060
B24	A24	1-1/2	1-7/8 -12 UN-2A	1.312		2.330
B32	A32	2	2-1/2 -12 UN-2A	1.781	+.010-.005	3.060

NOTES:
1. MATERIAL: Steel, carbon in accordance with procurement specification.
   Steel, corrosion-resisting in accordance with procurement specification.
2. PROTECTIVE COATING: Cadmium plated in accordance with procurement specification.
   Zinc plated in accordance with procurement specification.
   Phosphate coating in accordance with procurement specification.
   Passivation treatment in accordance with procurement specification.
3. DIMENSIONS AND TOLERANCES: Dimensions and tolerances not shown shall be in accordance with the SAE Standards for 37 Degree Flared Fittings (SAE J514).
4. THREADS: Threads shall be in accordance with Screw-Thread Standards for Federal Services, Handbook H28.
5. PART NUMBER: The MS part number consists of the MS number plus the dash number.
   A. For body only, cadmium plated, use the MS number, plus the body dash number. Example: MS51510B2.
   B. For complete assembly (with nuts and sleeves), cadmium plated, use the MS number, plus the assembly dash number. Example: MS51510A2.
   C. For zinc coating add (Z) to the dash number. Example: MS51510B2Z or MS51510A2Z.
   D. For phosphate coating add (P) to the dash number. Example: MS51510B2P or MS51510A2P.
   E. For corrosion-resisting steel add (S) to the dash number. Example: MS51510B2S or MS51510A2S.
6. For design feature purposes, this standard takes precedence over procurement documents referenced herein.
7. Reference documents shall be of the issue in effect on date of invitations for bid.
8. The illustration is for identification and is not intended to restrict designs or shapes not dimensioned.
9. (A) After 17 January 1979 bodies will be used for production only and SHALL NOT be stocked for maintenance. Existing stock of bodies should be used until depleted.

REVIEWER: CS-EL-ME
USER: AT-MC-YD

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

APPROVED 20 DEC 1971 REVISED (A) 17 JANUARY 1979

P.A. AR Other Cust OS	TITLE TEE, TUBE, 37°FLARED	MILITARY STANDARD MS51510
PROCUREMENT SPECIFICATION MIL-F-18866	SUPERSEDES:	SHEET 1 OF 1

DD FORM 1 SEP 67 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:04Z
Check the source to verify that this is the current version before use.