
FED SUP CLASS
5306





SECTION THRU THREAD PROFILE

TABLE I. Dash numbers and dimensions.

DASH NO.	L	K	APPROX WEIGHT LB/100
-04	.375	.079-.099	1.14
-05	.438	.079-.099	1.21
-06	.500	.079-.099	1.29
-07	.562	.079-.099	1.36
-08	.625	.079-.099	1.44
-09	.688	.079-.099	1.51
-10	.750	.079-.099	1.58
-11	.812	.079-.099	1.65
-12	.875	.079-.125	1.72
-13	.938	.128-.188	1.79
-14	1.000	.190-.250	1.86
-15	1.062	.252-.312	1.93
-16	1.125	.315-.375	2.00
-17	1.188	.378-.438	2.08
-18	1.250	.440-.500	2.15
-19	1.312	.502-.562	2.22
-20	1.375	.565-.625	2.29
-21	1.438	.628-.688	2.36
-22	1.500	.690-.750	2.43
-23	1.562	.752-.812	2.50
-24	1.625	.815-.875	2.57
-25	1.688	.878-.938	2.64
-26	1.750	.940-1.000	2.72
-27	1.875	1.065-1.125	2.86
-28	2.000	1.190-1.250	3.00
-29	2.125	1.315-1.375	3.14
-30	2.250	1.440-1.500	3.29
-31	2.375	1.565-1.625	3.43
-32	2.500	1.690-1.750	3.57
-33	2.625	1.815-1.875	3.71
-34	2.750	1.940-2.000	3.85
-35	2.875	2.065-2.125	4.00
-36	3.000	2.190-2.250	4.14
-37	3.125	2.315-2.375	4.29
-38	3.250	2.440-2.500	4.43
-39	3.375	2.565-2.625	4.58
-40	3.500	2.690-2.750	4.72
-41	3.625	2.815-2.875	4.85
-42	3.750	2.940-3.000	4.99
-43	3.875	3.065-3.125	5.13
-44	4.000	3.190-3.250	5.27
-45	4.125	3.315-3.375	5.42
-46	4.250	3.440-3.500	5.56
-47	4.375	3.565-3.625	5.71
-48	4.500	3.690-3.750	5.85
-49	4.625	3.815-3.875	6.00
-50	4.750	3.940-4.000	6.14
-51	4.875	4.065-4.125	6.29
-52	5.000	4.190-4.250	6.43
-53	5.125	4.315-4.375	6.56
-54	5.250	4.440-4.500	6.70
-55	5.375	4.565-4.625	6.84
-56	5.500	4.690-4.750	6.99
-57	5.625	4.815-4.875	7.13
-58	5.750	4.940-5.000	7.28
-59	5.875	5.065-5.125	7.42
-60	6.000	5.190-5.250	7.57
-61	1.812	1.002-1.062	2.79
-62	1.938	1.128-1.188	2.93

(B) ENTIRE STANDARD REDRAWN

APPROVED 16 DEC 65 REVISED (B) 30 SEPT 89

P.A. NAVY - AS Other Cust ARMY - AV	INTERNATIONAL INTEREST	TITLE BOLT, MACHINE-DOUBLE HEXAGON EXTENDED WASHER HEAD, DRILLED, PD SHANK, SILVER PLATED, .250-28 UNJF-3A.	MILITARY STANDARD MS9575
PROCUREMENT SPECIFICATION NONE	SUPERSEDES:		PAGE 1 OF 2

DD FORM 672-1 (OBSOLETE) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE. 5306-1244

USER ACTIVITIES:

REVIEWER ACTIVITIES:
ARMY-AR
AIR FORCE-82,85
DLA-IS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.


AMSC N/A

Source: https://assist.dla.mil -- Downloaded: 2026-10-23113:202
Check the source to verify that this is the current version before use.

REQUIREMENTS:

1. MATERIAL: CORROSION AND HEAT RESISTANT STEEL IN ACCORDANCE WITH AMS 5731 (UNS S66286).
2. FLUORESCENT PENETRANT INSPECTION: FLUORESCENT PENETRANT INSPECTION IN ACCORDANCE WITH AMS 2645 BEFORE PLATING.
3. FINISH: SILVER PLATE IN ACCORDANCE WITH AMS 2411 .0002-.0006 THICK AT THREAD PD. DIMENSIONS SPECIFIED ARE AFTER PLATING. PD MAY BE REDUCED .0012 MAXIMUM BEFORE PLATING.
4. THREADS: THREADS IN ACCORDANCE WITH MIL-S-8879. INCOMPLETE THREADS NOT TO ENTER FILLET.
5. MANUFACTURING: MANUFACTURE IN ACCORDANCE WITH AMS 7477.
6. DIMENSIONING AND TOLERANCING: DIMENSIONING AND TOLERANCING SHALL BE IN ACCORDANCE WITH ANSI Y14.5M.
7. EDGES: BREAK SHARP EDGES .003-.015 UNLESS OTHERWISE SPECIFIED.
8. SURFACE TEXTURE: SURFACE TEXTURE IN ACCORDANCE WITH ANSI/ASME B46.1. UNLESS OTHERWISE SPECIFIED, SURFACES TO BE 125 MICROINCHES EXCEPT UPSET HEAD.
9. TOLERANCING: UNLESS OTHERWISE SPECIFIED, TOLERANCES SHALL BE FOR LINEAR DIMENSIONS ±.010, ANGULAR DIMENSIONS ±5°.
10. WRENCHING CONFIGURATION: WRENCHING CONFIGURATION IN ACCORDANCE WITH AS 870.
11. MARKING: MARK PART NUMBER AND MANUFACTURER'S IDENTIFICATION IN ACCORDANCE WITH AS 478 CLASS A.
12. PART NUMBER: THE PART NUMBER SHALL CONSIST OF THE BASIC MS PART NUMBER FOLLOWED BY A DASH NUMBER FROM TABLE I.

EXAMPLE: MS9575-04



MS9575-04 INDICATES: BOLT, MACHINE - DOUBLE HEXAGON EXTENDED WASHER HEAD, DRILLED, PD SHANK, AMS 5731, SILVER PLATED, .250-28 UNJF-3A X .375 LONG.

NOTES:

1. ALL DIMENSIONS ARE IN INCHES.
2. DO NOT USE UNASSIGNED PART NUMBERS.
3. IN THE EVENT OF A CONFLICT BETWEEN IN THE TEXT OF THIS STANDARD AND THE REFERENCES CITED HEREIN, THE TEXT OF THIS STANDARD SHALL TAKE PRECEDENCE.
4. REFERENCED GOVERNMENT (OR NONGOVERNMENT) DOCUMENTS OF THE ISSUE LISTED IN THAT ISSUE OF THE DEPARTMENT OF DEFENSE INDEX OF SPECIFICATIONS AND STANDARDS (DoDISS) SPECIFIED IN THE SOLICITATION FORM A PART OF THIS STANDARD TO THE EXTENT SPECIFIED.
5. THIS STANDARD WAS DEVELOPED COOPERATIVELY WITH THE SAE AEROSPACE PROPULSION DIVISION.
6. AS AND AMS ARE SAE PUBLICATIONS.

USER ACTIVITIES:
REVIEWER ACTIVITIES:
ARMY-AR
AIR FORCE - 82,85
DLA-IS
This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

APPROVED 16 DEC 65 REVISED (8) FOR CHANGES SEE PAGES 1 AND 2

P.A. NAVY - AS Other Cust ARMY - AV	INTERNATIONAL INTEREST	TITLE BOLT, MACHINE-DOUBLE HEXAGON EXTENDED WASHER HEAD, DRILLED, PD SHANK, SILVER PLATED, .250-28 UNJF-3A.	MILITARY STANDARD MS9575
PROCUREMENT SPECIFICATION NONE	SUPERSEDES:		PAGE 2 OF 2

Source: https://assist.dla.mil — Downloaded: 2026-10-23T13:20Z
Check the source to verify that this is the current version before use.