MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, CERAMIC DIELECTRIC (GENERAL PURPOSE), ESTABLISHED RELIABILITY STYLES CKR25, CKR26, AND CKR27

This amendment forms a part of Military Specification MIL-C-39014/25, dated 16 October 1984, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Resistance to soldering heat: Delete "ΔC +20, -0 percent from initial measured value" and substitute "ΔC +15, -5 percent of the initial 25°C measurement."

PAGE 3

Marking, first sentence, delete and substitute:

"In accordance with MIL-C-39014 except that minimum marking as shown in the following example will be permitted for styles CKR25, CKR26 and CKR27."

Following Marking, add: "For similar voltage, capacitance and size molded capacitors, see MIL-C-39014/5, styles CKR11, CKR12 and CKR14."

Custodians:
Army - ER
Navy - EC
Air Force - 11

Review activities:
Army - AR, MI
Navy - EC
Air Force - 17, 85
DLA - ES

User activities:
Army - AT, AV, ME
Navy - MC
Air Force - 19

Agent:
DLA - ES

Preparing activity:
Army - ER

(Project 5910-1542-8)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:29Z
Check the source to verify that this is the current version before use.

FSC 5910