MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, CERAMIC DIELECTRIC
(GENERAL PURPOSE),
ESTABLISHED RELIABILITY
STYLE CKR04

This amendment forms a part of Military Specification MIL-C-39014/23, dated 7 December 1977, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

* Resistance to soldering heat: Delete "ΔC - +20, -0 percent from initial measured value" and substitute "ΔC - +15, -5 percent of the initial 25°C measurement."

Under Life, line 2: Delete "2,000" and substitute "3,000".

NOTE: The margin of this amendment is marked with an asterisk to indicate where changes from the previous amendment was made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - ER
Navy - EC
Air Force - 11
NASA - NA

Review activities:
Army - AR, MI
Navy - EC
Air Force - 11, 17, 85, 99
DLA - ES

User activities:
Army - AT, AV, ME
Navy - MC
Air Force - 19

Agent:
DLA - ES

Preparing activity:
Army - ER

(Project 5910-1542-6)

FSC 5910

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21 17:28Z
Check the source to verify that this is the current version before use.