INCH-POUND

MIL-PRF-39016J
SUPPLEMENT 1A
25 March 2025
SUPERSEDING
SUPPLEMENT 1
13 January 2023

PERFORMANCE SPECIFICATION

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY,
GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-PRF-39016J w/AMENDMENT 1, dated 25 March 2025.

SPECIFICATION SHEETS

MIL-PRF-39016/6	-	Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 2 Amperes (0.200-Inch Terminal Spacing)
MIL-PRF-39016/7	-	Relays, Electromagnetic, Established Reliability, SPDT, Low Level to 1.0 Ampere
MIL-PRF-39016/8	-	Relays, Electromagnetic, Established Reliability, SPDT, Low Level to 0.5 Ampere (Latching)
MIL-PRF-39016/9	-	Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 1.0 Ampere
MIL-PRF-39016/10	-	Relays, Electromagnetic, Established Reliability, SPDT, Low Level to 1.0 Ampere (Sensitive, 40 Milliwatts, Coil Operate Power at 25°C)
MIL-PRF-39016/11	-	Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 1.0 Ampere (Sensitive, 60 Milliwatts, Coil Operate Power at 25°C)
MIL-PRF-39016/12	-	Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 1.0 Ampere (Latching)
MIL-PRF-39016/13	-	Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 2 Amperes (0.150-Inch Terminal Spacing)
MIL-PRF-39016/14	-	Relays, Electromagnetic, Established Reliability, 4PDT, Low Level to 2 Amperes (0.150-Inch Terminal Spacing)
MIL-PRF-39016/15	-	Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 1.0 Ampere with Internal Diode for Coil Transient Suppression
MIL-PRF-39016/16	-	Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 1.0 Ampere (Sensitive, 60 Milliwatts) with Internal Diode for Coil Transient Suppression
MIL-PRF-39016/17	-	Relays, Electromagnetic, Established Reliability, DPDT, Low Level TO 1 Ampere Terminals 0.100-Inch Grid Pattern
MIL-PRF-39016/18	-	Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 1.0 Ampere, with Internal Diode for Coil Transient Suppression, Terminals 0.100-Inch Grid Pattern
MIL-PRF-39016/19	-	Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 1 Ampere with Internal Diode for Coil Transient Suppression and Polarity Reversal Protection, Terminals 0.100-Inch Grid Pattern
MIL-PRF-39016/20	-	Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 1.0 Ampere with Internal Diodes for Coil Transient Suppression and Polarity Reversal Protection
MIL-PRF-39016/21	-	Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 1.0 Ampere (Sensitive, 60 Milliwatts) with Internal Diodes for Coil Transient Suppression and Polarity Reversal Protection
MIL-PRF-39016/22	-	Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 2 Amperes (0.200-Inch Terminal Spacing) Coil Transient Suppressed
MIL-PRF-39016/23	-	Relays, Electromagnetic, Established Reliability, SPDT, Low Level to 1.0 Ampere with Internal Diode for Coil Transient Suppression
MIL-PRF-39016/24	-	Relays, Electromagnetic, Established Reliability, SPDT, Low Level to 1.0 Ampere with Internal Diodes for Coil Transient Suppression and Polarity Reversal Protection
MIL-PRF-39016/25	-	Relays, Electromagnetic, Established Reliability, SPDT, Low Level to 1.0 Ampere (Sensitive, 40 Milliwatts) with an Internal Diode for Coil Transient Suppression
MIL-PRF-39016/26	-	Relays, Electromagnetic, Established Reliability, SPDT, Low Level to 1.0 Ampere (Sensitive, 40 Milliwatts) with Internal Diodes for Coil Transient Suppression and Polarity Reversal Protection

AMSC N/A FSC 5945

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:30Z
Check the source to verify that this is the current version before use.

MIL-PRF-39016/27 - Relays, Electromagnetic, Established Reliability, SPDT, Low Level to 0.5 Ampere (Latching) with Internal Diodes for Coil Transient Suppression
MIL-PRF-39016/28 - Relays, Electromagnetic, Established Reliability, SPDT, Low Level to 0.5 Ampere (Latching) with Internal Diodes for Coil Transient Suppression and Polarity Reversal Protection
MIL-PRF-39016/29 - Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 1.0 Ampere (Latching) with Internal Diodes for Coil Transient Suppression
MIL-PRF-39016/30 - Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 1.0 Ampere (Latching) with Internal Diodes for Coil Transient Suppression and Polarity Reversal Protection
MIL-PRF-39016/31 - Relays, Electromagnetic, Established Reliability, Hermetically Sealed, 4 PDT, Low Level to 2 Amperes (0.150-Inch Terminal Spacing), Latching
MIL-PRF-39016/32 - Relays, Electromagnetic, DPDT, Low Level to 2 Amperes (Latching) (Inactive for new design after 4 August 1994.)
MIL-PRF-39016/35 - Relays, Electromagnetic, Established Reliability, Hermetically Sealed, 4 PDT Low Level to 2 Amperes (0.150-Inch Terminal Spacing), Latching, with Internal Diodes for Coil Transient Suppression
MIL-PRF-39016/36 - Relays, Electromagnetic, Established Reliability, Hermetically Sealed, 4PDT, Low Level to 2 Amperes (.150-Inch Terminal Spacing), Latching, with Internal Diodes for Coil Transient Suppression and Reverse Polarity Protection
MIL-PRF-39016/37 - Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 2 Amperes (0.150-Inch Terminal Spacing), with Internal Diode for Coil Transient Suppression
MIL-PRF-39016/38 - Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 2 Amperes (0.150-Inch Terminal Spacing), with Internal Diodes for Coil Transient Suppression and Reverse Polarity Protection
MIL-PRF-39016/39 - Relays, Electromagnetic, Hermetically Sealed, 4PDT, Low-Level to 3 Amperes (400 Milliwatts) (Inactive for new design after 4 August 1994.)
MIL-PRF-39016/40 - Relays, Electromagnetic, 4PDT, Low Level to 2.0 Amperes (0.100-Inch Terminal Spacing) (Inactive for new design after 29 January 1991.)
MIL-PRF-39016/41 - Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 1 Ampere, Terminals 0.100-Inch Grid Pattern (Sensitive, 60 Milliwatts, Coil Operate Power at 25°C)
MIL-PRF-39016/42 - Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 1.0 Ampere with Internal Diode for Coil Transient Suppression, Terminals 0.100-Inch Grid Pattern (Sensitive 60 Milliwatts, Coil Operate Power at 25°C)
MIL-PRF-39016/43 - Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 1.0 Ampere with Internal Diodes for Coil Transient Suppression, and Polarity Reversal Protection Terminal 0.100-Inch Grid Pattern (Sensitive, 60 Milliwatts, Coil Operate Power at 25°C)
MIL-PRF-39016/44 - Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 2 Amperes, Terminals 0.200-Inch Grid Pattern (Sensitive, 100/125 Milliwatts, Coil Operate Power at 25°C)
MIL-PRF-39016/45 - Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 2.0 Amperes (Latching)
MIL-PRF-39016/47 - Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 0.5 Ampere (.100 D.I.P. Terminal Spacing) One-Tenth Size, Sensitive, Bi-Stable, (Latching)
MIL-PRF-39016/48 - Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 0.5 Ampere (.100 D.I.P. Terminal Spacing) One-Tenth Size, Sensitive, Monostable
MIL-PRF-39016/53 - Relays, Electromagnetic, Established Reliability, Hermetically Sealed, 4PDT, Low Level to 2 Amperes (0.150-inch Terminal Spacing) with Internal Diode for Coil Transient Suppression
MIL-PRF-39016/54 - Relay, Electromagnetic, Established Reliability, Hermetically Sealed, 4PDT, Low Level to 2 Amperes (0.150-Inch Terminal Spacing), with Internal Diode for Coil Transient Suppression and Reverse Polarity Protection
MIL-PRF-39016/55 - Relay, Electromagnetic, Established Reliability, DPDT, Low Level to 2 Amperes (0.200-Inch Terminal Spacing), with Internal Diode for Coil Transient Suppression

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:30Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC
NASA - NA

Preparing activity:
DLA - CC

Review activities:
Army - MI
Navy - AS, MC, OS
Air Force - 19
Other – MDA

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:30Z
Check the source to verify that this is the current version before use.