INCH-POUND

MIL-S-64045/122 (AR)
16 October 2001

MILITARY SPECIFICATION SHEET

SCALE, GRAPHICAL FIRING, HE M483A1/M825A1, W/ICM, LOW ANGLE, (155-AN-2) CHARGE 5G, (P/N 11785434-143)

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring this item described here in shall consist of this document and the latest issue of Specification MIL-S-64045.

ACCURACY DATA

Charge	Range (meters)	Elevation (mils)	Drift (mils)	TF/FS (seconds)	FS/10m HOB (seconds)
	2500	114.0 ± 1	1.8 ± 1	7.8 ± .1	0.27
	3500	167.5 ± 1	2.7 ± 1	11.3 ± .1	0.19
	4500	225.9 ± 1	3.8 ± 1	14.9 ± .1	0.14
	6500	364.2 ± 1	6.6 ± 1	23.3 ± .1	0.09
	8000	506.9 ± 1	10.0 ± 1	31.4 ± .1	0.07

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:17Z
Check the source to verify that this is the current version before use.

ACCURACY DATA

Charge	Range (meters)	Elevation (mils)	FS (seconds)	Elevation (mils)	FS (seconds)
		M825A1		ICM 483A1	
5G	4000	213 ± 1	12.4 ± .1	232 ± 1	11.9 ± .1
	5000	270 ± 1	16.4 ± .1	284 ± 1	15.7 ± .1
	6000	336 ± 1	20.6 ± .1	347 ± 1	19.8 ± .1
		ICM 692/731		ICM 718/741	
	4500	358 ± 1	14.3 ± .1	240 ± 1	13.2 ± .1
	5500	395 ± 1	18.3 ± .1	302 ± 1	17.3 ± .1
	7000	488 ± 1	25.4 ± .1	413 ± 1	24.0 ± .1

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1220-0019)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:17Z
Check the source to verify that this is the current version before use.