INCH-POUND

MIL-S-64045/126 (AR)
16 October 2001

MILITARY SPECIFICATION SHEET

SCALE, GRAPHICAL FIRING, HE M483A1/M825A1, W/ICM,
HIGH ANGLE, (155-AN-2) CHGS 3G-4G-5G, (P/N 11785434-147)

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring this item described here in shall consist of this document and the latest issue of Specification MIL-S-64045.

ACCURACY DATA

Charge	Range (meters)	Elevation (mils)	TF (seconds)	FS/M577 (seconds)	Drift (mils)
3G	3500	1258.8 ± 1	48.3 ± .1	45.2 ± .1	101.1 ± I
	4200	1180.8 ± 1	46.7 ± .1	43.5 ± .1	60.2 ± I
	4800	1097.7 ± 1	44.8 ± .1	41.4 ± .1	43.7 ± 1
4G	4000	1291.0 ± 1	55.2 ± .1	52.6 ± .1	130.0 ± I
	5000	1208.2 ± 1	53.2 ± .1	50.6 ± .1	66.7 ± I
	6000	1101.2 ± 1	50.6 ± .1	47.8 ± .1	43.6 ± 1
5G	6500	1194.4 ± 1	60.0 ± .1	57.7 ± .1	63.4 ± 1
	7500	1108.1 ± 1	57.5 ± .1	55.2 ± .1	45.7 ± 1
	8500	988.7 ± 1	53.5 ± .1	51.0 ± .1	32.4 ± 1

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1220-0027)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:17Z
Check the source to verify that this is the current version before use.