MIL-C-60364 (MU)
AMENDMENT 1
9 September 1966

MILITARY SPECIFICATION

CARTRIDGE, 57MM, HE, M306A1
LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-C-60364 (MU), dated 30 March 1966.

Paragraph 2.1, SPECIFICATIONS, MILITARY: Delete "MIL-R-11471 - Radiographic Inspection of Metals".

Paragraph 2.1, STANDARDS, MILITARY: Add reference to "MIL-STD-453 - Inspection, Radiographic".

Paragraph 4.2.1, Lot formation: Delete the portion "A lot shall . . .MIL-STD-1168" and substitute the following:

"The term 'lot' as used throughout this specification refers to an inspection lot, which is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance of the lot with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the lot has been produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Changes to either the process, specification or drawing not affecting safety, performance, interchangeability or storage, as determined by the Government shall not be deemed to alter the homogeneity of the lot. Inspection lots shall comply with MIL-STD-105 and shall be numbered in accordance with MIL-STD-1168. Unless otherwise approved by the contracting officer, the inspection lot size of major assemblies or end items deliverable under the contract shall be not less than the smallest weekly estimate of quantities contractually scheduled for production during the contract period nor more than the largest monthly quantity contractually scheduled for delivery during the contract period. Inspection lots for components or subassemblies, other than the items of delivery, shall be homogeneous and of a size mutually convenient to both the contractor and the Government inspector."

FSC 1310

Source: https://assist.dla.mil -- Downloaded: 20261O-23T00:31Z
Check the source to verify that this is the current version before use.

Paragraph 4.2.1: Delete subparagraph "g" and substitute:
"g" High explosive from not more than two lots from one manufacturer."

Paragraph 4.2.2.3:
Line 1: Delete "Cartridge case of primer prior to assembly" and substitute "Primer, prior to assembly to cartridge case".
Minor category: Delete "AQL 1.0" and substitute "AQL 0.65".
Minor defect 201: Add "(see 3.7) . . . Visual 03003".

Paragraph 4.2.2.7:
Major category: Add new major defect 105 as follows:
"105. Crimp missing or inadequate (to extent that projectile is liable to separate) . . . Visual-Manual 07009".
Minor category: Delete "AQL 1.0" and substitute "AQL 1.5".
Minor category: Add new minor defect 204 as follows:
"204. Corrosion preventative compound missing from crimp . . . Visual 07010".

Paragraph 4.2.3.1, line 2: Delete "02005" and substitute "03004".

Paragraph 4.2.3.2: Delete entire paragraph and substitute the following:

"4.2.3.2 Cavitation (see 3.3 except 3.3.5 and dwg. 9215029) - Cavitation defects are classified as follows:

		Code No.
Critical:		
1.	Cavitation, cracks or annular rings in Segment A in excess of that permitted in Table I.	02006
2.	Cavitation, cracks or annular rings in Segment B in excess of twice that permitted in Table I.	02007
3.	Cracks in excess of that permitted by 3.3.3.	02008
4.	Base separation in excess of that permitted by 3.3.4.	02009
Minor:		
201.	Cavitation, cracks or annular rings in Segment B in excess of that permitted by Table I, but not more than twice that permitted by Table I.	02010

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:31Z
Check the source to verify that this is the current version before use.

The sampling plan and procedures for this test shall be in accordance with Standard MIL-STD-1235, using a CSP-A or a CSP-1 plan having an AQL of 0.015 percent for Critical defects and 1.5 percent for Minor defects. When applicable, the appropriate production interval shall be as specified by the procuring activity. The test shall be performed as specified in 4.3.1, using equipment in accordance with 4.2.4."

Paragraph 4.2.3.4: Delete Code No. "04005" and substitute "11001".

Paragraph 4.3.1.1: Delete reference to "Specification MIL-R-11471" and substitute "Standard MIL-STD-453".

Custodian:
Army-MU

Preparing activity:
Army-MU

Project No. 1310-A035

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:31Z
Check the source to verify that this is the current version before use.