INCH-POUND

MIL-F-63051A (AR)
AMENDMENT 2
27 July 1990
SUPERSEDING
AMENDMENT 1
11 August 1987

MILITARY SPECIFICATION

FUZE, M934 SERIES, ACTUATORS FOR

This Amendment forms a part of Military Specification MIL-F-63051A (AR) dated 1 July 1985, and is approved for use within the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

Delete paragraph 3.4.8.6 Moisture Resistance.

PAGE 8

Change the following under GROUP III Bruceton Analysis, subsection Test (All-Fire):

Test (All-Fire): Delete "-40" and substitute "40".

Delete note 5/

PAGE 12

Delete GROUP XIII in its entirety.

PAGE 15

4.4.2.2 Delete paragraph 4.4.2.2. (page 15) in its entirety and replace with a new sheet (enclosed as page 3 of this amendment).

PAGE 18

Delete paragraph 4.5.17 in its entirety.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:07Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in the notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire contents irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1336-A620)

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:07Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Actuator, Arming Actuator, Abort	1 of 1	9282665/9282666
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Environmental Exposure Sequence	1/	0.65%	3.4.8	
Major					
101	Mechanical Shock (Groups A&B) 2/		0.65%	3.4.8.2	4.5.9 (Visual)
102	Sinusoidal Vibration (Groups A&B) 2/		0.65%	3.4.8.3	4.5.10 (Visual)
103	Random Vibration (Groups A&B) 2/		0.65%	3.4.8.4	4.5.11 (Visual)
104	Acceleration (Groups A&B) 2/		0.65%	3.4.8.5	4.5.12 (Visual)
105	Lead-to-Lead Resistance (Pre-Fire) 2/		0.65%	3.4.3	4.5.3 (Ambient)
106	Insulation Resistance (Pre-Fire) 2/		0.65%	3.4.4	4.5.4 (Ambient)
107	No-Fire Characteristic (+140 F)		0.65%	3.4.5	4.5.5
108	All-Fire Characteristic/Exhibited Force (-50 F)		0.65%	3.4.6 3.4.7	4/5/6/4.5.7
109	Pin Protrusion/Retraction (Post-Fire)		0.65%	3.2	Gage
110	Insulation Resistance (Post-Fire)		0.65%	3.4.4.2	4.5.4 (+140 F)
111	Lead-to-Lead Resistance (Post-Fire) 3/		0.65%	3.4.3	4.5.16 (Ambient)

NOTES:

1/ Number of sample units per 4.4.2/ sample exposed to all tests listed.
2/ Samples divided into 2 equal groups, A&B. "A" units tested at +140 F; "B" units tested at -50 F.
3/ Abort actuator 9282666 only.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T02:07Z
Check the source to verify that this is the current version before use.