MILITARY SPECIFICATION

GLOVES, CLOTH, VINYL DIPPED, GENERAL PURPOSE

(WATER, AVIATION FUEL, HYDROGEN PEROXIDE, OILS)

This amendment forms a part of Military Specification MIL-G-82253C, dated 15 May 1978, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 1

2.1 - Delete in its entirety and substitute the following:

"2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement therto, cited in the solicitation."

Under "SPECIFICATIONS, FEDERAL", after "V-T-276 - Thread, Cotton", add the following document -

"NN-P-71 - Pallet, Material Handling, Wood, Stringer Construction, 2 Way and 4 Way Entry"

Page 2

Under "SPECIFICATIONS, MILITARY", before "MIL-B-17757 - Boxes, Shipping, Fiberboard", add the following document -

"MIL-P-15011 - Pallet, Material Handling, Wood, Post Construction, 4 Way Entry"

Under "SPECIFICATIONS, MILITARY", delete the following - "MIL-T-5624 - Turbine Fuel, Aviation, Grades JP-4 and JP-5"

AMSC N/A FSC 8415

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:57Z
Check the source to verify that this is the current version before use.

Before "LAWS AND REGULATIONS" add the following:

"2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation."

2.2 - Delete paragraph in its entirety and substitute the following:

"2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of documents which are DoD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS shall be the issue of the nongovernment documents which is current on the date of the solicitation."

After "UNIFORM FREIGHT CLASSIFICATION COMMITTEE, AGENT" information, add the following:

"AMERICAN SOCIETY FOR TESTING AND MATERIALS

Test method D-3787-80a

(Applications for copies shall be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, PA 19103)"

After "American Society for Testing and Materials" information, add the following new paragraph:

"2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained."

Page 3

3.3.1.2, Table I - Opposite characteristic "Courses per inch, Jersey knit" delete "26" and substitute "24". Opposite characteristic "Bursting strength, pounds (N)", under their respective columns delete "90 (400)" and "90 (400)" and substitute "45" and "45".

3.3.2, Table II - Characteristic for "Flat width, inches - minimum" delete "3 1/4 (8.1)" and substitute "2 1/4".

Page 4

3.3.4, line 3 - After "70," add "or heavier,".

3.3.5, line 5 - Delete the following: "in letters not less than 1/8 inch (3.2mm) in height".

Note, line 3, After "conforming to", add "Type VI,"

Source: https://assist.dla.mil - Downloaded: 2026-10-23T06:57Z
Check the source to verify that this is the current version before use.

3.3.5.1, line 3 - Delete the following: "not less tha 1/8 inch (3.2mm) for title and 3/32 inch (2.4cm) for the remainder".

Page 5

3.4, Table III - Opposite characteristic "Bursting strength", delete "50.0 (223)" and substitute "80". Last characteristic, delete "JP-4 fuel resistance" and substitute "Fuel resistance".

Page 9

Operation 10, line 4 - Delete "separted" and substitute "separated".

Page 12

4.1.1 - Delete in its entirety and substitute the following:

"4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Certificate of compliance. Where certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification."

4.3.1, line 9 - After "FED-STD-191" add "and ASTM D-3787-80a"

Page 13

Table VIII, characteristic for Bursting strength - Under "Test method" column, delete "5120" and substitute "ASTM-D-3787-80a".

Page 17

4.3.2, Delete in its entirety and substitute the following -

"4.3.5 Palletization examination. An examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the end item inspection lot. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:57Z
Check the source to verify that this is the current version before use.

Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted, incorrect, illegible, of improper size, location, sequence, or method of application."

Page 18

4.4, line 8 - Delete "JP-4". Table VIII - last characteristic, delete "JP-4 fuel" and substitute "Fuel".

Page 19

4.4.2, title - Delete "JP-4 fuel resistance test" and substitute "Fuel resistance test", line 3 - delete "JP-4 fuel, conforming to MIL-T-5624." and substitute "a mixture of 70% isooctane and 30% toluol."

Page 20

5.2.1, line 3 - Delete "SF" and substitute "CF" line 4 - delete "grade V2s," and add "variety DW, grade V15c,".

line 4 - Following "MIL-B-17757.", delete next sentence and substitute the following: "The fiberboard for the box liner shall be type CF, class domestic, of MIL-B-17757."

line 13 - At the end of paragraph, add the following: "Toward the end of the contract, or when there are less than the required amount per container of the same size (Type I only), mixed sizes may be packed within the same shipping container."

5.2.2, line 3 - Delete "grade 275" and add "variety DW, grade 200".

line 5 - Delete "variety DW, grade 200".

line 13 - At the end of paragraph, add the following: "Toward the end of the contract, or when there are less than the required amount per container of the same size (Type I only), mixed sizes may be packed within the same shipping container."

5.2.2.1 - Delete in its entirety

Page 21

5.3 - Delete in its entirety and substitute the following:

"5.3 Palletization. When specified (see 6.2) item, packed as specified shall be palletized on a 4-way entry pallet in accordance with load type IA of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with the bonding means C, K, and L or O or P. Pallet

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:57Z
Check the source to verify that this is the current version before use.

patterns shall be in accordance with the appendix of MIL-STD-147.

The pallet shall be 4-way, type IV; Type V, class 1, size 2; or Type VIII, fabricated from wood groups I, II, III, or IV, Grade A of NN-P-71, or 4-way, style 1, Size A, Type I, Class 1 fabricated from wood groups specified, of MIL-P-15011. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer."

After paragraph 5.4, add the following:

"5.4.1 Labels, mixed sizes. Each shipping container packed with mixed sizes shall have securely attached to the end and side, directly under the printing and stenciling, a white paper label 5 by 4 inches with the words "MIXED NSNS" plainly stamped or printed thereon and under these words shall be legibly stamped or printed the correct quantity and National Stock Numbers contained therein."

6.2 - Delete "c" in its entirety and add the following:

"c. When first article inspection is required (see 3.2), the item will be tested and should be a first article sample. The Contracting Officer should include specific instructions in acquisition documents regarding arrangement for examinations, quantity and testing and approval."

Delete "e" in its entirety.

After paragraph 6.4, add the following:

"6.5 Subject term (key word) listing.
fuel protective
solvent protective
utility
vinyl dipped
water resistant
wristlets, knitted"

Custodian:
Navy - NU
Air Force - 99

User Activities:
Navy - YD, AS, MC, OS

Review Activities:
Navy - SH
Air Force - 11, 82
DLA - CT

Preparing Activity:
Navy - NU

Project No. 8415-0355

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:57Z
Check the source to verify that this is the current version before use.