INCH-POUND
MIL-PRF-48656C
09 December 2021
SUPERSEDING
MIL-PRF-48656B
w/AMENDMENT 3
13 November 2013

PERFORMANCE SPECIFICATION

CARTRIDGES, SHOTSHELL

This specification is approved for use by all Departments and Agencies of the Department of Defense within the distribution limitations noted at the bottom of the page.

1. SCOPE

1.1 Scope. This specification covers shotshell cartridges for use in military shotgun weapons (see 6.1).

1.2 Classification. Items covered by this specification are as follows:

Type I – Combat / Riot or Military Police Applications (12 Gauge No. 00 Buckshot).
Type II - Training and Marksmanship Applications (12 Gauge No. 7 ½ Shot & No. 9 Shot).

Comments, suggestions, or questions on this document should be addressed to: U.S. Army DEVCOM Armaments Center, ATTN: FCDD-ACE-QSA, Picatinny Arsenal, New Jersey 07806-5000 or e-mailed to usarmy.pica.ccdc-ac.list.ardec-stdzn-branch@army.mil. Since contact information can change, you may want to verify the currency of this information using ASSIST Online database at https://assist.dla.mil/.

AMSC N/A FSC 1305

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are referenced in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or documents that are recommended for additional information or examples. While every effort has been made to ensure the completeness of this list, document users are cautioned they must meet all requirements as cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-372	–	Cleaning Compound, Solvent (For Bore of Weapons)
MIL-PRF-680	–	Degreasing Solvent
MIL-PRF-14107	–	Lubricating Oil, Weapons, Low Temperature
MIL-PRF-46000	–	Lubricant, Semi-Fluid (Automatic Weapons)
MIL-PRF-63460	–	Cleaner, Lubricant, and Preservative for Weapons and Weapons Systems

DEPARTMENT OF DEFENSE STANDARDS

DOD-STD-2101	–	Classification of Characteristics
MIL-STD-286	–	Propellants, Solid: Sampling, Examination & Testing
MIL-STD-636	–	Visual Standards for Small Arms Ammunition through Caliber .50
MIL-STD-810	–	Environmental Engineering Considerations & Laboratory Tests
MIL-STD-1168	–	Ammunition Lot Numbering and Ammunition Data Card
MIL-STD-1916	–	DOD Preferred Methods for Acceptance of Products

(Copies of these documents are available online at https://quicksearch.dla.mil/.)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF DEFENSE TECHNICAL BULLETIN

TB 700-2	–	Department of Defense Ammunition and Explosives Hazard Classification Procedures

(This document is available online at https://www.logsa.army.mil.)

U.S. ARMY COMBAT CAPABILITIES DEVELOPMENT COMMAND ARMAMENTS CENTER (DEVCOM AC) DRAWINGS

7553347	–	Box, Wirebound Boxes, Ammunition, M2A2
9390438	–	Cartridge, 12 Gauge Shotshell, No. 00 Buckshot
9390439	–	Cartridge, 12 Gauge Shotshell, No. 7 ½ Shot
9390440	–	Cartridge, 12 Gauge Shotshell, No. 9 Shot
9396197	–	Packing and Marking for M2A2 Ammo Box for Cartridges, Shotshell
9396206	–	Packing and Marking for Wirebound Box Assembly for Cartridges, Small Caliber
12551623	–	Cartridges, Loose Carton Pack – 12 Ga Shotshell, No. 00 Buckshot
12551625	–	Cartridges, Commercial Pack, 12 Ga Shotshell, No 7½ Shot
12551626	–	Cartridges, Commercial Pack, 12 Ga Shotshell, No 9 Shot
13032542	–	Box, Ammunition, M2A2 Assembly

(Copies of these drawings are available by email usarmy.pica.ccdc-ac.list.drawing-request-help-desk@army.mil.)

NAVAL SURFACE WARFARE CENTER INSTRUCTIONS

NAVSEAINST 8020.19 – Electrostatic Discharge Safety Program For Ordnance

(Copies of NAVSEA instructions are available online at: http://www.navsea.navy.mil.)

US ARMY TEST & EVALUATION COMMAND

ITOP 1-2-601	–	Internal Test Operations Procedure FR/GE/UK/US Laboratory Vibration Schedules
ITOP 4-2-601	–	Drop Tests for Munitions
ITOP 4-2-602	–	Rough Handling Tests TOP 1-2-608 Sound Level Measurements
TOP 3-2-609	–	Chemical Compatibility of Nonmetallic Materials Used in Small Arms Systems

(Copies of these documents may be requested from the US Army Test and Evaluation Command, online at http://www.atec.army.mil/publications/topsindex.aspx.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

SPORTING ARMS & AMMUNITION MANUFACTURER'S INSTITUTE

SAAMI – Technical Committee Manual Vol. IV Shotshell

(Copies of SAAMI manuals are available at https://saami.org.)

AMERICAN NATIONAL STANDARDS INSTITUTE

ANSI/SAAMI Z299.2 – Voluntary Industry Performance Standards for Pressure and Velocity of Shotshell Ammunition for the Use of Commercial Manufacturers

(Copies of ANSI Standards are available at https://saami.org/technical-information/ansi-saami-standards.)

2.4 Order of precedence. Unless otherwise noted herein or in the contract, in the event of conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Design verification test. When specified (see 6.2), a sample of the shotshell cartridges shall be subjected to design verification tests (DVT) in accordance with 4.1 and Table III. Requirements that are established during DVT will be the baseline for first article and conformance inspections.

3.1.1 Key characteristics. The key characteristics of the design that are deemed essential to meet requirements of this specification shall be identified and variability limits or baselines shall be established during design verification. The variability of key characteristics for the cartridges submitted for first article and lot acceptance shall conform to the baseline established for them during design verification (see 6.8).

3.1.2 Classification of characteristics. Defects inherent to the cartridge design that are not already listed in Table VI shall be identified during design verification and shall be classified as either a minor, major, or critical defect in accordance with DOD-STD-2101.

3.2 First article. When specified (see 6.2), a sample of the shotshell cartridges shall be subjected to first article inspection in accordance with 4.2.

3.3 Conformance inspection. When specified (see 6.2), a sample of the shotshell cartridges shall be subjected to conformance inspection in accordance with section 4.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

3.4 Cartridge. The cartridge shall comply with all requirements specified on Drawing 9390438, 9390439 or 9390440 and ANSI/SAAMI Z299.2.

3.5 Operating requirements.

3.5.1 Primed case sensitivity. The primer sensitivity shall be determined by dropping a steel ball onto a simulated firing pin. If one or more cartridge primers fail, a sensitivity rundown test shall be conducted in accordance with 4.5.1.

3.5.1.1 Primer initiation. The energy imparted by a steel ball weighing 1.94 ± 0.02 ounces falling 12 inches onto a simulated firing pin shall cause initiation of the primer.

3.5.1.2 Primer insensitivity. The energy imparted by a steel ball weighing 1.94 ± 0.02 ounces falling 2 inches onto a simulated firing pin shall not cause initiation of the primer.

3.5.2 Velocity. At a point 3.0 ± 0.5 feet directly in front of the muzzle of a 30.0 ± 0.1 inch test barrel, the mean velocity and the maximum standard deviation from the mean velocity shall be as shown in Table I.

TABLE I. Shot velocity requirements.

TYPE	NOMENCLATURE	AMBIENT		HOT		COLD	
		MEAN (ft/s)	SD (ft/s)	MEAN (ft/s)	SD (ft/s)	MEAN (ft/s)	SD (ft/s)
I	No. 00 Buckshot	1,325 ± 50	30	1415 MAX 1198 MIN	30	1415 MAX 1198 MIN	35
II	No. 7 $^{1}/_{2}$ Shot	1,145 ± 90	30				
II	No. 9 Shot	1,145 ± 90	30				

3.5.3 Chamber pressure. The average maximum chamber pressure shall not exceed 12,500 LUP (lead units of pressure) or 13,000 PSI (pounds per square inch). The maximum individual pressure shall not exceed 14,500 LUP or 15,000 PSI.

3.5.4 Function and casualty. The cartridge shall function without casualty in both manual and semiautomatic shotguns.

3.5.5 Pattern. The pattern shall be as follows for the appropriate shot size:

3.5.5.1 No. 00 Buckshot. The average percentage of pellets inside or touching a 30 inch diameter circle at a range of 40 yards shall be no less than 65 percent when fired through a 12 Ga. Shotgun with a barrel length of 29.0 ± 2.5 inches with a full choke (see 6.9).

3.5.5.2 No. 7 ½ Shot. The average percentage of pellets inside or touching a 30 inch diameter circle at a range of 40 yards shall be no less than 70 percent when fired through a 12 Ga. Shotgun with a barrel length of 28.0 ± 2.5 inches with a full choke (see 6.9).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

3.5.5.3 No. 9 Shot. The average percentage of pellets inside or touching a 30 inch diameter circle at a range of 25 yards shall be no less than 50 percent when fired through a 12 Ga. Shotgun with a barrel length of 26.0 ± 0.5 inches with a skeet choke (see 6.9).

3.5.6 Shot Type. The cartridges shall have the following shot:

3.5.6.1 No. 00 Buckshot. The cartridge shall contain 9 pellets of commercial shot size 0.330 ± 0.015 inches.

a. Nominal pellet count shall be 130 pellets per pound with 0.05 percent antimony.

b. The average pellet count shall not vary by more than 8 percent from 130 pellets per pound if using 0.05 percent antimony.

3.5.6.2 No. 7 ½ Shot. The cartridge shall contain 1 1/8 ounces +3/-5 percent of commercial shot size 0.095 ± 0.005 inches.

3.5.6.3 No. 9 Shot. The cartridge shall contain 1 1/8 ounces +3/-5 percent of commercial shot size 0.080 ± 0.005 inches.

3.6. Environmental requirements.

3.6.1 Operating temperatures. The shotshell cartridges shall remain safe, operable, and meet the functional requirements of this document throughout a temperature range from cold to hot.

3.6.2 Storage temperatures. The shotshell cartridges shall be capable of being stored throughout the temperature range of extreme cold to extreme hot and be safe to store and fire with no critical defects as defined in Table VII.

3.6.3 Chemical compatibility. The shotshell cartridges shall be safe for transportation, storage, handling and use, and remain operable after exposure to the chemicals and lubricants commonly used in military environments in accordance with TOP-3-2-609.

3.6.4 Sequential rough handling (Type I only). Cartridges shall be capable of withstanding the rigors of the sequential rough handling, storage, transportation and use throughout the temperature range of -60°F (-51°C) and 145°F (+63°C), and shall meet all performance requirements. Cartridges shall be exposed to the following conditions in this specified sequential order.

a. Secured-cargo vibration
b. 2.1 Meter drop test
c. Loose cargo test
d. 1.5 Meter drop test

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

3.6.5 12.2 Meter drop. When packaged in accordance with the packaging provisions of the contract and subjected to a 12.2 meter drop, the cartridges shall not detonate or burn, deflagrate, lose propellant, and ammunition shall be safe to handle and dispose of.

3.6.6 Long term storage. After being subjected to extreme temperatures during long term storage environment, the mean velocity shall not decrease from the design velocity at ambient temperature by greater than 5% as required in paragraph 3.5.2. The cartridges shall meet chamber pressure requirements of paragraph 3.5.3, and shall be safe to store and fire with no critical defects as defined in Table VII.

3.6.7 Thermal shock. After exposure to alternatively high and low temperatures of extreme cold to extreme hot, the cartridge shall be safe to store and fire with no critical defects as defined in Table VI.

3.6.8 Electrostatic discharge (ESD). In Personnel-borne environments (25 ± 1.2 kilovolts electrostatic discharge), the cartridge shall be operational and reliable without burning or exploding.

3.7 Support and ownership.

3.7.1 Ammunition lot numbering. Each lot of ammunition shall be identified by type and lot number in accordance with MIL-STD-1168. The lot numbering will appear only on the outer packaging.

3.7.2 Final hazard classification (FHC). The cartridge shall comply with the following Hazard Classification when packaged in commercial packaging or in accordance with packaging requirements in the contract.

DOD Hazard Class/Div: 1.4
DOD Hazard Compatibility Group: S
DOT Hazard Class: 1.4S
DOT Container Markings: CARTRIDGES, SMALL ARMS UN 0012.

3.7.3 Energetic materials compatibility. All energetic materials (explosives, propellants, and pyrotechnics) utilized must be compatible with all combinations of directly contacting energetic and non-energetic materials.

3.7.4 Propellant stability. All propellants shall be stable not less than 5 years.

3.7.5 Workmanship. All items shall be free of burrs, chips, flashing, voids, sharp edges, wrinkles, deep draw scratches, scaly metal, cracks, dirt, grease, rust and other imperfections. Cartridges shall be free of foreign material including, but not limited to, corrosion, stains, oil, sealant smears and metal chips.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

4. VERIFICATION.

TABLE II. Requirements/verification cross reference matrix.

Method of Verification 1 – Analysis 2 – Demonstration 3 – Examination 4 – Test		Classes of Verification A – Design verification B – First Article C – Conformance							
Section 3 Requirement	Description	Verification Methods				Verification Class			Section 4 Verification Method
		1	2	3	4	A	B	C	
3.1	Design verification	X	X	X	X	X			4.1
3.1.1	Key characteristics		X	X	X	X			4.1.1
3.1.2	Classification of characteristics			X		X			4.1.2
3.2	First article			X	X		X		4.2
3.3	Conformance inspection			X	X			X	4.3
3.4	Cartridge			X	X	X	X	X	4.4
3.5.1	Primed case sensitivity				X	X	X	X	4.5.1
3.5.2	Velocity				X	X	X	X	4.5.2
3.5.3	Chamber pressure				X	X	X	X	4.5.3
3.5.4	Function and casualty				X	X	X	X	4.5.4
3.5.5	Pattern				X	X	X	X	4.5.5
3.5.6	Shot type			X		X	X	X	4.5.6
3.6.1	Operating temperatures		X		X	X	X	X	4.6.1
3.6.2	Storage temperatures		X	X	X	X			4.6.2
3.6.3	Chemical compatibility		X	X	X	X			4.6.3
3.6.4	Sequential rough handling				X	X			4.6.4
3.6.5	12.2 Meter drop				X	X			4.6.5
3.6.6	Long term storage				X	X			4.6.6
3.6.7	Thermal shock				X	X			4.6.7

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

TABLE II. Requirements/verification cross reference matrix. – Continued

Method of Verification 1 – Analysis 2 – Demonstration 3 – Examination 4 – Test		Classes of Verification A – Design verification B – First Article C – Conformance							
Section 3 Requirement	Description	Verification Methods				Verification Class			Section 4 Verification Method
		1	2	3	4	A	B	C	
3.6.8	Electrostatic discharge (ESD)			X	X	X			4.6.8
3.7.1	Ammunition lot numbering			X			X	X	4.7.1
3.7.2	Final hazard classification		X		X	X			4.7.2
3.7.3	Energetic material qualification		X	X	X	X			4.7.3
3.7.4	Propellant stability				X		X		4.7.4
3.7.5	Workmanship		X				X	X	4.7.5

4.1 Design verification. When specified, a sample of cartridges shall undergo design verification by analysis, demonstration, examination and test in accordance with Tables II, Tables III, Tables VI, Tables VII, and applicable paragraphs within this section.

4.1.1 Key characteristics. Verify by examination of objective evidence and analysis that all key characteristics have been identified and valid variability limits have been established. A minimum of 5 sets of components, subassemblies and assemblies shall be subjected to a physical configuration audit (PCA) to establish a product uniformity baseline for the key characteristic identified in section 3.

4.1.2 Classification of characteristics. Verify by examination of objective evidence and analysis that all characteristics inherent to the design have been identified and correctly classified, based on safety, possible consequence of deficiency, and DOD-STD-2101.

4.1.3 Design verification rejection. If any item of the sample fails to comply with any design verification requirement specified, the design shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

TABLE III. Design verification tests and inspection.

Examination or Test 1/	Conformance Criteria			Requirement Paragraph	Inspection Method
	Qty	Acc	Rej		
Cartridge, 12 Gauge Shotshell					
Examination for defects					Table VI
Critical defect	100% & VL-VII	0	1	3.4	2/
Major defect	VL-V	0	1	3.4	2/
Minor defect	VL-III	0	1	3.4	2/
Key characteristics	50	0	1	3.1.1	4.1.1
Primer case sensitivity	75	3/		3.5.1	4.5.1
Velocity					
a. Type I					
1. Ambient	50	4/		3.5.2	4.5.2
2. Hot	50	4/		3.5.2	4.5.2
3. Cold	50	4/		3.5.2	4.5.2
b. Type II, Ambient	50	4/		3.5.2	4.5.2
Chamber pressure					
a. Type I					
1. Ambient	50	5/		3.5.3	4.5.3
2. Hot	50	5/		3.5.3	4.5.3
3. Cold	50	5/		3.5.3	4.5.3
b. Type II, Ambient	50	5/		3.5.3	4.5.3
Function and casualty					
a. Type I					
1. Ambient	100	6/		3.5.4	4.5.4
2. Hot	100	6/		3.5.4	4.5.4
3. Cold	100	6/		3.5.4	4.5.4
b. Type II, Ambient	100	6/		3.5.4	4.5.4
Pattern	30	7/		3.5.5	4.5.5
Shot type					
Type I	30	0	1	3.5.6	4.5.6
Type II	5	0	1	3.5.6	4.5.6
Operating temperatures				3.6.1	4.6.1
Storage temperatures					4.6.2
a. Long term high temperature storage	120			3.6.2	4.6.2.1
b. Long term low temperature storage	120			3.6.2	4.6.2.2
Chemical compatibility	60			3.6.3	4.6.3

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

TABLE III. Design verification tests and inspection. – Continued.

Examination or Test 1/	Conformance Criteria			Requirement Paragraph	Inspection Method
	Qty	Acc	Rej		
Sequential rough handling Type I only a. Secured-cargo vibration b. 2.1 Meter drop test c. Loose cargo test d. 1.5 Meter drop test	6 wire bound boxes			3.6.4	4.6.4
12.2 Meter drop a. Type I 1. Hot 2. Cold b. Type II 1. Hot 2. Cold	 6 wire bound boxes 6 wire bound boxes 6 fiberboard boxes 6 fiberboard boxes			3.6.5 3.5.6 3.5.6 3.5.6 3.5.6	4.6.5 4.6.5.1 4.6.5.1 4.6.5.2, 4.6.5.3 4.6.5.2, 4.6.5.3
Long term storage	200			3.6.6	4.6.6
Thermal shock	50			3.6.7	4.6.7
Electrostatic discharge	20			3.6.8	4.6.8
Final hazard classification				3.7.2	4.7.2
Energetic material qualification				3.7.3	4.7.3
Workmanship		0	1	3.7.5	4.7.5

NOTES:

1/ If no accept/reject criteria is expressed, the sample shall be rejected if any of the cartridges fail to comply with the applicable requirement.

2/ Inspection sampling shall be tightened to 100% plus VL-VII for the criticals, VL-V for majors and VL-III for minors in accordance with MIL-STD-1916.

3/ The criteria for primed case sensitivity acceptance are contained in 3.5.1 & 4.5.1.

4/ The criteria for velocity acceptance are contained in Table I.

5/ The criteria for chamber pressure acceptance are contained in 3.5.3.

6/ The criteria for function and casualty of the sample cartridges, tested at ambient, hot and cold temperatures for Type I rounds and at ambient temperature for Type II rounds, are contained in Table VII.

7/ The criteria for pattern acceptance are contained in 3.5.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

4.2 First article inspection. When specified in the contract, a sample of the cartridge and components shall be subjected to first article verification in accordance with Table II, Table IV, Table VI, and Table VII.

4.2.1 First article quantity. First article verification shall be performed on the quantity of cartridges, primed cases and grams of propellant as specified in Table IV.

4.2.2 Inspections to be performed. As determined by the Government, the first article assemblies, components and test specimens may be subjected to any or all of the examinations and tests specified in this specification (see Table IV) and be inspected for compliance with any or all requirements of the specification and the applicable drawings.

4.2.3 First article rejection. If any assembly, component or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected.

TABLE IV. First article tests and inspection.

Examination or Test	Conformance Criteria			Requirement Paragraph	Inspection Method
	Sample	Acc	Rej		
Cartridge, 12 Gauge Shotshell					
Examination for defects					Table VI
Critical defect	3073	0	1	3.4	1/
Major defect	512	0	1	3.4	1/
Minor defect	80	0	1	3.4	1/
Primed case sensitivity	30	2/		3.5.1	4.5.1
Velocity					
a. Type I					
1. Ambient	50	3/		3.5.2	4.5.2
2. Hot	50	3/		3.5.2	4.5.2
3. Cold	50	3/		3.5.2	4.5.2
b. Type II, Ambient	50	3/		3.5.2	4.5.2
Chamber pressure					
a. Type I					
1. Ambient	50	4/		3.5.3	4.5.3
2. Hot	50	4/		3.5.3	4.5.3
3. Cold	50	4/		3.5.3	4.5.3
b. Type II, Ambient	50	4/		3.5.3	4.5.3
Function and casualty					
a. Type I					
1. Ambient	100	5/		3.5.4	4.5.4
2. Hot	100	5/		3.5.4	4.5.4
3. Cold	100	5/		3.5.4	4.5.4
b. Type II, Ambient	100	5/		3.5.4	4.5.4
Pattern	30	6/		3.5.5	4.5.5

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

TABLE IV. First article tests and inspection. – Continued.

Examination or Test	Conformance Criteria			Requirement Paragraph	Inspection Method
	Sample	Acc	Rej		
Shot type					
Type I	30	0	1	3.5.6	4.5.6
Type II	5	0	1	3.5.6	4.5.6
Operating temperatures				3.6.1	4.6.1
Propellant stability	50 gm	0	1	3.7.4	4.7.4

Notes:

1/ For first article only, inspection sampling shall be tightened to 100% plus VL-VII for the criticals in accordance with MIL-STD-1916. A random sample of 512 cartridges for major defects shall be selected from the 3,073 cartridges. The first 80 shall be inspected for major and minor defects and the rest shall be inspected for major defects.

2/ The criteria for primed case sensitivity acceptance are contained in 3.5.1 & 4.5.1.

3/ The criteria for velocity acceptance are contained in Table I.

4/ The criteria for chamber pressure acceptance are contained in 3.5.3.

5/ The criteria for function and casualty of the sample cartridges, tested at ambient, hot and cold temperatures for Type I rounds and at ambient temperature for Type II rounds, are contained in Table VII.

6/ The criteria for pattern acceptance are contained in 3.5.5.

4.3 Conformance verification.

4.3.1 Inspection lot formation. Lot formation shall be in accordance with the lot formation requirement of MIL-STD-1168. Unless otherwise specified, component parts shall be homogeneous, inspected, and tested. The cartridge lot shall contain:

a. Cartridge cases from one unchanged process and from one manufacturer.
b. Shot from one unchanged process and from one manufacturer.
c. Primers from one lot interfix number and from one manufacturer.
d. Propellant from no more than two lot numbers and from one manufacturer.

4.3.2 Classification of characteristics.

a. Sampling requirements. Inspection sampling requirements for critical, major and minor characteristics are defined in MIL-STD-1916. Unless specified otherwise, Verification Level VII in addition to 100% inspection shall be used for all characteristics defined as Critical, Verification Level IV shall be used for all characteristics defined as Majors and Verification Level II for all Minor characteristics.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

b. Inspection. Conformance inspection shall be performed in accordance with Table II Table V, Table VI, and Table VII. For all conformance inspections, the same sample specimen may be used for all non-destructive examinations or tests.

4.3.4 Alternative conformance provisions. Unless otherwise specified herein or provided for in the contract, alternative conformance procedures, methods or equipment, such as statistical process control, tool control, or other types of sampling plans, may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions herein.

4.3.5 Test Provisions. If an equipment/weapon failure occurs which prevents the obtaining of a reliable test result, then the equipment/weapon shall be replaced or repaired; the individual test cartridge result shall be disregarded and another sample cartridge shall be fired for record. If the weapon/equipment failure prevented the obtaining of reliable results for the entire test series, then the entire test result shall be disregarded and a complete sample shall be fired for record.

TABLE V. Conformance inspection.

Examination or Test	Conformance Criteria			Requirement Paragraph	Inspection Method
	Sample	Acc	Rej		
Cartridge, 12 Gauge Shotshell					
Examination for defects					Table VI
Critical defect	100% & VL-VII	0	1	3.4	1/
Major defect	VL-IV	0	1	3.4	1/
Minor defect	VL-II	0	1	3.4	1/
Primed case sensitivity	30	2/		3.5.1	4.5.1
Velocity					
a. Type I					
1. Ambient	30	3/		3.5.2	4.5.2
2. Hot	30	3/		3.5.2	4.5.2
3. Cold	30	3/		3.5.2	4.5.2
b. Type II, Ambient	30	3/		3.5.2	4.5.2
Chamber pressure					
a. Type I					
1. Ambient	30	4/		3.5.3	4.5.3
2. Hot	30	4/		3.5.3	4.5.3
3. Cold	30	4/		3.5.3	4.5.3
b. Type II, Ambient	30	4/		3.5.3	4.5.3

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

TABLE V. Conformance inspection. – Continued.

Examination or Test	Conformance Criteria			Requirement Paragraph	Inspection Method
	Sample	Acc	Rej		
Function and casualty					
a. Type I					
1. Ambient	100	5/		3.5.4	4.5.4
2. Hot	100	5/		3.5.4	4.5.4
3. Cold	100	5/		3.5.4	4.5.4
b. Type II, Ambient	100	5/		3.5.4	4.5.4
Pattern	30	6/		3.5.5	4.5.5
Shot type					
Type I	30	0	1	3.5.6	4.5.6
Type II	5	0	1	3.5.6	4.5.6
Operating temperatures				3.6.1	4.6.1

Notes:

1/ To inspection sampling shall be tightened to 100% plus VL-VII for the criticals, VL-IV for majors and VL-II for minors in accordance with MIL-STD-1916.

2/ The criteria for primed case sensitivity acceptance are contained in 3.5.1 & 4.5.1.

3/ The criteria for velocity acceptance are contained in Table I.

4/ The criteria for chamber pressure acceptance are contained in 3.5.3.

3/ The criteria for function and casualty of the sample cartridges, tested at ambient, hot and cold temperatures for Type I rounds and at ambient temperature for Type II rounds, are contained in Table VII.

4/ The criteria for pattern acceptance are contained in 3.5.5.

TABLE VI. Examination for defects.

Classification	Examination or Test 1/	Conformance Criteria 2/	Requirement Paragraph	Inspection Method Reference
Critical				
1	Head or rim split (3d)	100% & Level VII	3.4	Visual
2	Mashed head (3c)	100% & Level VII	3.4	Visual
Major				
101	No primer (31)	100%	3.4	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

TABLE VI. Examination for defects. – Continued.

Classification	Examination or Test 1/	Conformance Criteria 2/	Requirement Paragraph	Inspection Method Reference
102	Cocked Primer (32)	100%	3.4	Visual
103	Inverted Primer (33)	100%	3.4	Visual
104	Perforated or split case (3h)	Level IV	3.4	Visual
105	Cartridge length, max	Level IV	3.4	Gage
106	Rim thickness, max	Level IV	3.4	Gage
107	Head diameter, max	Level IV	3.4	Gage
108	Case diameter, max	Level IV	3.4	Gage
109	Cartridge type, incorrect (4) 4/	Level IV	3.4	Visual/Gage
110	Open crimp (2)	Level IV	3.4	Visual
111	Defective head (3a)	Level IV	3.4	Visual
112	Sheared case over head (3b)	Level IV	3.4	Visual
113	Defective body (3e)	Level IV	3.4	Visual
114	Battery cup defects (3g)	Level IV	3.4	Visual
115	Battery cup above specification 3/	Level IV	3.4	Gage
Minor				
201	Illegible or missing cartridge marking (28)	Level II	3.4	Visual
202	Workmanship	Level II	3.7.5	Visual

Notes:

1/ Refer to shotshell/shotgun section of MIL-STD-636 for Visual Standards of defects.

2/ Level II or Level IV or Level VII refer to Verification Level II or Verification Level IV or Verification Level VII respectively of MIL-STD-1916.

3/ Battery cup shall be no more than .004 inch above flush. The primer cup shall be below flush of the battery cup.

4/ Inspection for incorrect cartridge type shall be performed during or immediately prior to the packaging operation which is before cartridge lot acceptance. Occurrence of any other type of cartridge shall be classified as a major defect. Any incorrect cartridge type found shall be replaced with a correct cartridge type and the entire lot shall be subjected to a subsequent 100% inspection. During the subsequent inspection, any incorrect cartridge type found shall be replaced with a correct cartridge type.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

TABLE VII. Function and casualty firing defects criteria.

Firing Defects 1/, 3/	Acc	Rej	Classification
1. Burst rim	0	1	Major
2. Blown primer or battery cup	0	1	Major
3. Wad or other obstruction remaining in bore	0	1	Major
4. Blown base wad	0	1	Major
5. Head pulled off	0	1	Major
6. Head cut off	0	1	Major
7. Dropped primer or battery cup	0	1	Major
8. Misfire	0	1	Major
9. Body cut off	0	1	Major
10. Head split	1	2	Major
11. Split knurl	1	2	Major
12. Split mouth 2/	3	4	Major
13. Partial cut off	1	2	Major
14. Rupture	1	2	Major
15. Partial split	3	4	Major
16. Head start	1	2	Major
17. Bulged rim	1	2	Major
18. Body split	3	4	Major
19. Powder burns	1	2	Major
20. Primer set back more than .025 in. above flush	1	2	Major
21. Battery cup set back more than .025 in. above flush	1	2	Major
22. Primer pierced	1	2	Major
23. Primer punctured	1	2	Major
24. Cumulative defects for 10 - 23	3	4	Major

Notes:

1/ For defects refer to MIL-STD-636, Shotshell cartridges section, for firing defects standards.

2/ At cold temperatures only, splits that do not exceed the severity of those shown in MIL-STD-636, figure no. 11, are permissible.

3/ For any ballistic test except function and casualty, where the occurrence of a firing defect prevents the obtaining of a valid result for the characteristic being tested the following shall apply. The defect shall be observed under the appropriate function and casualty defect category and included in the defect count for determining acceptance or rejection in accordance with Table IV. The particular test for which the round was fired shall not be penalized. A replacement round shall be fired to obtain the data for the characteristic being tested.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

4.4 Cartridge verification. All test cartridges shall be verified by standard measurement equipment or specialty gages.

4.5 Operating verification. All ballistic testing shall be examined against Table VI. For any ballistic test except function and casualty, where the occurrence of a firing defect prevents obtaining a valid result for the characteristic being tested, the defect shall be observed. The particular test for which the round was fired shall not be penalized. A replacement round shall be fired to obtain the data for the test. Unless otherwise specified, the following definitions describe the temperature conditions for this specification.

Extreme Cold:	-65°F ± 5°F (-54°C ± 3°C)
Cold:	-20°F ± 5°F (-29°C ± 3°C)
Ambient:	+70°F ± 5°F (+21°C ± 3°C)
Hot:	+125°F ± 5°F (+52°C ± 3°C)
Extreme Hot:	+160°F ± 5°F (+71°C ± 3°C)

The ammunition shall be conditioned at the respective temperatures for not less than 4 hours. The conditioned ammunition shall not be exposed to ambient temperature conditions for greater than 20 minutes. If so, the ammunition shall be reconditioned for not less than 4 hours.

4.5.1 Primed case sensitivity verification. The primed case sensitivity testing shall be performed as specified in SAAMI Technical Committee Manual Vol. IV Shotshell using a simulated firing pin with a nominal weight of 70 grains and a spherical end radius of 0.0500 ± 0.0025 inches.

4.5.1.1 Primer initiation. Empty primed shotshell cartridges shall be tested for primer sensitivity. Two-thirds of the sample shall be tested at a height of 12 inches and one-third of the sample shall be tested at a height of 2 inches. If one or more cartridge primers fail at either height, the sample fails and a sensitivity rundown test shall be conducted.

4.5.1.2 Primer insensitivity. The sensitivity rundown test shall consist of a 25 cartridge test at each 1 inch increment of height between 0 percent and 100 percent firing. If the average critical height (H) plus four standard deviations (4 sigma) exceeds 14 inches, or if the average critical height minus two standard deviations (2 sigma) is less than 1 inch, the lot of cartridges shall be rejected. The average critical height (H) is defined as the mean height at which 50 percent of the primers being tested will fire.

4.5.2 Velocity verification. The velocity test shall be conducted in accordance with SAAMI Technical Committee Manual Vol. IV Shotshell and ANSI/SAAMI Z299.2. The sample cartridges shall be temperature conditioned as follows (unpackaged cartridges) for four hours minimum.

4.5.3 Chamber pressure verification. The chamber pressure test shall be conducted in accordance with SAAMI Technical Committee Manual Vol. IV Shotshell and ANSI/SAAMI Z299.2. Conditioning for the sample cartridges temperature shall be as follows (unpackaged cartridges) for four hours minimum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

4.5.4 Function and casualty verification. Cartridges shall be fired in accordance with Table VIII below. Conditioning for the sample cartridges temperature shall be as follows (unpackaged cartridges) for four hours minimum.

Semi-automatic weapons shall have a total chamber and magazine capacity of five cartridges minimum. The weapons shall be loaded to capacity and the test performed until the total test sample quantity is reached.

Table VIII. Function and casualty weapons.

	Type I		Type II
	Weapons 1 Sample	Weapons 2 Sample	Weapons 1 Sample
Manual Ambient Hot Cold	50 50 50	50 50 50	100
Semi-automatic Ambient Hot Cold	50 50 50	50 50 50	100

4.5.5 Pattern verification. The pattern test shall be conducted in accordance with SAAMI Technical Committee Manual Vol. IV Shotshell.

4.5.6 Shot type verification. The shot shall be as follows and in accordance with SAAMI Technical Committee Manual Vol. IV Shotshell.

4.5.6.1 No. 00 Buckshot. Thirty (30) cartridges shall be weighed, and the pellets shall be counted. The number of pellets per pound shall be calculated for each cartridge, and the average of the pellet counts per pound shall be calculated (paragraph 3.5.6).

4.5.6.2 No. 7 ½ and No. 9 Shot shotgun shells. The shot from each of five (5) cartridges shall be weighed and counted, and pellets size measured (10 pellets per cartridge).

4.5.6.2.1 Pellet count. Pellet count shall be determined by removing pellets from each of the five shells to obtain 1 ounce of shot or 437.5 grains ± 1 grain to perform pellet count and compare to SAAMI Vol IV shot table: Miscellaneous: Shot size /Pellet count/Tolerances, taking antimony content and pellet size into account.

4.6 Environmental verifications.

4.6.1 Operating temperatures. Operating temperatures shall be verified during function and casualty testing (see 4.5.4).

4.6.2 Storage temperatures.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

4.6.2.1 High temperature storage. The long term high temperature storage test shall be conducted in accordance with MIL-STD-810, High Temperature, Procedure I. A sample of 120 rounds shall be subjected to continuous heating at +160°F and 15% relative humidity for 28 days. The cartridges shall then be stored under ambient conditions for 48 hours. The cartridges shall be visually inspected and function fired at ambient temperature; distributing quantity equally between the weapons.

4.6.2.2 Low temperature storage. The long term low temperature storage test shall be conducted in accordance with MIL-STD-810, Low Temperature, Procedure I. A sample of 120 rounds shall be subjected to continuous cooling at -65°F and 15% relative humidity for 28 days. The cartridges shall then be stored under ambient conditions for 48 hours. The cartridges shall be visually inspected and function fired at ambient temperature; distributing quantity equally between the weapons.

4.6.3 Chemical compatibility. The overall test procedure shall be conducted in general accordance with TOP 3-2-609. Prior to the start, a visual inspection shall be performed on 70 cartridges to determine suitability for test. If any deficiencies are noted, the cartridges shall be removed from testing. After inspection, the sample cartridges shall be completely submerged for 1 hour in each of the compounds listed in Table IX below (10 cartridges per chemical). At the end of the test period, each sample shall be inspected for any type of reaction of the chemical. If the test sample appeared to be unaffected or only mildly affected by the chemical, the absorbent pads shall be reapplied to its initial setting for an additional 7 hours. After a total exposure time of 8 hours, the chemicals shall be wiped away. At the end of the test, the items shall be visually inspected for signs of degradation, including pitting and staining. All cartridges shall be functioned from the shotgun. Any round that cannot be fired shall be considered a failure.

TABLE IX. Conditioning chemicals.

Chemical	Specification
Cleaning Compound, Solvent (For Bore of Weapons)	MIL-PRF-372
Degreasing Solvent	MIL-PRF-680
Cleaner, Lubricant, and Preservative for Weapons and Weapons Systems	MIL-PRF-63460
Lubricant, Semi-Fluid (Automatic Weapons)	MIL-PRF-46000
Lubricating Oil, Weapons, Low Temperature	MIL-PRF-14107
Simulated Sea Water or 5 percent NaCL	ASTM D1141

4.6.4 Sequential rough handling (Type I only). Three hundred twenty (320) cartridges shall be packed into a military pack in accordance with drawings 9396206 and 9396197. One hundred sixty (160) cartridges per M2A2 ammunition box (13032542) and two (2) M2A2 ammunition boxes per wire bound box (7553347). Testing shall be in accordance with ITOP 4-2-602.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

a. Secured cargo vibration. The secured cargo vibration shall be conducted in accordance with ITOP-1-2-601. The vibration schedule employed shall replicate vehicular transportation such as semi-trailers, trucks and two-wheeled trailers that would transport packaged ammunition on their beds. The wire bounds shall be conditioned and subjected to vibration schedules as specified in Table X below.

TABLE X. Secured cargo vibration.

Wire bound box	Temperature	Orientation
1	+145°F (+63°C)	Horizontal
2	+145°F (+63°C)	Vertical
3	+145°F (+63°C)	Horizontal
4	-60°F (-51°C)	Horizontal
5	-60°F (-51°C)	Vertical
6	-60°F (-51°C)	Horizontal

b. 2.1 meter drop. The 2.1 meter drop test shall be conducted in accordance with ITOP 4-2-602, Appendix A. 2.1 Meter Drop. Wire bounds shall be conditioned and dropped as specified in Table XI below.

TABLE XI. 2.1 Meter drop.

Wire-bound box	Temperature	1st Drop orientation	2nd Drop orientation
1	+145°F (+63°C)	45° Top end edge	Side
2	+145°F (+63°C)	Bottom (Base)	End of package up
3	+145°F (+63°C)	45° Bottom end edge	End of package down
4	-60°F (-51°C)	45° Top end edge	Side
5	-60°F (-51°C)	Bottom (Base)	End of package up
6	-60°F (-51°C)	45° Bottom end edge	End of package down

c. Loose cargo vibration. The loose cargo vibration test shall be conducted in accordance with ITOP 4-2-602, Appendix B. Loose Cargo Test. The wire bounds shall be conditioned and subjected to vibration schedules as specified in Table XII below. At the conclusion of the testing, all wire bound boxes shall be opened and one M2A2 ammunition box, from each wire bound box, shall be unpacked and the cartridges visually examined for damage. A random sample of 80 cartridges shall be selected and test fired to determine functioning. The two remaining M2A2 ammunition boxes shall be used for 1.5 meter drop testing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

TABLE XII. Loose Cargo.

Wire bound box	Temperature	1st Orientation
1	+145°F (+63°C)	Horizontal
2	+145°F (+63°C)	Vertical
3	+145°F (+63°C)	Horizontal
4	-60°F (-51°C)	Horizontal
5	-60°F (-51°C)	Vertical
6	-60°F (-51°C)	Horizontal

d. 1.5 Meter drop. The 1.5 meter drop test shall be conducted in accordance with ITOP 4-2-602, Appendix C. 1.5 Meter Drop. The ammunition cans shall be conditioned and dropped as specified in Table XIII below. Drops shall be made from a quick-release hook attached to an overhead hoist. The boxes shall be allowed to fall freely onto hard surface such as concrete or a steel plate. All of the cartridges shall then be visually inspected for damage. Cartridge marking shall be examined. Cartridges that are deemed safe to fire shall be expended by function testing.

TABLE XIII. 1.5 Meter drop.

Wire bound box	Temperature	1st Drop orientation	2nd Drop orientation
1	+145°F (+63°C)	Bottom down	Top down
2	+145°F (+63°C)	45° long side	45° short side
3	+145°F (+63°C)	Horizontal	Horizontal
4	-60°F (-51°C)	Bottom down	Top down
5	-60°F (-51°C)	45° long side	45° short side
6	-60°F (-51°C)	Horizontal	Horizontal

.

4.6.5 12.2 Meter drop. The test shall be performed in accordance with ITOP 4-2-601. The test shall be conditioned at hot and cold. The cartridge shall be safe to handle and dispose upon the completion of this test.

4.6.5.1 No. 00 Buckshot. The cartridges shall be packed in accordance with Drawing 12551623. Three hundred twenty (320) cartridges shall be packed shall be packed in accordance with Drawings 9396206 and 9396197 with one hundred sixty (160) cartridges per M2A2 ammunition box (13032542) and two (2) M2A2 ammunition boxes per wire bound box (7553347).

4.6.5.2 No. 7 ½ Shot. The cartridges shall be packed in accordance with Drawing 12551625. Five hundred (500) cartridges shall be packed with twenty five (25) cartridges per carton and twenty (20) cartons per fiberboard box.

4.6.5.3 No. 9 Shot. The cartridges shall be packed in accordance with Drawing 12551626. Five hundred (500) cartridges shall be packed with twenty five (25) cartridges per carton and twenty (20) cartons per fiberboard box.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

4.6.6 Long term storage verification. Testing for long term storage shall be conducted in accordance with MIL-STD-810, High Temperature- Procedure 1 at a constant extreme hot temperature, and with MIL-STD-810, Low Temperature- Procedure 1, at a constant extreme cold temperature. The cartridges shall then be stored under ambient conditions for 48 hours. The cartridges shall be visually inspected and then fired at ambient temperature; distributing quantity equally between shotshell weapons.

4.6.7 Thermal shock. Testing for thermal shock shall be performed in accordance with MIL-STD-810, Temperature Shock. The cartridges shall be placed inside an environmental chamber set at extreme cold for initiation of the test sequence. At the completion of the first 4-hour cycle, the cartridges shall be transferred to a high temperature chamber set at extreme hot for a 4-hour cycle. This process shall be repeated until six cycles (48 hours of exposure) are completed. The cartridges shall be visually inspected for any signs of deterioration. The cartridges shall then be stored under ambient condition for 48 hours. The cartridges shall then be visually inspected for any signs of corrosion. The cartridges shall be function fired from the Mossberg 590 and Remington 870 and the velocity shall be measured.

4.6.8 Electrostatic discharge (ESD). ESD tests shall be conducted in accordance with NAVSEAINST 8020.19. Cartridges shall meet the passing criteria for personnel-borne and helicopter-borne ESD.

4.7 Support and ownership verifications.

4.7.1 Ammunition lot numbering verification. Visually verify that an ammunition lot number has been assigned to each lot of 12 gauge shotshell cartridges in accordance with MIL-STD-1168.

4.7.2 Final hazard classification verification. Compliance with the FHC requirements specified at paragraph 3.7.2 shall be validated during the DVT. DVT tests for FHC shall be in accordance with TB-700-2 (4.a).

4.7.3 Energetics material qualification. Data shall be provided to the Government proving that all energetic materials meet NATO AOP-7 (see 6.5).

4.7.4 Propellant stability verification. Propellant stability tests shall be conducted in accordance with the test procedures listed below. Stability is verified when results comply with the requirements listed below.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

Table VIII. Propellant stability tests.

Test	Reference Document	Test Procedure Description	Requirement
Heat	MIL-STD-286	Method 404.1.2	For single base propellants - Methyl violet paper shall not change to salmon pink in less than 40 minutes, and the sample shall not explode in less than 5 hours at 274.1°F (134.5°C). For double base propellants - Methyl violet paper shall not change to salmon pink in less than 40 minutes, and no fumes given off less than 1 hour at 248°F (120°C).
Storage Degradation/Surveillance	MIL-STD-286	Method 407.1	No fumes in less than 30 days of storage at 149.9°F (65.5°C).

4.7.5 Workmanship. Visually verify that all parts and assemblies meet requirements of paragraph 3.7.5.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. These cartridges are intended for use in US military weapons for tactical and training purposes. The 12 gauge cartridges procured to this specification are military unique because they must meet the military's propellant stability and shelf life storage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

requirements of 5 years, which exceeds commercial industry's normal requirements. They must also meet the high and low temperature requirements for the combat rounds.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number and date of this specification.
b. Issue of DODISS to be sited in the solicitation, and, if required, the specific issue of individual documents referenced (see 2.2.1).
c. Requirements for submission of design verification samples (where applicable).
d. Requirements for submission of first article.
e. Requirements for submission of conformance samples.
f. Requirements and provisions for submission of test data as required.
g. Requirements for Ammunition Lot Numbering.
h. Packaging requirements (see section 5.1) (see 6.3).
i. If the Final Hazard Classification on record was based on government packaging drawings it may be necessary to include those packaging drawings in the contract to ensure continued legal transportation. Determination should be made by FCDD-ACE-QSF.
j. Requirements for ammunition data cards.

6.3 Packaging. Packaging will be level A for Type I rounds and level B for Type II rounds:

Type I cartridges can be packed in accordance with packaging drawing 9396206 (Cartridge, 12 Gauge Shotshell, No. 00 Buckshot, NSN 1305-01-232-8338). Type II cartridges can be unit packed in cartons in accordance with the best commercial practice. The packed cartridges will be over packed in a (4G) fiberboard box Class WWVR, Grade V3c or W5c, Style RSC, waterproofed per ASTM D5118 and closed in accordance with ASTM D1974. Five hundred rounds is a standard quantity per fiberboard box (25 cartridges/carton, 20 cartons/fiberboard box) (Cartridge, 12 Gauge Shotshell, No. 7-1/2 Shot, NSN 1305-01-232-8339; and Cartridge, 12 Gauge Shotshell, No. 9 Shot, NSN 1305-01-232-7415).

6.4 Ammunition lot numbers. Ammunition lot numbers require ammunition data cards in accordance with MIL-STD-1168.

6.5 Submission of inspection equipment designs for approval. Submit inspection equipment designs as required to DEVCOM Armaments Center, ATTN: FCDD-ACE-QMD, Picatinny Arsenal, NJ 07806-5000.

6.6 Submission of test data. In addition to the normal distribution of records, when the cartridge is procured by the US Army DEVCOM AC, one (1) copy of the ammunition data card for each lot should be forwarded to: DEVCOM Armaments Center, ATTN: FCDD-ACE-QMD Picatinny Arsenal, NJ 07806-5000.

6.7 Submission of alternative conformance provisions. All contractor proposed alternative conformance provisions will be submitted to the Government for evaluation / approval as directed by the contracting activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

6.8. Key characteristics. Key characteristics fall into two categories: (1) those relating to the product, and (2) those inherent in the manufacturing process. They include performance, features, reliability, conformance, durability, serviceability, aesthetics, quality and safety.

6.9 Chokes. The "full" choke and "skeet" choke designations refer to the industry standard for choke constriction diameters.

6.10 Subject term (keyword) listing.

12 Gauge
Shotgun
Combat
Riot
Military Police
Training

6.11 Changes incorporated. MIL-PRF-48656 Revision C incorporates ECP R21Q2011.

6.12 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

CONCLUDING INFORMATION

Custodian:
Army – AR
Navy – OS
Air Force - 170

Preparing activity:
Army – AR
(Project 1305-2022-022)

Review activities:
Army – MR
Navy – AS, MC, SH
Air Force – 40

Civil agency:
GSA - FAS

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.