INCH-POUND

MIL-W-64044 (AR)
AMENDMENT 7
21 June 1994
SUPERSEDING
AMENDMENT 6
16 February 1990

MILITARY SPECIFICATION

WARHEAD, 2.75 INCH ROCKET, M261 AND M267, PARTS FOR

This amendment forms a part of MIL-W-64044 (AR), dated 7 October 1983, and is approved for use by the US Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.2: Add to Product Drawings: "9334152 Obturator Support Assy".

3.2: Add to list of drawing: "9334152".

PAGE 3

* Add new paragraph 3.5 as follows:

"3.5 Push-off test. The environmental protector shall withstand a push-off test of 9.0 pounds minimum and 17.0 pounds maximum when performed in accordance with 4.5.4."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:12Z
Check the source to verify that this is the current version before use.

PAGE 4

4.3.1, Parts Description: Add:

*	"Protector, Environmental	9349897	15
	O-ring	9334139	10
	O-ring	9334114	10
	Obturator Support, Split	9334154	15 or 5/cavity whichever is greater
	Obturator Support Assy	9334152	25
	Ring, Retaining, Auto Jettison #9 Grenade (M261 only)	12561495	15
	Ring, Retaining, Auto Jettison (M261 only)	12561496	15
	O-ring, Cargo Retaining (M261 only)	12561497	15"

PAGE 7

TABLE I: Add:

*	"Protector, Environmental (Dwg. 9349897)			
	Push-off test	15	3.5	4.5.4
	Examination for defects	15	3.2	4.4.2.21
	Obturator Support, Split (Dwg. 9334154)			
	Examination for defects	15(a)	3.2	4.4.2.14
	Obturator Support Assy (Dwg. 9334152)			
	Examination for defects	25	3.2	4.4.2.15
	O-ring (Dwg. 9334139)			
	Examination for defects	10	3.2	Gage
	O-ring (Dwg. 9334114)			
	Examination for defects	10	3.2	Gage"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:12Z
Check the source to verify that this is the current version before use.

PAGE 10

4.4.2.2, Major 101: Delete "largest outside diameter" and substitute "second largest diameter".

Major 103: Delete "Center" and substitute "blow-through".

Minor 202: Delete in its entirety.

Add Minor 206: "206 Largest Outside Diameter .65% 3.2 Gage"

PAGE 17

4.4.2.9, Minor 201: Delete in its entirety.

Minor 202: Delete in its entirety.

PAGE 20

4.4.2.12: Add Major 111 and Minor 210 respectively:

"111	Surface finish (Note 8)	0.40%	3.2	Gage/Visual
210	Stake height	0.65%	3.2	Gage"

PAGE 21

4.4.2.13: Add Major 102:

"102	Continuity (cable)	100%	3.2	milliohmmeter"

Minor 201: Delete in its entirety.

Minor 202: Delete in its entirety.

Add 4.4.2.14, included Page (21a).

Add 4.4.2.15, included Page (21b).

Add 4.4.2.16, included Page (21c).

Add 4.4.2.17, included Page (21d).

Add 4.4.2.18, included Page (21e).

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:12Z
Check the source to verify that this is the current version before use.

PAGE 21 (continued)

Add 4.4.2.19, included Page (21f).

Add 4.4.2.20, included Page (21g).

* Add 4.4.2.21, included Page (21h).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:12Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-W-64044 (AR)
AMENDMENT 7

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.14	Obturator Support, Split	1 OF 1	9334154
			NEXT HIGHER ASSEMBLY: 9334152

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
CRITICAL	None defined.			
MAJOR				
101	Outside diameter	0.40%	3.2	Gage
102	Smaller inside diameter	0.40%	3.2	Gage
103	Larger inside diameter	0.40%	3.2	Gage
104	Depth	0.40%	3.2	Gage
105	Split width, max.	0.40%	3.2	Gage
106	Mold inspection	5/Cavity		
MINOR				
201	Evidence of poor workmanship	0.65%	3.4	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- (21 added: 2026-10-23T03:12Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-W-64044 (AR)
AMENDMENT 7

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.15	Obturator Support Assembly	1 OF 1	9334152
			NEXT HIGHER ASSEMBLY: 9334122

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
CRITICAL	None defined.			
MAJOR				
101	Tape missing or improperly located	0.40%	3.2	Visual
MINOR				
201	Evidence of poor workmanship	0.65%	3.4	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:12Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-W-64044 (AR)
AMENDMENT 7

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.16	O-ring	1 OF 1	9334139

NEXT HIGHER ASSEMBLY: 9334148 or 9334097

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
CRITICAL	None defined.			
MAJOR				
101	Inside diameter	0.40%	3.2	Gage
102	Cross section diameter	0.40%	3.2	Gage
MINOR				
201	Evidence of poor workmanship	0.65%	3.4	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- (Downloaded: 2026-10-23T03:12Z)
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-W-64044 (AR)
AMENDMENT 7

PARAGRAPH	TITLE		SHEET 1 OF 1	DRAWING NUMBER
4.4.2.17	O-ring			9334114
				NEXT HIGHER ASSEMBLY
				9334123 or 9334122
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
CRITICAL	None defined.			
MAJOR				
101	Inside diameter	0.40%	3.2	Gage
102	Cross section diameter	0.40%	3.2	Gage
MINOR				
201	Evidence of poor workmanship	0.65%	3.4	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:12Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-W-64044 (AR)
AMENDMENT 7

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.18	Ring, Retaining, Auto Jettison - #9 Grenade	1 OF 1	12561495
			NEXT HIGHER ASSEMBLY: 9334122

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
CRITICAL	None defined.			
MAJOR				
101	Thickness-top surface	0.40%	3.2	SMI*/Gage
102	Color code	0.40%	3.2	Visual
MINOR				
201	Largest inside diameter	0.65%	3.2	SMI*/Gage
202	Thickness-side	0.65%	3.2	SMI*/Gage
203	Center of hole to largest inside diameter	0.65%	3.2	SMI*/Gage
204	Spring tab height	0.65%	3.2	SMI*/Gage
205	Width of notch	0.65%	3.2	SMI*/Gage
206	Location of notch	0.65%	3.2	SMI*/Optical Comparator
207	Dimple height	0.65%	3.2	SMI*/Gage
208	Evidence of poor workmanship	0.65%	3.4	Visual

NOTES:
* Standard Measuring Instrument

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:12Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-W-64044 (AR)
AMENDMENT 7

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.19	Ring, Retaining, Auto Jettison	1 OF 1	12561496
			NEXT HIGHER ASSEMBLY: 9334122

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
CRITICAL	None defined.			
MAJOR				
101	Thickness-top surface	0.40%	3.2	SMI*/Gage
MINOR				
201	Largest inside diameter	0.65%	3.2	SMI*/Gage
202	Thickness-side	0.65%	3.2	SMI*/Gage
203	Center of hole to largest inside diameter	0.65%	3.2	SMI*/Gage
204	Spring tab height	0.65%	3.2	SMI*/Gage
205	Width of notch	0.65%	3.2	SMI*/Gage
206	Location of notch	0.65%	3.2	SMI*/Optical Comparator
207	Evidence of poor workmanship	0.65%	3.4	Visual

NOTES:
* Standard Measuring Instrument

Source: https://assist.dla.mil-DoDSSP (21 of 41) Updated: 2026-10-23T03:12Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-W-64044 (AR)
AMENDMENT 7

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.20	O-ring, Cargo Retaining	1 OF 1	12561497
			NEXT HIGHER ASSEMBLY: 9334122

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
CRITICAL	None defined.			
MAJOR				
101	Inside diameter	0.40%	3.2	SMI*/Gage
102	Cross section diameter	0.40%	3.2	SMI*/Gage
MINOR				
201	Evidence of poor workmanship	0.65%	3.4	Visual

NOTES:
* Standard Measurement Instrument

Source: https://assist.dla.mil-1 Downloaded: 2026-02-23T03:12Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.21	Environmental Protector	1 OF 1	9349897
			NEXT HIGHER ASSEMBLY: 9334097/9334148

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
CRITICAL	None defined.			
MAJOR				
101	Push-off test	0.40%	3.5	4.5.4
MINOR				
201	Evidence of poor workmanship	0.65%	3.4	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:12Z
Check the source to verify that this is the current version before use.

* Add new paragraph 4.5.4:

"4.5.4 Push-off test. A push-off test shall be set up to simulate the removal of the environmental protector. The dimensions of the simulated umbilical cable connector where the environmental protector fits on shall have .368 ± .001 inch large outside diameter, .273 ± .001 inch small outside diameter, and .157 ± .001 inch width of the large outside diameter. The surface shall have 32 microinches finish all over. A steady load shall be applied with a hemi-spherical (.180 ± .005 inch radius) plunger against the inside surface of the environmental protector. Any environmental protector that does not meet the required load shall be classed defective."

* 6.3: Delete "US Army Armament Research and Development Command, ATTN: DRDAR-QAF-I" and substitute "Armament Research, Development and Engineering Center, US Army Armament, Munitions and Chemical Command, ATTN: SMCAR-QAF-I".

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1340-A938)

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:12Z
Check the source to verify that this is the current version before use.