INCH-POUND

MIL-C-48155 (AR)
AMENDMENT 5
14 September 1995
SUPERSEDING
AMENDMENT 4
04 February 1993

MILITARY SPECIFICATION

CARTRIDGE, IGNITION, XM299
PARTS FOR

This amendment forms a part of MIL-C-48155 (AR), dated 01 September 1974, and is approved for use by the U.S. Army Armament Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1, Specifications and Standards: Add new listing as follows:

"MIL-STD-810 - Environmental Test Methods."

PAGE 2

3.2.1, Add new paragraph which reads as follows:

"3.2.1 Corrosion resistance (salt spray). Parts selected for the salt spray test shall show no evidence of pitting or mottling when tested in accordance with 4.5.2."

AMSC N/A
FSC 1395
DISTRIBUTION STATEMENT A.
Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

4.4.2.3, Body:

Major Category:

Major B149: Substitute "Min" for "Max".

Major B151: Delete in its entirety.

Major B152 and B153: Change number "152" to "151" and "153" to "152".

Minor category:

Minor 201: Delete in its entirety.

Minor 202 thru 206: Change "202" to "201", "203" to "202", "204" to "203", "205" to "204", and "206" to "205".

4.4.2.3, Major 153: Delete in its entirety and substitute the following:

"153 Salt spray test ... .065% ... 3.2.1 ... Visual/4.5.2".

* Major 153, Delete "callouts" and substitute:

"153 Salt spray test ... 1/ ... (-) ...3.2.1 ... Visual/4.5.2".

* Add: "Note 1/ See 4.5.2".

4.4.2.5, Head:

Major Category:

Major 141: Delete in its entirety and substitute the following:

"141 Diameter of external thread undercut ... 0.40% ... 3.2 ... Gage".

Major 142: Delete in its entirety and substitute the following:

"142 Large internal diameter ... 0.40% ... 3.2 ... Gage".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

PAGE 9 (cont)

Major B144: Add new CD which reads as follows:

"144 True position of large internal diameter to external thread ... 0.40% ... 3.2 ... Gage".

Major B145: Add new CD which reads as follows:

"145 True position of small internal diameter to external thread... 0.40% ... 3.2 ... Gage".

Major B146: Add new CD which reads as follows:

"146 True position of internal thread to external thread ... 0.40% ... 3.2 ... Gage".

Minor Category:

Minor 204: Delete in its entirety and substitute the following:

"204 Length from small outside diameter to shoulder of large outside diameter ... 0.65% ... 3.2 ... Gage".

Minor 205: delete in its entirety.

Minor 206 thru 211: Change "206" to "205", "207" to "206", "208 to "207", "209" to "208", "210" to "209", and "211" to "210".

PAGE 11

4.4.2.6, Major 137: Delete in its entirety and substitute the following:

"137 Salt spray test ... 0.065% ... 3.2.1... Visual/4.5.2".

* Major 137, Delete "0.65%" and substitute "1/".

* Add: "Note 1/ See 4.5.2".

Minor 202: Delete in its entirety.

Minor 203: Change "203" to "202".

PAGE 12

4.4.2.7, Delete in its entirety and substitute the following: (included).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

MIL-C-48155 (AR)
AMENDMENT 5

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	CAP	1 OF 1	9280537
			NEXT HIGHER ASSEMBLY 9293422

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Outside diameter	0.40%	3.2	Gage
102	True position of cavity	0.40%	3.2	Gage
103	Diameter of cavity	0.40%	3.2	Gage
104	Depth of cavity	0.40%	3.2	Gage
105	Protective finish missing	0.40%	3.2	Visual
106	Length from flange to face (3 places)	0.40%	3.2	Gage
107	Small outside diameter	0.40%	3.2	Gage
108	True position of small outside diameter	0.40%	3.2	Gage
Minor				
201	Radii or chamfers missing	0.65%	3.2	Visual
202	Evidence of poor workmanship	0.65%	3.5	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil - Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

4.5.2: Add new paragraph which reads:

"4.5.2 Salt spray test. Samples selected for this test shall be tested using equipment and procedures in accordance with MIL-STD-810, Method 509.2, Salt Fog. Parts shall be tested with the black powder pellet end up and the pellet cavity inclined approximately six degrees from the vertical in fixturing which does not obstruct the longitudinal flash hole. Parts shall be tested for 96 hours minimum. After testing parts shall be rinsed, dried and examined for evidence of pitting or mottling of the finish, especially on all black powder pellet contact surfaces (rear face of flash tube or cavity in body). The body (dwg. 9293428) prior to rinsing shall be transversely sectioned approximately 0.25 inch from the front face in order to facilitate visual inspection of the cavity. The cutting tool must not remove any part of the black powder pellet cavity. One or more pits or mottling shall be cause for rejection of all anodized parts represented by the sample. After three (3) consecutive lots have been accepted the sampling may be reduced to an AQL of 0.25%, inspection level S-4."

4.5.2: Delete in its entirety and substitute:

* "4.5.2 Salt spray test. Samples selected for this test shall be tested in accordance with MIL-STD-810, Method 509.2, Salt Fog. Bodies shall be tested with the black powder pellet cavity facing up. Flash tubes shall have the small OD end up. Parts shall be inclined approximately six (6) degrees from the vertical, in fixturing which permits easy drainage of the salt solution through the longitudinal flashhole. Parts shall be tested for 96 hours, minimum. After testing, parts shall be rinsed, dried and examined for evidence of pitting or mottling of the finish, with special attention given to the face of the flash tube at the end of the small OD and the black powder cavity in body. One or more pits or mottling shall be cause for rejection of all anodized parts represented by the sample.

For the salt spray test, the lot size shall not exceed the number of parts anodized during one eight (8) hour production period. Sampling of flash tubes or bodies from the anodized lot shall be in accordance with MIL-STD-105, Table IIA, Level S-3 at 0.65% AQL. Samples from more than one anodizing lot may be tested in the same salt spray chamber, however, identity of the components and their representative test specimens must be maintained. After passing the test, anodized lots may be mixed together and identity of the anodized lots is no longer required."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (modifications, additions, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in this notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1395-0096)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.