MIL-F-55608(EL)
AMENDMENT 1
28 May 1975

MILITARY SPECIFICATION

FILTER, INFRARED, INTERFERENCE TYPE, FOR AN/TVS-3

This amendment forms a part of Military Specification MIL-F-55608(EL), dated 15 February 1968, and is approved for use by all Departments and Agencies of the Department of Defense

Page 1

2.1, under Specifications, Military, add:

"MIL-R-52351	Reflector, Light, Parabolic 30 inch Diameter for AN/TVS-3 "

Page 3

3.6, Line 3; Delete "equilibrium temperature of" and substitute "290°F to".

3.8, Delete in its entirety and substitute:

"3.8 Visual security. - There shall be no visible light detectable through the interference coated filter when tested in accordance with 4.6.5."

3.10.1, Line 2; Delete "80°F" and substitute "70°F".

3.10.2, Line 3; Delete "65°F" and substitute "50°F".

Page 6

4.5.2.2, Line 2; Delete "4.5.2" and substitute "4.5.2.1".

Page 9

4.6.1, Line 8, from top of page - After "$\frac{A_1}{A_2}$" add "X 100%".

4.6.2, Delete in its entirety and substitute:

"4.6.2 Spectral transmission. - The spectral transmission of the infrared filter segments shall be measured at not less than four points normal to the plane of the filter. Measurements shall be made with the outside surface temperature of the filter at 70°F to 80°F and again at 290°F to 300°F. Failure to meet the spectral transmission requirements of 3.6 shall constitute failure of this test."

FSC 5855

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:41Z
Check the source to verify that this is the current version before use.

ration pest management operations. Some pest management consultants for the conduct or instal

4.6.3, Line 4; Delete "80°" and substitute "70°".

Line 5; Delete "65°" and substitute "50°".

4.6.5, Delete in its entirety and substitute:

"4.6.5 Visual security. - The filter shall be installed in a AN/TVS-3 searchlight or equivalent and placed in a test area with an ambient illumination not greater than 1 X 10-4 footcandles. The searchlight shall be operated at the 20 kilowatt power level. Three observers having 20/20 vision, normal or corrected, shall be used for this test. The observers shall be dark-adapted for not less than 30 minutes in the same area in which the test will be performed. After the dark adaptation period, each observer shall look at the filter in the center of the beam from a point 1200 meters from the searchlight. Each observer shall then decrease the distance between himself and the light until the light can be detected by visual observation. The point at which each observer can see the light shall be marked and the distance measured from this point to the filter. An average of the three distances greater than 1000 meters shall constitute failure of the test. Duration of viewing the searchlight should be limited to the time necessary for an effective visual security determination and at no time should the observers look directly into the beam at a distance less than 800 meters from the searchlight. The filter shall then be removed from the searchlight and placed on a test fixture over a variable intensity light source located at the focal point of a reflector conforming to MIL-R-52351. The same three observers shall be located 20 feet from the surface of the filter and the room darkened for not less than 30 minutes to enable the observers to become dark adapted. The light source shall be turned on and the light intensity increased until 2 of the 3 observers can detect the light through the filter. The light level shall be measured and recorded."

CUSTODIAN:
ARMY-EL

PREPARING ACTIVITY:
ARMY-EL

Project No.: 5855-A099

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:41Z
Check the source to verify that this is the currentversion before use.