MIL-F-63136(AR)
AMENDMENT 3
22 May 1978
SUPERSEDING
AMENDMENT 2
28 December 1977

MILITARY SPECIFICATION

FUZE, IMPACT, PYROTECHNIC, M733;
DELAY ASSEMBLY FOR

LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-F-63136(AR), dated 11 March 1977.

PAGE 1

Under STANDARDS, MILITARY add the following:

"MIL-STD-331 - Fuze and Fuze Components, Environmental and Performance Tests for"

PAGE 2

Add the following paragraph:

"3.5 Transportation vibration. - The cartridge shall be safe to transport and shall show no evidence of external damage that will affect the intended function."

PAGE 4

Add the following to TABLE I

"Transportation vibration, prior to performing the smoke emission test (cartridges) 50 3.5 4.5.5"

*Delete "Static smoke emission (projectiles) 50 3.2 4.5.3"

*Smoke emission (cartridges). - Change "50" to "50-2-3"

PAGE 5

Paragraph 4.4.1, c. - Delete "Ignition" and substitute "First fire"

FSC: 1390

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:18Z
Check the source to verify that this is the current version before use.

PAGE 6

Paragraph 4.4.2.1. -

Major 101. - Delete "ignition" and substitute "First fire"

*Delete defect characteristic "Major 103" in its entirety.

Add the following major defect characteristic:

"105. Transportation vibration, prior to performing the smoke emission test (cartridges)	3.5	4.4.3.6 4.4.3.7 4.5.5"

PAGE 7

Paragraph 4.4.3.1. - Delete "Ignition" and substitute "First fire"

*Delete "Paragraphs 4.4.3.2, 4.4.3.2.1, 4.4.3.2.2, 4.4.3.2.3 and 4.4.3.2.4" in their entirety.

*Delete "Paragraphs 4.4.3.3, 4.4.3.3.1, 4.4.3.3.2, 4.4.3.3.3 and 4.4.3.3.4", in their entirety and substitute the following:

"4.4.3.3 Static burn time of delay assembly. - One hundred and sixteen (116) delay assemblies shall be selected from each lot and tested as follows:

4.4.3.3.1 Hot temperature. - Eight (8) samples shall be subjected to this test.

4.4.3.3.2 Ambient temperature. - One hundred (100) samples shall be subjected to this test.

4.4.3.3.3 Cold temperature. - Eight (8) samples shall be subjected to this test.

4.4.3.3.4 Rejection . - If four (4) or more samples in ambient phase fail the applicable drawing requirement, the lot represented by the sample shall be rejected. Burning time in hot and cold phase shall be recorded for informational purposes."

Source: https://assist.dla.mil -- Downloaded: 20261010-23T02:18Z
Check the source to verify that this is the current version before use.

PAGE 8

*Delete "Paragraphs 4.4.3.4, 4.4.3.5 and 4.4.3.6" in their entirety.

*Delete "Paragraph 4.4.3.7" in its entirety and substitute the following:

"4.4.3.7 Smoke emission of delay assembly (cartridges) (Dwg. 9323256) . - The Government inspector shall select thirty-two (32) delay assemblies from each lot, assemble into fuzes, assemble into cartridges and subjected to this test. If two (2) or more assemblies fail to comply with the drawing requirement, the lot shall be rejected.

NOTE: Prior to performing this test, the thirty-two (32) cartridges selected shall be packed in their regular shipping containers and subjected to the transportation vibration test specified in 4.5.5. The cartridges shall be unpacked and examined visually for any evidence of the requirements of 3.5."

PAGE 9

*Delete "Paragraph 4.5.3" in its entirety.

Add the following paragraph:

"4.5.5. Transportation vibration. - The cartridges shall be packaged and packed in accordance with Dwgs. 9209204 and 9209205 and tested in accordance with Test No. 104 of MIL-STD-331, except that each box shall be vibrated at the specified amplitudes for three (3) positions (i.e., box positioned so that the cartridges are vertical with case end down, box positioned so that the cartridges are vertical with case end up, and box positioned so that the cartridges are horizontal. After the test, the cartridges shall be examined for the requirements of 3.5. Cartridges shall be used for subsequent tests."

Delete "Section 5" in its entirety and substitute the following:

"5. Packaging

5.1 Preservation and packaging

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:18Z
Check the source to verify that this is the currentversion before use.

5.1.1 Level B. - One-hundred (100) delay assemblies shall be packaged in a 1/2 inch thick Kraft paperboard spacer with 100, .27 inch diameter holes located on 1/2 inch centers except that first row to be located 7/16 inch from edge. Size of spacer to be 5 3/8 inch (+1/16) square. A. 06 inch thick Kraft paperboard sheet 5 3/8 inch (+1/16) square shall be securely glued to the bottom of the spacer. Care to be taken that no glue is present at the bottom of the holes. After packaging the 100 delay assemblies in the spacer assemblies in the spacer assembly (spacer plus .06 Kraft sheet), a 5 3/8 inch (+1/16) square by 1/12 inch thick Kraft Paperboard cover shall be placed on top of the delay assemblies and secured with two strips of Type I, Specification PPP-T-42 masking tape positioned 90° apart. Tape to be 15 inches long by 1 inch wide each.

Eight (8) of the above packs shall be placed in a M2A1 metal box (Dwg. 7553296) or alternate PA2 metal box (Dwg. 9217658) in 4 layers, 2 long. Type I, Style 1, Specification PPP-P-291, cushioning material, 9 1/2 by 4 1/2 inches shall be added on top of contents to obtain a tight pack. Close metal box by securing latch.

5.2 Packing

5.2.1 Level B . - Two (2) metal boxes shall be packed in a Grade A, Type I, Class 1, specification MIL-B-46506 wirebound box. Inside dimensions of wirebound box to be 12 1/4 x 12 1/6 x 7 9/16 inches. Commercial chipboard filler material or specification MIL-F-50449 material shall be used as a separator between metal boxes and between metal box and wood box as required for tight packing. Size of separators to be 10 1/2 x 7 1/16 x 1/16 inch thick. Size of fillers to be 9 x 5 x 1/6 or 7 1/2 x 10 x 1/16 inch thick. The wood box shall be closed in accordance with Dwg. 8796522. Outside dimensions of wood box to be 14 5/8 by 12 13/16 by by 9 1/8 inches.

5.2.2 Palletization (optional). - Forty-eight (48) boxes shall be packed on a 40 by 48 Type 1, any class, specification 9 1/8 high. Boxes to be secured with 3/4 inch wide, Class I, Type I, regular duty, finish A, specification QQ-S-781 with connectors.

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:18Z
Check the source to verify that this is the current version before use.

5.3 Marking. - Metal boxes shall be marked by means of a string tag in accordance with MIL-STD-129. Wooden boxes to be marked by means of an easily removed tag. The DOT marking shall be "Igniters" and in accordance with Code of Federal Regulations, Title 49, Parts 100-199.

5.4 Shipping. - When components from more than one lot are shipped as a carload, each lot shall be kept separate and the division between lots clearly indicated to prevent mixing of lots in transit."

NOTE: This amendment is marked with an asterisk to indicate where changes (addition, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespictive of the notations and relationship to the previous amendment.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number: 1390-A186

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:18Z
Check the source to verify that this is the current version before use.