MIL-G-58083A
AMENDMENT 2
30 January 1988
SUPERCEDING
AMENDMENT 1
~~8 May 1981~~

MILITARY SPECIFICATION

GENERATOR, TACHOMETER, FOUR-POLE, SCREW-MOUNTED

This amendment forms a part of Military Specification MIL-G-58083A, dated 1 June 1967, and is approved for use by all Department and Agencies of the Department of Defense.

PAGE 1

2.1, under SPECIFICATION, Federal:

Delete:	QQ-P-416	Plating, Cadmium (Electrodeposited)
Substitute:	MIL-C-83488	Coating, Aluminum ION Vapor Deposited
Add:	PPP-B-601	Boxes, Wood Cleated, Plywood
	PPP-B-636	Boxes, Shipping Fiberboard

under SPECIFICATION, Military:

Delete:	MIL-E-5272	Environmental Testing, Aeronautical and Associated Equipment, General Specification for

Add boxed paragraph to bottom of page.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Aviation Systems Command, ATTN: AMSAV-ELS, 4300 Goodfellow Blvd., St. Louis, MO 63120-1798, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 6620

DISTRIBUTION STATMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:00Z
Check the source to verify that this is the current version before use.

2.1 under STANDARD, Military

Delete:	MIL-STD-440	Soldering Techniques for Standard Type Solder Terminals
Substitute:	MIL-STD-454	Standard General Requirements for Electronics Equipment
Add:	MIL-STD-810C	Environmental Test Methods.
Delete:	MS33586	Metals, Definition of Dissimilar
Substitute:	MIL-STD-889	Dissimilar Metals
Delete:	MIL-STD-1188	Commercial Packaging of Supplies and Equipment
Substitute:	ASTM D3951	Commercial Packaging, Practice for

2.1, under SPECIFICATION, Air Force - Navy Aeronautical Design Standard:

Delete:	AND10005	Mounting Pad and Drive-Aircraft Tachometer
Substitute:	AND20005	Drive-Type Xv Engine Accessory.

3.1 Delete "AND10005" and substitute "AND20005".

Page 3

Add the following new paragraph:

3.2.1 Recycled, Virgin and Reclaimed Materials. This specification shall require the use of reclaimed materials to the maximum extent possible (see 6.4.).

3.3.4 Delete "MIL-STD-440" and substitute "MIL-STD-454".

3.3.5 Delete "MS33586" and substitute "MIL-STD-889.

Page 4

3.3.6.3 Delete "or cadmium plated in accordance with QQ-P-416" and substitute "ION vapor deposited aluminum coating in accordance with MIL-C-83488".

Page 7

4.4.2, line 2, delete "cps" and substitute "Hz."

4.4.2, line 4, add the following sentence: "Refer to Method 514.2, paragraph 4.2 of MIL-STD-810C for mounting techniques.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:00Z
Check the source to verify that this is the current version before use.

Page 8

4.5.5, line 2, delete "Procedure II of MIL-E-5272" and substitute "Method 514.2, Procedure I, Part 1 (Category b.1), Curve L of MIL-STD-810C, except as specified herein.

4.5.5, line 2, delete "shall be 5 to 250 cps" and substitute "of curve L shall be 5 to 250 Hz."

Page 9

4.5.8, line 2, delete "Procedure II of MIL-E-5272." and substitute "Method 502.1, Procedure I of MIL-STD-810C, except as specified here. Step 2 of Method 502.1 shall have a storage temperature of -62°C (-80°F) and maintained for a 48-hour period in lieu of -57°C and a 24-hour period."

4.5.8, after second insert the following sentence: "The temperature of the chamber for step 4 shall be -54°C (-65°F) and maintained for a 24-hour stabilization period."

4.5.9, line 2, delete "Procedure II of MIL-E-5272" and substitute "Method 501.1, Procedure I of MIL-STD-810C."

4.5.9, change second sentence to read as follows: "At the conclusion of step 3 of Method 501.1 and while still at the test temperature, the generator shall be made to operate two indicators (see 4.4.4) conforming to MIL-I-7098 at a generator speed of 1,400 rpm, and the output voltage shall be noted."

4.5.9, delete third sentence and substitute the following two sentences: "The temperature of the chamber for step 4 shall be 90°C (194°F), plus or minus 2°C, for a 4-hour period. During step 5 the generator shall again operate continuously the same indicators of step 3 at the same generator speed."

Page 10

4.5.15, delete first and second sentences and substitute the following: "The humidity test shall be in accordance with Method 507.1, Procedure I, of MIL-STD-810C, except as specified herein. The internal chamber temperature of step 2 of Method 507.1 shall be 71°C (160°F) in lieu of 65°C. The relative humidity throughout testing shall be 95 percent. Also, the total number of cycles shall be reduced to 5 in lieu of 10. The generator shall be subjected to, and shall meet the requirements of, the test specified in 4.5.2 during step 6."

Page 11

4.5.16, delete title and substitute "Salt fog."

4.5.16, line 2, change "salt spray" to "salt fog."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:00Z
Check the source to verify that this is the current version before use.

4.5.16, line 3, delete "Procedure I of MIL-E-5272." and substitute the following: "Method 509.1, Procedure I, of MIL-STD-810C."

4.5.16, change second sentence to read "At the end of the exposure period, the generator shall be subjected to, and shall meet the requirements of, the tests specified in 4.5.2 and 4.5.6."

5. Delete and substitute. 5. PREPARATION FOR DELIVERY

5.1 Preservation and Packaging. Generators shall be preserved and packaged level A or Commercial, as specified (see 6.2).

5.1.1 Level A. Generators shall be packaged in accordance with Method II of MIL-P-116.

5.1.2 Commercial. Generators shall be packaged in accordance with ASTM D3951.

5.2 Packing. Generators packaged level A or Commercial shall be packed level A, B, or Commercial, as specified (see 6.2).

5.2.1 Level A. Generators shall be packed in PPP-B-601 plywood boxes (overseas type).

5.2.2. Level B. Generators shall be packed in snug-fitting PPP-B-636 fiberboard boxes, class weather-resistant.

5.2.3 Commercial. Generators shall be packaged to ensure carrier acceptance in accordance with ASTM D3951.

5.3 Marking. In addition to any special marking required by the contact, marking shall conform to MIL-STD-129 or ASTM D3951, as specified (see 6.2).

6.2(d) Delete and substitute: "6.2(d) Type of marking required (see 5.3)."

Add the following new paragraph:

6.4 Reclaimed Material. This specification shall require the use of reclaimed materials to the maximum extent possible without jeopardizing the intended end use of the item (see 3.2.1).

6.5 Metric conversion Factors.

6.5.1 Weight. To convert pound (lb) to kilogram (kg), multiply number of pounds by 0.4536.

6.5.2 Inches. To convert inch (in) to Millimeter (mm), multiply number of inches by 25.4.

6.5.3 Torque. To convert pound.force.inch (lb.f.in) to Newton.meter (N.m), multiply by 0.113.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:00Z
Check the source to verify that this is the current version before use.

6.6 Subject Term (Key Word Listing)

Generator, Tachometer

Generator, Tachometer a.c.

Generator, Tachometer, Alternating Current

Tachometer Generator

Tachometer Generator, a.c.

Tachometer Generator, Alternating Current

6.7 Changes From Previous Issue. The margins of this amendment are marked with an asterisk or verticle lines to indicate when changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian
Army - AV
Air Force - 99

User Activity
Navy - CG

Preparing Activity
Army - AV

Project No. 6620-0434

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:00Z
Check the source to verify that this is the current version before use.