MIL-W-63452 (AR)
AMENDMENT 8
18 November 1988
SUPERSEDING
AMENDMENT 7
14 April 1986

MILITARY SPECIFICATION

WARHEAD, GUIDED MISSILE, HE, M207E2
BODY AND BOATTAIL BUSHING FOR

This Amendment forms a part of Military Specification MIL-W-63452 (AR) dated 17 June 1981 and is approved for use within the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

In the specification, wherever "M207E2" appears add "and M207E5". This change is applicable to page 1 (2 places) and pages 4 and 9 (1 place).

In the specification, wherever "9340751" appears delete this number and substitute "9340751-1 or 9340751-2". This change is applicable to page 2 (2 places) and pages 3, 4, 5, 6, 7 and 9 (1 place).

In the specification, wherever "M207E2" and "M207E5" appears, add "M207E6". This change is applicable to page 1, (2 places) and pages 4 and 9 (1 place).

PAGE 6

* 4.4.2.1 Major 101: Delete in its entirety and substitute the following:

"101 Runout of taper with datums A and B 0.40%...3.2 ...Gage"

4.4.2.1 Major 103: Add "See Note 1" at the end of sentence. At bottom of page add Note 1 as follows:

"Note 1. I.D. shall be inspected for entire length".

* 4.4.2.1 Major 110: Delete in its entirety and substitute the following:

"110 Profile of taper between X and Y 0.40%...3.2 ...Gage"

Major 116: Delete "AQL 0.40%" and substitute "100%".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:54Z
Check the source to verify that this is the current version before use.

PAGE 7

4.4.2.1 Add Major defect 122 as follows:

"122 Evidence of raised hanging burrs on exit hole surface of 6 threaded holes, 100%, 3.2, 10X Magnifier."

4.4.2.1 Add Major defect 123 as follows:

"123 Minor diameter of small aft threads, max., 100%, 3.2, Gage."

Minor 205: Delete in its entirety.

4.4.2.1 Minor 208: Delete and substitute:

"208 - Protective finish missing, damaged or incomplete".

4.4.2.1 Add Minor defects 213, 214 and 215 as follows:

"213 Radius on conduit slot, 0.65%, 3.2, Gage.
214 Distance to conduit surface, 0.65%, 3.2, Gage.
215 Angle of conduit surface, 0.65%, 3.2, Gage".

PAGE 8

4.4.2.2 Add Major defect 107 as follows:

"107 Smallest outside diameter, 0.40%, 3.2, Gage."

PAGE 9

Add 4.5.2 as follows:

"4.5.2 Molded components. At the start of production from a new mold, or repair to a mold or cavity, consecutively produced units from each mold or cavity shall be dimensionally examined until 4 consecutive units meet all applicable drawing requirements. After adjustment or repair, those dimensions affected by the adjustment or repair shall similarly be examined. During production, the molding procedures shall be monitored randomly every two hundred units for uniformity of molding practices. Suspected deviations in mold product shall be examined to determine if corrective action or mold repair is required."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:54Z
Check the source to verify that this is the current version before use.

NOTE: The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumed no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document in relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project1336-A591)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:54Z
Check the source to verify that this is the current version before use.