INCH-POUND

MIL-G-52346C(ME)
8 August 1988

SUPERSEDING
MIL-G-52346B(ME)
21 November 1980

MILITARY SPECIFICATION

GUARD, ROADWAY CROSSING

This specification is approved for use within the USA Belvoir Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a roadway crossing guard.

2. APPLICABLE DOCUMENTS

*2.1 Government documents.

*2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

*

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research, Development, and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3835

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

PPP-B-636 - Boxes, Shipping, Fiberboard.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-130 - Identification Marking of US Military Property.
MIL-STD-889 - Dissimilar Metals.

*2.1.2 Government drawing. The following Government drawing forms a part of this specification to the extent specified herein.

DRAWING

ME

13200E4793 - Roadway Crossing Guard.

(Copies of specifications, standards and drawings required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

*2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The roadway crossing guard (hereinafter called "guard") shall be in accordance with drawing 13200E4793, and as specified herein.

3.1.1 Drawing. The drawing forming a part of this specification is an end product drawing. No deviation from the prescribed dimensions or tolerances is permissible without prior

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within those prescribed on the drawing to ensure correct fit, assembly, and operation of the guard. Any data (shop drawings, layouts, flow sheets, processing procedures) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the guard, shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 Material. Material shall be as specified on the applicable drawing. Material not specified shall be selected by the contractor and shall be subject to all provisions of this specification.

*3.2.1 Material deterioration prevention and control. The guard shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable operating and storage environments.

*3.2.1.1 Dissimilar metals. Dissimilar metals shall not be used in intimate contact with each other unless protected against galvanic corrosion. Dissimilar metals and methods of protection are defined and detailed in MIL-STD-889.

*3.2.1.2 Identification of materials and finishes. The contractor shall identify the specific material, material finish or treatment for use with component and subcomponent, and shall make information available upon request to the contracting officer or designated representative.

*3.2.2. Recovered materials. For the purpose of this requirement, recovered materials are those materials that have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces and parts incorporated in the guard may be newly fabricated from recovered materials to the maximum extent practicable, provided the guard produced meets all other requirements of this specification. Used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the guard.

3.3 Identification marking. The guard shall be identified in accordance with MIL-STD-130.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

3.4 Workmanship. The guard shall be free from burrs, sharp edges, or corners, except when sharp edges or corners are required and are not detrimental to safety or cause damage to the hoseline.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

*4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

*4.1.2 Component and material inspection. The contractor is responsible for ensuring that components and materials used are manufactured, examined and tested in accordance with referenced specifications and standards, as applicable.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. Quality conformance inspection (see 4.3).

b. Inspection of packaging (see 4.4).

4.3 Quality conformance inspection.

*4.3.1 Examination. Sampling for examination shall be in accordance with MIL-STD-105. Samples selected shall be examined for the following defects. Presence of one or more defects shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

Major

101. Dimensions not as specified (see 3.1, 3.1.1).
102. Material not as specified (see 3.2).
103. Materials not resistant to corrosion and deterioration, or treated to be resistant to corrosion and deterioration for the applicable storage and operating environments (see 3.2.1).
104. Dissimilar metals as defined in MIL-STD-889 are not effectively insulated from each other (see 3.2.1.1).
105. Contractor does not have documentation available for identification of material, material finishes, or treatment (see 3.2.1.2).
106. Used, rebuilt or remanufactured components, pieces, or parts incorporated in the guard (see 3.2.2).
107. Identification marking missing, incomplete or illegible (see 3.3).
108. Workmanship not as specified (see 3.4).

4.4 Inspection of packaging.

4.4.1 Quality conformance inspection.

*4.4.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.4.1.2 Sampling. Sampling for inspection shall be in accordance with MIL-STD-105.

*4.4.1.3 Examination. Samples selected in accordance with 4.4.1.1 shall be examined for the following defects.

109. Packing not as specified for level A or C.
110. Guards not bundled in quantities specified in the contract or order.
111. Bundle not tightly and compactly formed.
112. Bundle not secured through the center holes on each side.
113. Marking illegible, incomplete, incorrect, or missing.

5. PACKAGING

*5.1 Preservation. Each guard shall be treated with corrosion preventive as specified on Drawing 13200E4793, and no preservation is required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A or C, as specified (see 6.2).

*5.2.1 Level A. The guards in quantities of 10 or less, shall be tightly nested together to form a compact bundle. The bundle shall be secured through the center and two end holes, on each side, with soft annealed wire. The bundles shall be secured to a skid base, the weight of the material shall not exceed 3000 pounds.

*5.2.2 Level C. Guard shall be nested in bundles and packed in boxes in accordance with PPP-B-636, domestic type. The qualities packed shall not exceed the size or weight limitations of the box. Box closure and strapping shall be in accordance with the appendix of the box specification.

*5.3 Marking (see 6.3). In addition to any special marking required by the contract or order, shipping containers, shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The guard is intended for use with a 4-inch, lightweight, collapsible hoseline system.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Degree of packing required (see 5.2).

6.3 Marking for degree of protection. Since no preservation is required, the degree of protection marking for items packed level A shall be any acceptable method.

*6.4 Subject term (key word) listing.

Guard, Crossing
Guard, Hoseline
Guard, Roadway

*6.5 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army - ME

Preparing activity:
Army - ME

Review activity:
DLA - CS

Project 3835-A088

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
Belvoir RD&E Center
ATTN: STRBE-TSE
Fort Belvoir, VA 22060-5606

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-G-52346C(ME)	Guard, Roadway Crossing

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.