MIL-T-82309(ONR/NTDC)
21 January 1965
SUPERSEDING
NAVTRADEVCEN 353-124
30 November 1960

MILITARY SPECIFICATION

TRAINER, FLAG HOIST

This specification has been approved by the Office of Naval Research (U. S. Naval Training Device Center), Department of the Navy.

1. SCOPE

1.1 This specification covers one type of flag hoist trainer used for teaching flag hoist procedure and familiarization.

1.1.1 This item has been designated by the Office of Naval Research (U. S. Naval Training Device Center) as Device 29HP1 for Navy procurement (see 6.2).

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on the date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Federal

| | |
|---|---|
| PPP-B-621 | Boxes, Wood, Nailed and Lock corner |
| PPP-B-636 | Box, Fiberboard |

Military

| | |
|---|---|
| MIL-P-116 | Preservation; Methods of |
| MIL-L-10547 | Liners, Case and Sheet Overwrap, Water-Vaporproof or Waterproof, Flexible |

STANDARDS

Military

| | |
|---|---|
| MIL-STD-129 | Marking for Shipment and Storage |

FSC 6910

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:02Z
Check the source to verify that this is the current version before use.

DRAWINGS

U. S. Naval Training Device Center

| | |
|---|---|
| No. 1101 | Assembly Drawing, Flag Hoist Trainer Device 29HP1 |

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials.- Unless otherwise specified herein, materials shall be as specified on the drawings of 2.1. Materials not specified herein or on the drawings shall be selected on the basis of compatibility with the established design and suitability to the specific application in satisfying the performance requirements specified herein.

3.2 Design.- The trainer as shown on the drawings of 2.1 shall be a small stylized model of a flag locker equipped with four simulated halyards, a yardarm, and a truck.

3.2.1 Interchangeability.- All parts, subassemblies and assemblies having the same part number shall be directly and completely interchangeable with each other in respect to installation and performance, regardless of sources from which obtained, without alteration and without selection for fit or performance.

3.3 Construction.- Construction shall be as shown on the drawings of 2.1, utilizing the Government-loaned molds and dies.

3.4 Performance.- The trainer shall be so constructed as to insure the proper performance of the flags and pennants in the halyards and truck. The flag tabs and tacks shall slide up and down the halyard and truck slots freely and shall not bind.

3.5 Details of components.- The trainer shall consist of the following major components, the details of which shall be as shown on the drawings of 2.1:

(a) Carrying case
(b) Halyards, yardarm and truck
(c) Flags, pennants and tacks.

3.5.1 Carrying case.- The carrying case shall consist of a top and bottom section made of Boltaron, or equal. The lower section of the case shall contain a tray for storing the flags and pennants. The tray shall



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:02Z
Check the source to verify that this is the current version before use.

contain two identification strips printed in color, and made of the same material as the flags and pennants. The top section of the case shall be used to store the halyards, yardarm and truck.

3.5.2 Halyards, yardarm and truck.- The halyards, yardarm and truck shall be fabricated of hardwood.

3.5.2.1 Each of the four halyards shall contain eight bar magnets to hold the flags and pennants, and the truck shall contain three bar magnets.

3.5.3 Flags, pennants, and tacks.- The carrying case shall contain three each of 68 different flags and pennants, plus three each of four sets of tacks.

3.6 Dimensions and tolerances.- Dimensions and tolerances shall be as shown on the drawings of 2.1. Tolerances not shown on the drawings shall be maintained to assure meeting the interchangeability and performance requirements specified herein.

3.7 Finish and color.-

3.7.1 Finish.- Finish shall be as shown on the drawings of 2.1.

3.7.2 Color.- The color shall be as shown on the Government-loaned sample device.

3.8 Nameplates or product markings.-

3.8.1 Nameplate.- A Government-furnished nameplate shall be affixed to the trainer in a location designated by the contracting officer.

3.9 Government-furnished property.- One nameplate will be furnished by the Government for each trainer.

3.10 Government-loaned property.- The following property will be loaned by the Government:

| | | |
|---|---|---|
| (a) | Flag Hoist Trainer, Device 29HP1 | - - 1 |
| (b) | Forming molds for case and flag trainer | - - 3 |
| (c) | Stamping dies for flags and pennants | - - 2 |

3.11 Workmanship.- The trainer shall be constructed and finished with particular attention given to neatness, thoroughness of marking of parts and assemblies, sanding, painting, riveting and assemblage.

3.11.1 Cleanup.- Units shall be thoroughly cleaned of foreign material after final assembly.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:02Z
Check the source to verify that this is the current version before use.

## 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection.- Inspections to be performed are classified as follows:

(a) In-process inspection
(b) Quality conformance inspection.

4.3 In-process inspection.- In-process inspection shall include such visual and mechanical examinations and testing of materials, subassemblies, parts, and accessories (including purchased standard items) during the manufacturing process as may be necessary to assure conformance to all the requirements specified herein.

4.4 Quality conformance inspection.-

4.4.1 Preproduction inspection.- Preproduction inspection shall be conducted on the preproduction sample and shall consist of all the examinations and tests specified herein.

4.4.2 Production inspection.- Production units shall be inspected to the extent necessary to maintain quality control and conformance to the Government-accepted preproduction sample.

4.5 Examinations.- Examinations shall be performed to verify conformance to the following requirements:

(a) Materials
(b) Construction
(c) Dimensions and tolerances
(d) Finish and color
(e) Nameplates or product markings
(f) Workmanship
(g) Preparation for delivery.

4.6 Performance test.- A performance test shall be conducted to verify conformance to 3.4.

## 5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.- Preservation and packaging shall be level A or C (see 6.2).



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:02Z
Check the source to verify that this is the current version before use.

5.1.1 Level A.- For level A, each trainer shall be preserved and packaged for mechanical and physical protection in accordance with Specification MIL-P-116, Method III.

5.1.1.1 Unit packaging.- Each trainer shall be packaged one unit to a container conforming to Specifications PPP-B-636.

5.1.2 Level C.- For level C, preservation and packaging shall conform to manufacturer's commercial practice.

5.2 Packing.- Packing shall be level A or C (see 6.2).

5.2.1Level A.-Units packaged in accordance with 5.1.1 shall be packed in exterior containers conforming to Specification PPP-B-621. Unless otherwise specified by the procuring activity (see 6.2), the gross weight shall not exceed the weight limitations of the shipping container. Each exterior shipping container shall be lined with a waterproof moisture barrier sealed with adhesive or tape to effect water resistance in accordance with Specification MIL-L-10547. A case liner shall not be required where the package(s) and package dunnage have been treated to resist water. Unit fiber boxes, conforming to Specification PPP-B-636 class 2, closed, reinforced and waterproofed as specified in the appendix thereto, and used as shipping containers, shall not be overpacked.

5.2.2 Level C.- Units packaged in accordance with 5.1.2 shall be packed in containers which will insure acceptance by common carrier and safe delivery at destination. Shipping containers shall comply with common carrier rules and regulations as applicable to the mode of transportation and may be the supplier's commercial practice when such meets the requirements of this level.

5.3 Physical protection.- All material shall be packaged and packed in containers constructed to provide a compact and nonshifting load. Adequate cushioning, blocking and bracing shall be provided within shipping containers in a manner designed to prevent damage due to shock, vibration or impact during shipment, handling and storage.

5.4 Marking.- Interior packages and exterior shipping containers shall be marked in accordance with Standard MIL-STD-129.

6. NOTES

6.1 Intended use.- The trainer will be used by military personnel to familiarize them with the international alphabet flags, phonetic and semaphore alphabet.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number, and date of this specification
(b) Procuring activity designation (device number or other)(see 1.1.1)



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:02Z
Check the source to verify that this is the current version before use.

(c) Selection of applicable levels of preservation, packaging, and packing (see 5.1 and 5.2)

(d) Gross weight of shipping container (see 5.2.1)

6.3 Definitions.- Except as specified herein, definitions will be furnished upon written request to the procuring activity.

6.3.1 Preproduction sample.- A production item furnished under production contracts for the purpose of determining compliance with requirements of the detail training device specification already established and accepted. It shall be electrically and mechanically representative of production sets though not necessarily made with production line jigs, fixtures, and methods.

6.3.2 Production unit.- A unit in its final mechanical and electrical form of final production design made by production tools, jigs, fixtures and methods.

6.3.3 Training device.- An item designed exclusively for training purposes and which falls into one of the following categories:

(a) Trainer -- A training device designed to provide a synthetic situation in which human skills or techniques are developed or improved by direct participation of trainee.

(b) Training aid -- A training device designed to demonstrate or illustrate a concept.

Specifically excluded are training-type operational equipment such as training aircraft and all other ordnance, electronics and transportation equipment designed for operating use as distinguished from training purposes, and which are or may be used in a training situation.

Custodian:
Navy-TD

Preparing activity:
Navy - TD



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:02Z
Check the source to verify that this is the current version before use.

# SPECIFICATION ANALYSIS SHEET

Form Approved Budget Bureau No. 119-R004

**INSTRUCTIONS**

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

| ORGANIZATION | CITY AND STATE |
|---|---|
| | |

| CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT |
|---|---|---|
| | | $ |

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

| SUBMITTED BY *(Printed or typed name and activity)* | DATE |
|---|---|
| | |

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:02Z
Check the source to verify that this is the current version before use.