MIL-A-23404A (AS)
2 December 1982
SUPERSEDING
MIL-A-23404 (Wep)
25 July 1962

MILITARY SPECIFICATION

ADAPTER KIT, MARINE MARKER MK 34 MOD 0

This specification is approved for use by the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification establishes the requirements for the manufacture and inspection of the Adapter Kit, Marine Marker, MK 34, Mod 0.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.
MIL-STD-1168	Ammunition Lot Numbering.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Engineering Specifications and Standards Department (Code 93), Naval Air Engineering Center, Lakehurst, NJ 08733 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 1370

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:38Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

NAVAL AIR SYSTEMS COMMAND

LD282828	Adapter Kit, Marine Marker, MK 34 Mod 0.
LD282830	Box, Shipping and Storage, Marine Adapter Kit.
SA2522913	Assembly, Test Fixture, MK 34 Kit.
1331991	Package, Shipping, Storage.
1212853	Adapter Kit.
1212851	Leaf Spring Assembly.
1129618	U Pin.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified, a sample shall be subjected to first article inspection (see 4.3 and 6.3).

3.2 Material. Unless otherwise specified in the contract, or purchase order, all materials and purchased parts entering into the final assembly of the adapter shall conform strictly to the detail requirements indicated on the drawings and specifications listed on LD 282828 or as specified herein.

3.3. Design and construction. The assemblies and component parts of the adapter kit (drawing 1212853) shall be of the design, construction and physical dimensions specified in LD282828. The adapter kit shall consist of a cadmium plated steel retainer nominally three inches in diameter and 2-1/16 inches deep. A coil spring, approximately two inches in diameter, shall be secured in the bottom of the retainer. A cadmium plated steel spring assembly shall have a plug seal at each end and shall be attached to the coil spring with a wire.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:38Z
Check the source to verify that this is the current version before use.

3.4 Performance characteristics.

3.4.1 Sealing. The adapter kit shall withstand an external hydrostatic pressure of 4.5 psig minimum to 6.0 psig maximum for a minimum period of 30 seconds without leakage into the fuze simulator cavity when tested as specified in 4.5.1.

3.4.2 Leaf spring embrittlement. The leaf spring (drawing 1212851) shall not crack or break when tested as specified in 4.5.2.

3.5 Workmanship. The product, in all stages of production, shall be processed under such inspection control as to assure uniformity in quality. There shall be no imperfections or deviations from the specification affecting the functioning or assembly of the product. Where applicable, all material shall be free of pits, corrosion, cracks, spalls, rough edges, etc. All components shall be free of chips, dirt, grit, or other foreign material. The cleaning methods used shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents employed.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure suppplies and services conform to prescribed requirements.

4.2 Classification of inspections. The inspections specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

4.3 First article inspection. First article inspection shall be performed at a laboratory acceptable to the Government on sample units produced with equipment and procedures normally used in production. First article inspection shall consist of all the tests of this specification as specified under inspection methods (see 4.5).

4.3.1 Sample. Unless otherwise specified (see 6.3) in the contract or purchase order, the first article sample shall consist of forty adapter kits. Approval of the first article shall be based on no defects allowed in a unit.

4.4 Quality conformance inspection. Quality conformance inspection shall consist of all the tests specified under inspection methods (see 4.5).

4.4.1 Inspection lot. Unless otherwise specified by the procuring agency, each inspection lot shall consist of 3000 units. The inspection lot definition, formation and size shall be in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:38Z
Check the source to verify that this is the current version before use.

4.4.2 Sampling plan. Samples shall be selected at random from the inspection lot. For the sealing test (see 4.5.1), samples shall be inspected in accordance with MIL-STD-105, special inspection level S-4, acceptance quality level (AQL) 2.5 percent defective. For the leaf spring embrittlement test (see 4.5.2), failure of one or more leaf springs (drawing 1212851) shall be cause for rejection of the inspection lot represented.

4.5 Inspection methods.

4.5.1 Sealing. Sample adapter kits shall be assembled on the fuze simulator, drawing SA2522913, sheet 6, with the U-pin (drawing 1129618) in place and submerged in water under hydrostatic pressure as specified in 3.4.1. Release the pressure and remove from tank. Adapter kits shall be inspected through the plastic end for presence of water in the fuze simulator cavity. Defectives are adapter kits failing to meet the requirements of 3.4.1.

4.5.2 Leaf spring embrittlement. After completion of the seal test, all samples shall be subjected to the leaf spring embrittlement test as follows. Remove seal plugs. Wrap the leaf spring (drawing 1212851) around a two inch diameter rod and leave for a period of 165 +15 hours. The leaf spring may be held by tape or any other method that does not add support to the spring. Defectives are lead springs failing to meet the requirements of 3.4.2.

4.5.3 Examination. Adapter kits shall be inspected for conformance to the requirements of this specification with respect to material, design, construction and workmanship (see 3.2, 3.3 and 3.5).

4.5.4 Inspection of packaging. The sampling and inspection of the packing and container marking shall be in accordance with LD282830, 1331991, MIL-STD-129 and MIL-STD-1168 (see 5.2 thru 5.3.2).

5. PACKAGING

5.1 Preservation. Not applicable.

5.2 Packing. Packing shall be level A only.

5.2.1 Level A. Sixty adapter kits shall be packed in accordance with LD282830 per container drawing 1331991.

5.3 Marking.

5.3.1 Normal marking. Boxes shall be marked in accordance with container drawing 1331991. Marking shall conform to the requirements of MIL-STD-129.

5.3.2 Ammunition lot number. Ammunition lot number shall be in accordance with MIL-STD-1168.

6. NOTES

6.1 Intended use. The Adapter Kit, Marine Marker, MK 34, Mod 0 is intended for use with the Marker, Location, Marine MK 25, Mod 0 in the gravity drop equipment on aircraft.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:38Z
Check the source to verify that this is the current version before use.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Quantity required.

c. First article inspection (see 6.3).

6.3 First article. When a first article inspection is required, the item will be tested and should be a first article sample. When a contractor is in continuous production of adapter kits from contract to contract, consideration should be given to waive the first article inspection. The contracting officer shall include specific instructions in the contract or purchase order regarding arrangements for examinations, tests and disposition.

6.4 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Navy - AS

Preparing Activity:
Navy - AS
(Project No. 1370-N177)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:38Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer
Naval Air Engineering Center
Engineering Specifications & Standards
Department (ESSD) Code 93
Lakehurst, NJ 08733

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:38Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. *PROBLEM AREAS*

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:38Z
Check the source to verify that this is the current version before use.