MIL-B-23388A
24 September 1969
SUPERSEDING
MIL-B-23388
26 July 1962

MILITARY SPECIFICATION

BURSTERS FOR WP FILLED 5-INCH 54-CALIBER AND 6-INCH 47-CALIBER PROJECTILES; LOADING AND PACKING

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the loading and packing of bursters used in WP-filled 5-inch 54-caliber and 6-inch 47-caliber projectiles.

1.2 Classification. The bursters shall be of the following types (see 6.1):

Type I - 5 inch 54 caliber (Dwg 2092845).
Type II - 6 inch 47 caliber (Dwg 1253381).

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

QQ-S-781 - Steel Strapping, Flat.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-C-843 - Cushioning Material, Cellulosic.
PPP-F-320 - Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.

FSC 1320

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:36Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-C-440 - Compositions A-3 and A-4.
MIL-C-3955 - Cans, Fiber, Spirally Wound.
MIL-T-43036 - Tape, Pressure-Sensitive Adhesive, Plastic Film, Filament Reinforced (For Sealing Fiber Containers and Cans).

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedure and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

DRAWINGS

NAVAL ORDNANCE COMMAND

LD No. 289025 - Projectile, Smoke, WP, 6"/47 MK41, - List of Drawings, Subassemblies and Parts (3 sheets).
LD No. 289028 - Projectile, Smoke, WP, 5"/54 MK48, Mod 1 - List of Drawings, Subassemblies and Parts (3 sheets).

US ARMY MUNITIONS COMMAND

EDGEWOOD ARSENAL

D150-2-1 - Marking Diagram for Shipping Containers.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

CODE OF FEDERAL REGULATIONS

49 CFR 171-179 - Department of Transportation Rules and Regulations for the Transportation of Explosives and Other Dangerous Articles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:36Z
Check the source to verify that this is the current version before use.

(The Department of Transportation regulations are a part of the Code of Federal Regulations available from the Superintendent of Documents, Government Printing Office, Washington, D. C. 20402. Orders for the above publication should cite "49 CFR 171-179.")

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing LD No. 289028 and LD No. 289025 or on the subsidiary drawings shall conform to the specifications listed thereon, or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the burster shall conform to the specifications and drawings listed on Drawing LD No. 289028 and LD No. 289025 and subsidiary drawings.

3.2 Loading. The burster tube shall be loaded as shown on Drawing 2092845 or 1253381 and table I (see 6.2). All loose particles on the surface shall be removed.

Table I. Weight of explosives

Drawing	Ingredient	Specification	Explosive weight
2092845 (5"/54)	Composition A-3	MIL-C-440	0.45 lb min
1253381 (6"/47)	Composition A-3	MIL-C-440	0.86 lb min

3.3 Weight. The weight of the explosive shall conform to table I when tested in accordance with 4.2.4.

3.4 Workmanship. The loaded burster shall be free from contamination, oil, grease, and deformation which would affect its intended use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:36Z
Check the source to verify that this is the current version before use.

any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Quality conformance inspection.

4.2.1 Lotting. A lot shall consist of like bursters of one interfix number, produced by one manufacturer, under essentially the same loading conditions. However, no more than one lot of composition A-3 shall be used in any one lot of loaded bursters.

4.2.2 Sampling for examination and nondestructive test. Sampling shall be conducted in accordance with MIL-STD-105.

4.2.3 Inspection provedure.

4.2.3.1 For examination and nondestructive test. Sample bursters shall be examined in accordance with the classification of defects and with MIL-STD-105.

4.2.3.2 Classification of defects.

(a) Burster charge subassembly and burster charge (Dwg 2092845 and Dwg 1253381).

Categories	Defects
Critical:	None defined.
Major:	AQL 1.0 percent defective
101	Component missing or incorrectly assembled.
102	Overall length or outside diameter incorrect.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:36Z
Check the source to verify that this is the current version before use.

4.2.3.2 Classification of defects (continued).

(a) Burster charge subassembly and burster charge (Dwg 2092845 and Dwg 1253381) (continued).

Categories	Defects	Acceptance standards
Major:	AQL 1.0 percent defective	
103	Cavity diameter or depth incorrect.	
104	Sealing compound missing or incorrect.	
*105	Protective finish, interior and exterior, missing or incorrect.	
106	Camber excessive.	
107	Loose particles on surface.	
108	Weight incorrect.	4.2.4
Minor:	AQL 2.5 percent defective	
201	Marking illegible or incorrect	
202	Workmanship (3.4)	

*To be checked prior to loading.

4.2.4 Weight test. The burster tube (Drawings 1253382 and 1253397) shall be weighed before and after loading and the net weight of the composition A-3 calculated.

5. PREPARATION FOR DELIVERY

5.1 Packaging, level C. The bursters shall be individually packaged in type II, grade B, style a, class 1 fiber can conforming to MIL-C-3955. Prior to bursters being placed in cans, type II, class b cellulose wadding conforming to PPP-C-843 shall be tightly packed into open end of burster. Circular filler pads conforming to type CF, class weather resistant, fiberboard of PPP-F-320 shall be cut to a diameter that will allow pads to fit snugly inside of the cans. One pad shall be placed on the bottom of the can and after the burster is placed in the can another pad shall be placed on top of the burster. Additional pads shall be used as required to make a tight pack. The fiber can shall be closed and the cover secured in place with minimum 1-1/2 inch wide tape, color yellow No. 13538 conforming to MIL-T-43036 (see 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:36Z
Check the source to verify that this is the current version before use.

5.2 Packing, level C. One-hundred bursters, weighing approximately 150 lb, of the same size packaged as specified in 5.1, shall be packed in a class 1, style 2, $2\frac{1}{2}$, 4 or $4\frac{1}{2}$ nailed wood box conforming to PPP-B-621. Filler pads, fabricated from type CF, class domestic, conforming to PPP-F-320, shall be utilized to insure a tight pack. The box shall be closed in accordance with the requirements of PPP-B-621, and strapped using type 1, class A, grade 2 of QQ-S-781.

5.3 Marking. In addition to any special marking required by the contract or order, unit packages and the shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type of burster.

6.2 Precautions. Due to the hazardous nature of loading munitions of this type, suppliers are advised to take all necessary precautions to protect personnel from injury.

6.3 Color code. The tape is used for ammunition color code marking as well as for sealing the closure seam on the fiber can (unit package).

Custodians:

Army - MU
Navy - OS
Air Force - 70

Preparing activity:

Army - MU(EA)

Project No. 1320-0103

Review activities:

Navy - OS
Air Force - 70

1

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:36Z
Check the source to verify that this is the current version before use.