MILITARY SPECIFICATION

MEASURING SET, DEPTH-SOUND SPEED

AN/BQH-1( )

This amendment forms a part of Military Specification MIL-M-23416(SHIPS), 26 November 1962.

Pages 6 and 7, paragraphs 3.6.4.3 and 3.6.4.4: Delete.

Page 7, paragraph 3.6.4.8: Delete and substitute:

"3.6.4.8 Accuracy.- On the 0- to 800-foot scale, the absolute error shall be no greater than 2.5 feet and on the 700- to 1500-foot scale, the absolute errors shall be no greater than 5 feet, when operated at the voltage and frequency specified in 3.6.4.1. The maximum deviation of depth indication on both scale ranges under the extreme line voltage and frequency variations of 3.2.2 shall be not greater than plus or minus 5 feet. Absolute depth shall be determined by a dead weight tester using 44.5 pounds per square inch pressure for 100 feet of depth."

Page 7, paragraph 4.1: Delete and substitute:

"4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements."

Preparing activity:
Navy - SH
(Project 6625-N398Sh)

FSC 6625

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:40Z
Check the source to verify that this is the current version before use.