INCH-POUND
MIL-DTL-24643/10D
1 October 2009
SUPERSEDING
MIL-DTL-24643/10C
22 August 2002

DETAIL SPECIFICATION SHEET

CABLE, ELECTRICAL, -20 °C TO +90 °C, TYPE LSPBTMU

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-24643.

Construction, Watertight

First	-	One copper and one constantan conductor for each pair, uncoated. 22 AWG, Class K stranding. The conductor shall have a cross-sectional area between 672 cma and 728 cma. Temperature/electromotive force relationship shall follow ANSI MC96.1. Any necessary joints in the individual strands shall be silver-soldered for copper, and welded for constantan.
Second	-	Separator may be used at manufacturer's option where required to provide free-stripping insulation.
Third	-	Thermoset insulation. Minimum average wall thickness of 0.015 inch. Telephone identification code applied by Method 3.
Fourth	-	Each pair shall be one copper and one constantan conductor cabled together with a lay not greater than 3 inches.
Fifth	-	The specified number of pairs (see table I) shall be cabled in accordance with 3.4.4 of MIL-DTL-24643. Fillers may be used as necessary to form a firm, well-rounded assembly. Cabling sequence shall be consecutive, starting with pair no. 1, from the center outward.
Sixth	-	An optional binder.
Seventh	-	Cross-linked polyolefin jacket. Minimum average wall thickness of 0.040 inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:56Z
Check the source to verify that this is the current version before use.

TABLE I. Details.

Military part no. M24643/10	Type and size	Number of pairs	Overall diameter	
			min. (inch)	max. (inch)
-01UN	LSPBTMU-5	5	0.499	0.540
-02UN	LSPBTMU-15	15	0.694	0.750
-03UN	LSPBTMU-30	30	0.907	0.980

REQUIREMENTS:

Qualification required.

INSPECTION:

Basic Electricals:	
ANSI MC96.1 calibration limits of error	±1 °C
Voltage withstand (volts, root mean square, min.)	
Conductor to conductor	1000
Insulation resistance (megohms/1000 feet, min.)	
Conductor to conductor	100
Conductor continuity	No failure
Group A:	
Visual and dimensional	No failure
Watertightness (see MIL-DTL-24643 for limits of water leakage)	No failure
Group B:	
Cold bending cable	No failure
Thermoset proof test (percent, max.)	
Insulation	50
Jacket (when tested at 200 °C)	50
Drip (95±1 °C)	Zero
Physicals (unaged)	
Insulation (extruded)	
Tensile strength (lb/in^2, min.)	700
Elongation (percent, min.)	150
Jacket (cable)	
Tensile strength (lb/in^2, min.)	1300
Elongation (percent, min.)	160

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:56Z
Check the source to verify that this is the current version before use.

Tear (lb/in thickness, min.)	35
Group C:	
Physicals (aged) air oven	
Insulation (extruded)	
Tensile strength (percent of unaged, min.)	75
Elongation (percent of unaged, min.)	75
Jacket (cable)	
Tensile strength (percent of unaged, min.)	60
Elongation (percent of unaged, min.)	60
Permanence of printing (jacket) (cycles, min.)	125
Heat distortion (percent of unaged, max.)	30
Cable fill (sealant) removability	No failure
Shrinkage	No failure
Group D:	
Flame propagation (cable)	No failure
Qualification Inspection:	
Qualification inspection shall include basic electricals; groups A, B, C, and D; plus the following:	
Aging and compatibility (cable) (125±5 °C)	No failure
Abrasion resistance (jacket) (scrapes, min.)	75
Acid gas equivalent (percent, max.)	
Jacket	2
Fillers	2
Insulation	18
Halogen content (percent, max.)	
Jacket	0.2
Fillers	0.2
Insulation	0.2
Immersion (jacket)	
Tensile strength (percent of unaged, min.)	50
Elongation (percent of unaged, min.)	50
Smoke index (max.)	
Jacket	25
Fillers	45

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:56Z
Check the source to verify that this is the current version before use.

Insulation	45
Toxicity index (max.)	
Jacket	5
Fillers	5
Insulation	1.5
Durometer (jacket) - Type A (hardness, min.)	80
Weathering (jacket)	No failure
Electrical moisture absorption	No failure

UNIT ORDERING LENGTHS:

Type and size	Feet (nominal)
LSPBTMU-5	2500
LSPBTMU-15	1500
LSPBTMU-30	1000

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army – MI
Navy – SH

Preparing Activity:
Navy – SH
(Project 6145-2008-014)

Review Activities:
Army – AR, AV, CR
Navy – CG, EC
DLA – CC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:56Z
Check the source to verify that this is the current version before use.