INCH-POUND
MIL-DTL-24643/4E
1 October 2009
SUPERSEDING
MIL-DTL-24643/4D
22 August 2002

DETAIL SPECIFICATION SHEET

CABLE, ELECTRICAL, -20 °C TO +90 °C, 600 VOLTS, TYPE LSMCOS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-24643.

Construction, Non-Watertight

First	-	Copper conductor, coated or uncoated, Class K (see table I for size).
Second	-	Separator may be used at manufacturer's option where required to provide free-stripping insulation.
Third	-	Thermoset insulation (see table I for wall thickness) – Sizes 2, 4, and 7 shall have special identification code applied by Method 3. Size 5 shall have one shielded pair (colors black and white) and 3 singles (colors red, green, and blue) applied by Method 3. Size 6 shall have two shielded pairs (colors black and white for first pair and blue and red for second pair) and two singles (colors yellow and green) applied by Method 3.
Fourth	-	(For all pairs only) An optional binder.
Fifth	-	(For all pairs only) Braided shield of 34 or 36 AWG coated or uncoated copper. Braid angle 30 to 35 degrees; minimum coverage of 88 percent.
Sixth	-	The required number of singles and shielded pair(s) to be cabled together with a left-hand lay. The length of lay (pairs and cables) shall be as required for the completed cable to meet the twisting and bending endurance tests; and for Sizes 5 and 6, the additional mutual inductance test. Fillers may be used as necessary to form a firm, well-rounded assembly. A single conductor (or pair) shall not be used as a central core for the cable. The Size 7 cable shall have a central core of fiberglass.
Seventh	-	An optional binder.
Eighth	-	Braided shield of 34 or 36 AWG coated or uncoated copper. Braid angle of 30 degrees minimum; minimum coverage of 88 percent.
Ninth	-	An optional binder.
Tenth	-	Cross-linked polyolefin jacket. Minimum average wall thickness of 0.040 inch.

NOTE: Omit eighth and ninth construction steps for Sizes 5 and 6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:53Z
Check the source to verify that this is the current version before use.

TABLE I. Details.

Military part no. M24643/4	Type and size	Conductors		Insulation thickness min. average (inch)	Overall diameter		Voltage withstand conductor to conductor (volts)	Insulation resistance minimum (megohms)	Conductor resistance maximum (ohms)
		No. of condr.	AWG		min. (inch)	max. (inch)			
-01UO	LSMCOS-2	2	18	0.023	0.440	0.460	2000	200	6.96
-02UO	LSMCOS-4	4	18	0.023	0.490	0.510	2000	200	6.96
-03UN	LSMCOS-5	5	20	0.013	0.375	0.390	1000	100	11.28
-04UN	LSMCOS-6	6	20	0.013	0.460	0.480	1000	100	11.28
-05UO	LSMCOS-7	7	18	0.023	0.575	0.595	2000	200	6.96

REQUIREMENTS:

Qualification required.

INSPECTION:

Basic Electricals:

Conductor resistance (ohms/1000 feet at 25 °C, max.)	See table I
Voltage withstand (volts, root mean square, min.)	
Conductor to conductor	See table I
Conductor to shield (pair or overall)	500
Overall shield to ground (LSMCOS-2, -4, and -7 only)	1500
Insulation resistance (megohms/1000 feet, min.)	
Conductor to conductor	See table I
Conductor to shield (pair or overall)	See table I
Conductor continuity	No failure
Shield continuity	No failure
Group A:	
Visual and dimensional	No failure
Group B:	
Cold bending (flexing cable)	No failure
Thermoset proof test (percent, max.)	
Insulation	50
Jacket (when tested at 200 °C)	50
Physicals (unaged)	
Insulation (extruded)	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:53Z
Check the source to verify that this is the current version before use.

Tensile strength (lb/in^2, min.)	700
Elongation (percent, min.)	150
Jacket (cable)	
Tensile strength (lb/in^2, min.)	1300
Elongation (percent, min.)	160
Tear (lb/in thickness, min.)	35
Twisting and bending endurance	
At 75 °C (cycles, min.)	6000
At minus 30±2 °C (cycles, min.)	2000

NOTE: Roller diameters for bending endurance test shall be as follows:

Cable type and size	Roller diameter (inch, max)
LSMCOS-2	1.4
LSMCOS-4	1.5
LSMCOS-5	1.2
LSMCOS-6	1.4
LSMCOS-7	1.8

Group C:	
Physicals (aged) air oven	
Insulation (extruded)	
Tensile strength (percent of unaged, min.)	75
Elongation (percent of unaged, min.)	75
Jacket (cable)	
Tensile strength (percent of unaged, min.)	60
Elongation (percent of unaged, min.)	60
Permanence of printing (jacket) (cycles, min.)	125
Heat distortion (percent of unaged, max.)	30
Shrinkage	No failure
Mutual inductance (LSMCOS-5 and LSMCOS-6 only)	
Microhenries (max.)	0.0135
Shield (conformance to material, construction and coverage)	No failure
Group D:	
Flame propagation (cable)	No failure

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:53Z
Check the source to verify that this is the current version before use.

Qualification Inspection:

Qualification inspection shall include basic electricals; groups A, B, C, and D; plus the following:

Aging and compatibility (cable) (125±5 °C)	No failure
Abrasion resistance (jacket) (scrapes, min.)	75
Acid gas equivalent (percent, max.)	
Jacket	2
Fillers	2
Insulation	18
Halogen content (percent, max.)	
Jacket	0.2
Fillers	0.2
Insulation	0.2
Immersion (jacket)	
Tensile strength (percent of unaged, min.)	50
Elongation (percent of unaged, min.)	50
Smoke index (max.)	
Jacket	25
Fillers	45
Insulation	45
Toxicity index (max.)	
Jacket	5
Fillers	5
Insulation	1.5
Durometer (jacket) - Type A (hardness, min.)	80
Weathering (jacket)	No failure
Electrical moisture absorption	No failure

UNIT ORDERING LENGTHS:

Type and size	Feet (nominal)
All types and sizes	2000

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:53Z
Check the source to verify that this is the current version before use.

Custodians:
Army – MI
Navy – SH

Preparing Activity:
Navy – SH
(Project 6145-2008-009)

Review Activities:
Army – AR, AV, CR
Navy – CG, EC
DLA – CC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:53Z
Check the source to verify that this is the current version before use.