MILITARY SPECIFICATION

BATTERY, NICKEL - CADMIUM, VENTED: 10541198

This amendment forms a part of Military Specification MIL-B-60298A(MU), dated 18 June 1970.

Page 3, paragraph 3.4.4.1: Delete and substitute the following:

3.4.4.1 Operation.- The Battery shall meet the requirements of 3.5.2.1 when elevated from ground level to the conditions encountered at an altitude of 10,000 feet above sea level within a period of 10 minutes and maintained at these conditions while meeting these requirements.

* Page 3, paragraph 3.5: Delete and substitute the following:

3.5 Performance.- The requirements of 3.5.2.1 and 3.5.2.2 shall be met when each section of the battery has attained the minimum voltage level specified below when charged at the temperature specified at a constant current of 500 ± 25 MA.

10.5V at 70°F
10.2V at 130°F
13.0V at -25°F

* Page 3, paragraph 3.5.1: Delete paragraph contents in its entirety and substitute "not applicable".

* Page 3, paragraph 3.5.2: Delete paragraph contents in its entirety and substitute "not applicable".

Page 3, paragraph 3.5.2.1 a, b, c and Page 4, paragraph 3.5.2.2 a, b, c: Add the word "minimum" in front of the phrase "constant current."

* Page 4, sub-paragraph 3.5.4a, line 3: Delete "full capacity" and substitute "the voltage specified in 3.5."

* Page 4, sub-paragraph 3.5.4b: Delete and substitute - "b. Five cycles in which the battery shall be discharged to the specified minimum voltage (7V per section) at 155°F and charged to the voltage specified in 3.5 while stabilized at 130°F".

* Page 4, sub-paragraph 3.5.4c, line 3: Delete "full capacity" and substitute "the voltage specified in 3.5".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:26Z
Check the source to verify that this is the current version before use.

* Page 4, paragraph 3.5.4, last sentence, line 2: Delete "3.5.2" and substitute "3.5.2.1 and 3.5.2.2". Also in line 3: Delete "3.5.1" and substitute "3.5".

Page 5, paragraph 3.5.5: Delete and substitute the following:

Temperature Sensing Resistor.- The resistance between Pins G and H shall be as specified below at the temperatures indicated:

Resistance	Temperature
870 ohms ± 10%	+77°F
718 ohms ± 10%	+130°F
1615 ohms ± 10%	-25°F

* Page 5, paragraph 3.7, line 4: Delete "1000 Megohms" and substitute "1 Megohm". Add to end of line 5 "when the battery is in a new condition and has not been charged."

* Page 6, paragraph 4.3.2.1, table I: Delete characteristics 101 and 102 and substitute:

"101.	Performance (70°F)	3.5	4.6.6
102.	Room temperature discharge (70°F)	3.5.2.1	4.6.7."

* Page 7, paragraph 4.4.2, table III: Delete characteristics 309 to 312 inclusive and substitute:

"309.	Performance (+130°F)	3.5	4.6.6
310.	Performance (-25°F)	3.5	4.6.6
311.	High temperature discharge (+155°F)	3.5.2.1	4.6.7
312.	Low temperature discharge (-25°F)	3.5.2.2	4.6.7."

* Page 8, paragraph 4.5.3, delete Item No. 1 and substitute:

"1.	Voltmeter, Digital D.C.	Minimum input resistance of 1 megohm, capable of measuring to 15 volts with accuracy of .1% of reading and .1% of range."

* Page 9, paragraph 4.6.1: Add to last sentence, "with exception of 4.6.13."

Page 9, paragraph 4.6.2 Shock: Delete the second sentence and substitute the following:

"The test shall be performed as specified in Procedure I of MIL-F-13962 except the shock pulse shall comply with the wave form, time duration and peak "G" value specified in 3.4.2."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:26Z
Check the source to verify that this is the current version before use.

* Page 9, paragraph 4.6.3 Vibration: Delete the fourth sentence and substitute the following - "The vibration test shall be performed in accordance with figure 514-1 curve C of MIL-STD-810 except double amplitude shall not exceed .036 inch.".

* Page 9, paragraph 4.6.4, line 2: After the words "Procedure I" add the words "Condition R".

Page 9, paragraph 4.6.5 Altitude, Non-operating: Delete and substitute the following:

Conduct this test after the battery has been discharged at 70°F as in 4.6.7. Perform this test in accordance with Procedure II of the altitude test in MIL-F-13926, with conditions specified in 3.4.4.2. The battery shall conform to the requirements of 3.4.4.2 when rotated to any position.

* Page 9, paragraph 4.6.6: Delete and substitute the following:

"4.6.6 Performance charge.- Discharge the 3 sections of the battery at the rates specified in 3.5.2.1 and 3.5.2.2 to lower the terminal voltage of each section to 7.0 ± 0.1V. Allow the battery pack to temperature stabilize for 2 hours. Charge each section at the rate specified in 3.5 until the terminal voltage of each section, measured with the voltmeter (item 1 of 4.5.3), attains the level specified in 3.5. At -25°F a minimum time of 10 minutes must be allowed before monitoring the terminal voltage.".

* Page 10, paragraph 4.6.7: Delete title "Full Capacity Discharge" and substitute "Discharge". In line 2 delete "3.5.2" and substitute "3.5".

* Page 10, paragraph 4.6.8: Delete and substitute the following:

"4.6.8 Retention of charge.- charge the battery at 70°F as follows: charge each section at a constant current rate of 500 ± 25 MA until the terminal voltages reach a level of 10.85 VDC. Charge sections 10541201 and 10558189 for an additional 36 minutes, and charge section 10541200 for an additional 48 minutes. Discharge each section at the current rates specified in 3.5.2.1 until the terminal voltages equal 7 VDC. Record the discharge time for each section. Repeat the above charging procedure. Store the battery at the temperature specified in 3.5.3 for the 30 day period. Discharge the battery at the rate specified in 3.5.1 until the terminal voltage of each section measures 7V. Record the discharge time. The discharge time after storage shall be at least 60% of the discharge time before storage."

* Page 10, paragraph 4.6.9: Delete and substitute the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:26Z
Check the source to verify that this is the current version before use.

"4.6.9 Operational Cycle.- Charge and discharge each battery section as specified in 4.6.8. Record the discharge time. Charge and discharge the battery at the rates specified in 3.5, 3.5.2.1 and 3.5.2.2 as specified in 3.5.4. Charge and discharge each battery section as specified in 4.6.8 and record the discharge time. The discharge time shall be at least 75% of the discharge time before cycling."

* The margin of this specification is marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notation and relationship to the last previous issue.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1240-A497

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:26Z
Check the source to verify that this is the current version before use.