MILITARY SPECIFICATION

CABLE, ELECTRICAL (FLEXIBLE, FLAT, UNSHIELDED),
(FLAT CONDUCTOR)
GENERAL SPECIFICATION FOR

This amendment forms a part of Military Specification MIL-C-49059A, dated 12 April 1979, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 13

4.6.4 and 4.6.4.1: Delete in their entirety and substitute:

"4.6.4 Flammability (see 3.7).

"4.6.4.1 Apparatus. The test shall be performed within draft free enclosure open at top and front to provide adequate ventilation for combustion but to prevent drafts. The specimen holder shall be designed so that the lower end of a 24-inch cable specimen is held by a clamp. A clamp is then attached to the upper end of the cable specimen and a wire attached to this clamp passes over a pulley and can be suitably weighted to hold the specimen taut at an angle of 60 degrees with the horizontal, in a plane parallel to and approximately 6 inches from the back of the chamber. The separation between clamp and pully shall be such that a minimum of 20 inches of the specimen is freely suspended. The test flame shall originate from a Bunsen type gas burner with a 1/4-inch inlet, a needle valve in the base for gas adjustment, 3/8-inch bore nominal, and an approximate 4-inch barrel length above the air inlets. The burner shall be adjusted to furnish a 3-inch conical flame with an approximate 1-inch long inner core and a flame temperature not less than 954°C (1749°F) at tip of inner blue flame as measured with an accurate temperature measuring device 1 percent full scale. A sheet of facial tissue conforming to UU-T-450 shall be suspended taut and horizontal 9-1/2 inches below the point of application of the flame to the cable specimen and at least 1/2 inch from the chamber floor, so that any material dripping from the cable specimen shall fall upon the tissue."

PAGE 15

4.6.4.2, line 3: Delete "with the flat of the cable in a horizontal position".

PAGE 20

4.6.11, add the following:

"4.6.11 Vacuum stability (see 3.13). One specimen qualifies all cables using the same material, independent of conductor size."

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:46Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - AS
Air Force - 85

Review activities:
Army - AR, AV, MI
Navy - EC, OS
Air Force - 17, 99
DLA - IS, ES
NSA
NAS
NASA - MSFC

User activities:
Army - AT, ME
Navy - SH
Air Force - 99

Preparing activity:
Army - CR

Agent:
DLA - ES

(Project 6145-0805-1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:46Z
Check the source to verify that this is the current version before use.