MILITARY SPECIFICATION

CHARGE, PROPELLING, 155MM, M203A1
LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-C-70462C (AR) dated 4 April 1986, and is approved for use within the US Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of Department of Defense.

PAGE 3

3.5 Delete in its entirety and substitute new paragraph 3.5:

"3.5 Moisture content of black powder. The moisture content of the black powder at the igniter loading station at the time of loading shall not exceed 0.7%. The moisture content of the black powder in the basepad of the propelling charge shall be determined in accordance with 4.5.5."

PAGE 23

4.5.6 Delete in its entirety and substitute new paragraph 4.5.6:

"4.5.6 Moisture content of CBI. The moisture content of CBI shall be determined in accordance with the procedure outlined below for informational purposes:

Exactly 10 gms of CBI shall be weighed in an aluminum disposable pan liner, properly positioned, on the Ohaus Moisture Determination Balance. The infrared heat lamp that is built into the machine shall be moved directly over the sample; heat adjusted to the desired temperature; and time and wattage controls regulated to a setting based on a predetermined drying curve. The moisture determination shall then be read directly in either grams or percent moisture loss with the accuracy of the final percent moisture or percent moisture loss with the accuracy of the initial 10 gm sample. The pan and dried CBI shall be weighed until constant weight is obtained, or until the weight between weighings does not exceed one milligram."

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1320-A913)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.