INCH–POUND

MIL-C-70628 (AR)
w/AMENDMENT 2
28 May 2012

SUPERSEDING
MIL-C-70628 (AR)
w/AMENDMENT 1
23 FEBRUARY 1990

MILITARY SPECIFICATION

CONTAINER, AMMUNITION, PA108 ASSEMBLY

This Specification is approved for use by the US Army Armament, Munitions and Chemical Compound, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a Container, Ammunition, PA108 Assembly intended for shipping and storing (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

Comments, suggestions, or questions on this document should be addressed to: Commander, U.S. Army ARDEC, ATTN: RDAR-QES-E, Picatinny Arsenal, New Jersey 07806-5000 or e-mailed to ardecstdzn@conus.army.mil. Since contact information can change, you may want to verify the currency of this information using ASSIST Online database at https://assist.dla.mil.

AMSC N/A FSC 1305

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

TT-C-490	- Cleaning Methods and Pretreatment of Ferrous Surfaces for Organic Coatings

STANDARDS

MILITARY

MIL-STD-1168	- Lot Numbering of Ammunition
MIL-STD-1171	- Acceptance and Description Sheets (For Propellants and Explosives)
MIL-STD-1916	- DOD Preferred Methods for Acceptance of Product
MIL-STD-31000	- Technical Data Packages

(Copies of these documents are available online at https://assist.dla.mil/quicksearch/ or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of solicitation.

DRAWINGS

9396178	-	Container, Ammunition, PA108 Assembly
9396179	-	Body Assembly
9396181	-	Body
12998172	-	Coatings, High Performance (For Ammunition Containers)

(Copies of these drawings may be requested online at pica.drawing.request@conus.army.mil or from U.S. Army ARDEC, ATTN: RDAR-AIS-TD, Picatinny Arsenal, NJ 07806-5000.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents are DOD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless other specified, the issues of documents not listed in the DoDISS shall be issue of the nongovernment documents which is current on the date of the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING MATERIALS (ASTM)

ASTM B117	- Standard Practice for Operating Salt Spray (Fog) Apparatus
ASTM D1654	- Standard Test Method for Evaluation of Painted or Coated Specimens Subjected to Corrosive Environments
ASTM D3951	- Standard Practice for Commercial Packaging

(Copies may be ordered from ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, http://www.astm.org)

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

ASME Y14.100 Engineering Drawing Practices and Related Documentation Practices

(Copies of this document may be ordered from www.asme.org or ASME Information Central Orders/Inquires, P.O. Box 2300 Fairfield, NJ 07007-2300.)

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

ANSI/ISO/ASQC A8402 - Quality Management and Quality Assurance – Vocabulary

(Copies of ANSI standards may be ordered from the American National Standards Institute, 11 W 42nd Street, 13th Floor, New York, NY 10036, or online at http://www.ansi.org/.)

2.4 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specifications sheets of MS standards), the text of this specification shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Required inspections.

3.1.1 First article inspection. When specified in the contract or purchase order, a sample shall be subjected to first article inspection in accordance with the technical provisions herein (see 4.3).

3.2 Material. The contractor shall be responsible for selecting from the classification list contained in the raw material specification, the surface and physical condition of the raw material intended for use in manufacture. The physical and chemical properties specified on the applicable drawing shall be uniformed throughout each part within specified tolerances.

3.3 Assembly. Components and assemblies for container, ammunition, PA108

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

assembly shall be combined to produce an assembly which conforms to the requirements of drawing 9396178.

3.4 Protective coating.

3.4.1 Paint. The paint film thickness and coating shall comply with the requirements of the applicable drawing. In addition, the coating shall be smooth, unbroken and free of blisters, runs, thin spots and foreign matter. Adhesion of the paint to the pretreated surfaces shall comply with the applicable requirements of TT-C-490.

3.4.2 Corrosion resistance. The exterior surface of the container shall show no visible evidence of paint blistering, creepage (loss of adhesion), or corrosion of base metal in excess of 1/8 inch on either side of the score marks, or rusting of parts of the hardware subject to pressure or abrasion in normal use or exceeding the standards permissible in MIL-STD-406, or more than (5) scattered blisters or corrosion spots having individual diameters greater than 3/16” in diameter in any 4 X12 inch flat area, excluding score marks, after exposure to a 5% solution of salt spray for 96 hours.

3.5 Functioning.

3.5.1 Cover assembly. The cover of the container shall open, close and be removed without binding or requiring exertion of undue force. The gasket shall not stick to top edges of the container, be cut or split, not shift within the gasket retainer when cover is opened. Hinge pins shall be secure in body half of hinge.

3.5.2 Hasp and latch. Mating parts of the body hasp and the latch shall meet without requiring deformation of any container part, and the latch shall close and open freely. When closed, the latch of the assembled container shall remain closed until manually opened.

3.5.3 Elevated temperature storage. Following storage of the container in its closed position at an air temperature of 163 degrees Fahrenheit (°F) minimum for a period of 24 hours minimum and subsequent return to ambient temperature, the cover of the container shall function as required in 3.5.1 and 3.5.2.

3.6 Airtightness (of container assembly). The assembled container shall not release more than four (4) bubbles of air when subjected to an air pressure differential of three (3) pounds per square inch (psi) for 15 seconds.

3.7 Weld security.

3.7.1 Cover handle assembly. The cover handle of the container shall withstand a pull of 300 pounds for a period of one minute without separation from the cover or failure of either link, clip, or any weld.

3.7.2 Cover hinge assembly. The cover hinge assembly shall withstand a pull of 500 pounds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

3.7.3 Hasp assembly. The assembly of the hasp to the container shall withstand a pull of 1000 pounds for one minute without failure of the hasp or weld.

3.8 Physical characteristics. The dimensions, tolerance, and finish of the containers will be specified on the applicable drawings and the following.

3.8.1 Metal defects. The containers shall be free of burrs, rough spots, sharp projections, cracks, splits, buckles or sintered surfaces.

3.8.2 Foreign matter. The containers shall be free of corrosion, chips, dirt, grease and other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified herein, or in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. In addition, the Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of section 3 and 5. The inspection set forth in this purchase description shall become a part of contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance if any defective material.

Quality assurance terms and definitions. Quality assurance terms and definitions used herein are in accordance with ANSI/ISO/ASQC A8402.

4.2 Classification of inspection. The following types of inspection shall apply:

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of thirty (30) painted containers and two (2) complete sets of unassembled component parts.

4.3.2 Inspection to be performed. The first article assemblies, components and test specimens may be subject by the Government to any or all of the examinations and tests specified in this specification and to any or all requirements of the applicable drawings.

4.3.3 Rejection. If any assembly, component or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of any assembly, component or test specimen in the sample to comply with any of the stated requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

Table I. First article inspections

CLASSIFICATION OF DEFECTS & TESTS

Paragraph	**Title** Container Assemblies		**Sheet** 1 of 1		**Drawing Number** See Below **Next Higher Assembly**
Category	**Examination of Tests**	**No. of Sample Units**	**AQL or 100%**	**Requirement Paragraph**	**Paragraph Reference / Inspection Method**
	Assembly (Dwg. 9396178)				
	Examination for defects	15	-	3.3	4.4.2.1, 4.4.2.2, 4.4.2.3
	Functioning	15	-	3.5	4.5.3
	Air Tightness of Container Assembly	30	-	3.6	4.5.4
	Gasket Compression (Dwg. 9396178)	10	-	3.3	4.5.6
	Weld Security (1/)				4.5.5.1
	Cover handle assembly	5	-	3.7.1	
	Cover hinge assembly	5	-	3.7.3	4.5.5.2
	Hasp assembly	5	-	3.7.4	4.5.5.3
	Paint film thickness and adhesion	3	-	3.4.1	4.5.1, 4.5.1.2
	Corrosion resistance	3	-	3.4.2	4.5.2

Notes:
1/ The weld security inspections shall be performed after the other inspections have been performed on the samples.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Lot formation shall be in accordance with Section 4 of MIL-STD-1916.

4.4.2 Examination. Unless otherwise specified in the Classification of Defects and Tests. Tables, sampling plans, and procedures shall be in accordance with MIL-STD-1916, Verification Level III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

Quality Conformance Inspection

CLASSIFICATON OF DEFECTS & TESTS

Paragraph 4.4.2.1	**Title** Body		**Sheet** 1of 1		**Drawing Number** 9396181 **Next Higher Assembly** 9396178
Category	**Examination or Test**	**No. of Samples Units**	**AQL or 100%**	**Requirement Paragraph**	**Paragraph Reference / Inspection Method**
Critical	None Defined.				
Major					
101.	Inside length, minimum (min.)			3.3	Gage
102.	Inside width, min.			3.3	Gage
103.	Inside height, min.			3.3	Gage
104.	Flatness, incorrect			3.3	Gage
Minor	None defined				
NOTES:					

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

Quality Conformance Inspection

CLASSIFICATON OF DEFECTS & TESTS

Paragraph 4.4.2.2	**Title** Cover Assembly		**Sheet** 1of 1		**Drawing Number** 9396180 **Next Higher Assembly**
Category	**Examination or Test**	**No. of Samples Units**	**AQL or 100%**	**Category**	**Paragraph Reference / Inspection Method**
Critical	None defined				
Major 101.	Concavity or convexity of cover assembly			3.3	Gage
Minor	None defined				
NOTES:					

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

Quality Conformance Inspection

CLASSIFIACTON OF DEFECTS & TESTS

Paragraph 4.4.2.3	**Title** Container, Ammunition, PA108 Assembly		**Sheet** 1 of 1		**Drawing Number** 9396178 **Next Higher Assembly**
Category	**Examination of Tests**	**No. of Sample Units**	**AQL or 100%**	**Requirement Paragraph**	**Paragraph Reference / Inspection Method**
Critical					
Major					
101.	Incomplete manufacture			3.3	Visual (see note)
102.	Incorrect assembly			3.3	Visual
103.	Incomplete or inadequate paint coverage			3.3	Visual
104.	Burrs, rough spots, sharp projections, cracks, splits, buckles			3.9.1	Visual
Minor					
201.	Outside length, maximum (max.)			3.3	Gage
202.	Outside width, max.			3.3	Gage
203.	Outside height, max.			3.3	Gage
204.	Chips, dirt, grease and other foreign matter			3.9.2	Visual
205.	Surface imperfection, excessive paint not dry			3.3	Visual

Notes:
Refer to MIL-STD-406 for visual defects standards. The standard defects classification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

Conformance Inspection by classification of characteristics

CLASSIFIACTON OF DEFECTS & TEST

Paragraph 4.4.2.4	**Title** Container, Ammunition, PA108 Assembly		**Sheet** 1 of 1		**Drawing Number** 9396178 **Next Higher Assembly**
Category	**Examination of Tests**	**No. of Sample Units**	**AQL or 100%**	**Requirement Paragraph**	**Paragraph Reference / Inspection Method**
	TESTS				
	Paint film thickness and adhesion	3		3.4.1	4.5.1.1, 4.5.1.2
	Corrosion resistance	3		3.4.2	4.4.2
	Airtightness of container assembly		100%	3.6	4.4.4
	Gasket compression		See Note	3.3	4.4.6
	Functioning	13		3.5	4.4.3
	Weld Security	13		3.7	4.4.5
NOTES: Sampling shall be in accordance with MIL-STD-1916, Verification Level II.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.

4.3.3.1 Film thickness and paint adhesion. (See 3.4.1). Three (3) containers shall be randomly selected and tested as specified in 4.5.1. Failure of any containers to conform to the requirement, shall be cause to require the manufacturer to correct his painting practice to comply with the requirement.

4.4.3.2 Corrosion resistance. (See 3.4.2). Three (3) containers shall be randomly selected and tested as specified in 4.5.2. Failure of any containers to conform to the requirement shall be cause to require the manufacturer to correct his painting processes to comply with the requirement.

4.4.3.3 Functioning.

4.4.3.3.1 Cover assembly. (See 3.5.1) Major defect- Thirteen (13) container assemblies shall be randomly selected from each lot and tested as specified in 4.5.3. Failure of one or-more sample units to comply with the specified requirements for functioning of the hasp and latch assembly shall be cause for rejection of the lot.

4.4.3.3.2 Hasp and latch. (See 3.5.2) Major defect- Thirteen (13) container assemblies shall be randomly selected from each lot and tested as specified in 4.5.3. Failure of one or more sample unit to comply with the specified requirements for functioning after the elevated test shall be cause for rejection of the lot.

4.4.3.3.3 Elevated temperature. (See 3.5.3) Major defect- Thirty-two (32) container assemblies shall be randomly selected from each lot and tested as specified in 4.5.3. Failure of one or more sample units to comply with the specified requirements for functioning after the elevated test shall be cause for rejection of the lot.

4.4.3.4 Airtightness of container assembly. (See 3.6). Major defect- This test shall be performed 100% in accordance with 4.5.4. Any container assembly which fails to meet the requirement shall be removed from the lot. These defective container assemblies may be reworked and resubmitted for retesting.

4.4.3.5 Weld security of cover assembly (see 3.7.1), cover hinge assembly (see 3.7.2) and hasp assembly (see 3.7.3) Major defect. Thirteen (13) container assemblies shall be randomly selected from each lot and tested as specified in 4.5.5. Failure of one or more of the sample units to comply with the specified requirements for weld security shall be cause for rejection of the lot.

4.4.3.6 Gasket compression. (see dwg. 9396178). Major defect. The container assemblies shall be sampled in accordance with MIL-STD-1916, Verification Level II. The test shall be performed as specified in 4.5.6.

4.4.4 Inspection equipment. The inspection equipments required to perform the examinations and test prescribed herein is described in the “Paragraph Reference/ Inspection Method” column in the tables starting with 4.4.2.1. The contractor shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

submit for approval inspection equipment designs in accordance with terms of the contract. (see 6.3).

4.5 Methods and inspection.

4.5.1 Paint.

4.5.1.1 Paint Thickness. The method of test shall be as specified in TT-C-490. The test shall be performed on three (3) randomly selected surfaces of each unit of the sample.

4.5.1.2. Paint adhesion. The method of test shall be as specified in TT-C-490. The test shall be performed on three (3) randomly selected surfaces of each unit of the sample.

4.5.2 Corrosion resistance. The method of test shall be as specified in ASTM B117 - Standard Practice for Operating Salt Spray (FOG) Apparatus. Using a sharp instrument (machinist scribe or equivalent), the painted specimens shall be scribed in a vertical direction approximately 3 inches long on the flat portion of each side, the bottom, the hinge end, and the cover. The sample shall be positioned so that the hinged edge of the assembled box is elevated approximately 15 degrees from the horizontal and rests upon a wooden support while the cover face is parallel to the principal direction of horizontal flow of fog through the chamber. Traces of paint blistering or corrosion spots on component edges or sharp corners shall not be classed as protective coating failure. After salt spray testing, the scribe shall be evaluated according to ASTM D1654, Procedure A, Methods 1 or 2.

4.5.3 Functioning. The container shall be inspected to assure compliance with requirements of 3.5 through the following procedures:

a. Unlock and lock the cover assembly by hand leverage. Note the locking and unlocking action on the container assembly for effectiveness and ease of operation.

b. Remove and replace the cover assembly. Note any sticking of gaskets to the top edge of the body assemblies, or any misfit or bind within the body assembly and inspect hinge pins for security in the body half of the hinge.

c. Remove all cover assemblies. Inspect the gaskets for fit security, cuts, and splits.

d. Environmentally condition the box assemblies as specified in 3.6.3. After conditioning, re-inspect the containers assemblies in accordance with a, b, and c above.

4.5.4 Airtightness of container assembly. The container shall be conditioned to a temperature of 70°F ± 2°F and ambient pressure prior to testing. The containers shall be tested in accordance with 4.5.4.1 or with Government approval 4.5.4.2 (see 6.6). A wetting agent may be used to minimize air bubbles clinging to the exterior surface.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

4.5.4.1 Vacuum method. The assembled container shall be tested for leakage by immersing the closed container, in a vacuum vessel, to a depth of at least one inch below the surface of the water. The air pressure in the vessel shall be lowered such that it is between 3 and 4 psi below ambient pressure and maintained at this point for the duration of the test. Observation for air leakage of air from the interior of the container assembly shall be made during the period of lowering pressure for a minimum of 15 seconds after the 3 psi pressure deferential has been reached.

4.5.4.2 Hot water method. The assembled container shall be tested for leakage by immersing the closed container to a depth of one inch below the surface of the water. The temperature of the water and the length of time of immersion shall be that which will assure an increase in pressure to a minimum of 3 psi above ambient pressure (see 6.6). Observation for air leakage from the interior of the container assembly shall be made during the period of pressure build up and for a minimum of 15 seconds after the 3 psi pressure deferential has been reached.

4.5.5 Weld security.

4.5.5.1 Cover handle assembly. The assembled container shall be clamped with the sample body assembly resting on its, bottom. Attach the test fixture to the cover handle. With one fixture security held, apply the specified tensional force through the other test fixture, vertical to the container bottom against the ferrule of each handle. The force shall be applied at a rate of .125 to .25 inch per minute and held for one minute. After removal of the force, examine the handle and hasp for distortion and weld failure.

4.5.5.2 Cover hinge assembly. The assembly shall be tested in a suitable fixture with the container resting on its bottom with the cover raised at a right angle. The container shall be clamped securely and the body assembly shall be supported by means of a snug fitting wood filler box in order to prevent its distortion or collapse. Secure the other test fixture to the cover assembly. The force shall be applied at a rate of .125 to .25 inch per minute and held for one minute. After removal of the force, examine the cover, cover hinge and the body hinge for distortion and weld failure.

4.5.5.3 Hasp assembly. The sample body assembly resting on their bottoms shall be clamped in a suitable device. Using a test fixture clamped securely on the hasp assembly, the specified force shall be slowly applied perpendicular to the bottom and against the underside of the offset of the hasp. The force shall be applied at a rate of .125 to .25 inch per minute and held for one (1) minute. After removal of the force, examine the hasp for distortion and weld failure.

4.5.6 Gasket compression.

4.5.6.1 Compressed gasket and cover measurements. The container shall be positioned in a suitable fixture so that it cannot be moved (see 6.5). Four points, two on each side, two inches from the front and the rear, shall be located (and numbered 1, 2, 3 and 4) on both the body and the cover. With the body fully closed, a reading at each point, with a standard height gage, shall be recorded, then the cover shall be removed and

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

the height to the hemmed edge of the body at the same point shall be recorded. Subtraction of the second reading from the first reading gives the value of the compressed gasket and cover.

4.5.6.2 Uncompressed gasket and cover measurements. The cover and uncompressed gasket shall be measured at each of the four locations with a precision measurement device and readings recorded. Care must be exercised so that the surface of the measuring device does not rest in the groove of the compression set. These readings are the uncompressed gasket and cover values.

4.5.6.3 Average gasket compression value. The compressed gasket and cover results (4.5.6.1) shall be subtracted from the uncompressed gasket and cover readings (see 4.5.6.2) at corresponding location points. The sum of the resulting values for the four location points divided by four shall be considered the average gasket compression value. The average value for each container shall be used in the application of the procedures of MIL-STD-414.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with ASTM-D3951.

6. NOTES

6.1 Intended use. The container, ammunition, PA108 assembly is intended for use in the shipment and storage of small arms ammunition.

6.2 Ordering data. Procurement documents shall specify the following:

6.2.1 Procurement requirements.

a. Title, number and date of this specification
b. Quantity required and delivery schedules
c. Serialization requirements, if applicable.
d. Quality conformance inspection, if other than specified in Section 4 of this specification.
e. First article sample requirements, if other than specified in Section 4 of the specification.
f. Packaging requirements, if other than specified in section 5 of this specification.

6.2.2 Contract data requirements.

a. Contract data requirements for inspection equipment designs (conforming to Data Item Description DI-E-1118 or DI-R-1714 with appropriate addendum to each). See 6.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

b. Data Cards - When required by incorporation of DD Form 1423 in to the contract, data cards shall be prepared for each lot in accordance with Data Item Description DI-L-1410, except that for propellant or explosive lots, Acceptance and Description Sheets will be prepared in accordance with MIL-STD-1171.

6.3 Inspection equipment designs. Inspection equipment designs are of two types: Government Special Inspection Equipment (SIE) designs and contractor designs. SIE designs are designated by drawing numbers under the "Methods of Inspection" heading in Section 4, or on the Equipment Lists referenced on the Equipment Tabulation, whichever is specified in the item detail specification. Design responsibility for all other inspection equipment is assigned to the contractor. However, the contractor need not furnish any design when a complete Government SIE design is part of the Technical Data Package (TDP). Unless otherwise specified, the contractor may submit alternate or modified contractor designs of SIE in accordance with 6.3.2 and 6.3.3 should he elect to do so.

6.3.1 SIE designs. SIE designs may consist of any of the following.

a. Detailed drawings which completely depict all information necessary for the fabrication and use of the item of inspection equipment

b. A source control drawing or a specification control drawing as defined in ASME Y14.100.

c. An envelope drawing, as defined in ASME Y14.100, which establishes the criteria which a detailed design shall meet. When envelope drawings are specified, the contractor shall prepare designs which comply with the criteria therein.

6.3.2 Contractor designs. Contractor designs are required for all inspection equipment for which SIE designs are not specified and may include commercial equipment which the contractor proposes to use. (Commercial equipment is defined as unmodified equipment which is cataloged and available for purchase by the general public). Contractor designs shall include appropriate operating instructions, calibration procedures and maintain procedures. Commercial equipment shall be fully described by catalog listings or other means which provide sufficient information to permit identification and evaluation by the Government and may include illustrations and engineering data. Designs shall be prepared for any special fixture(s) required to be used with commercial equipment, or with SIE designs if on otherwise covered thereby (see 6.3.1c). Designs shall be of the category and form (per MIL-DTL-31000) specified in the Contract Data Requirements Lists (DD Form 1423). The item detail specification number, paragraph number, and defect number from Section 4 shall be referenced on each contractor design together which the component or assembly drawing number, revision letter and date to which the specified design applies.

6.3.3 Submission of designs of approval. Contractor designs shall be approved by the Government prior to fabricating or procuring the equipment. Designs shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

submitted for approval in accordance with the stipulations, time frame and distribution specified in the Contract Data Requirements lists (DD Form 1423) or in the contract. Partial submission of inspection of equipment designs is permissible and encouraged. However, the completion date for design review will be based on the date of the final submission of designs and the required deliver schedule as stipulated in the contract.

The specific segment of AMCCOM to which the Contractor designs shall be sent will be specified in the item detailed specification. When the contractor submits inspection equipment designs to the Government for approval, he shall give the following information in his letter transmittal:

a. The contract number
b. The contractor item (name, model, number etc.)
c. The designs remaining to be submitted and the expected date of submittal.

Submit equipment designs, as required to: Commander, U.S. Army Armament Research, Development and Engineering Center, ATTN: RDAR-QEW-A, Picatinny Arsenal, New Jersey 07806-5000.

6.4 Drawings. Drawings listed in Sections 2 of this specification under the heading U.S. Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC

6.5 Measurement for gasket compression. Three point contact of the container resting on blocks may be used to overcome any rocking which might be encountered with the container resting on the surface plate. However, since the measurement technique relies upon relative distances, care should be taken to assure that there is no displacement on the referenced surfaces between the readings.

6.6 Hot water method for airtightness. The hot water test procedure for each container should be submitted to Commander, AMCCO, ATTN: RDAR-QEM-D, Picatinny Arsenal, NJ 07806-5000. for approval. The test procedure should include water temperature, immersion time, the data to support time and periodic verification procedure.

6.7 Subject term (key word) listing.

Military Specification
Box , ammunition
Small Arms Ammunition

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

6.8 Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1305-2011-006)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.