INCH-POUND

MIL-F-71127 (AR)
AMENDMENT 1
09 November 1993

MILITARY SPECIFICATION

FUZE, POINT DETONATING, PRACTICE, M775 WITH PYROTECHNIC SIGNATURE CARTRIDGE

This Amendment forms a part of Military Specification MIL-F-71127 (AR), dated 26 May 1992, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

3.10, Change from: "3.10 Ogive weld and mechanical joint test. The ogive shall withstand an axial pulling force of 50 + 5 pounds on the ogive at both the forward and rear section joint and at the rear section joint after it is properly assembled to an M775 fuze body."

To: "3.10 Ogive weld and mechanical joint test. The ogive shall withstand an axial pulling force of 50 + 5 pounds on the ogive when applied to the forward section joint and the rear section joint after it is properly assembled to an M775 Fuze body."

PAGE 6

4.1.3.2, Change from "c. Rivet, dwg. MS9403" to "c. Rivet, dwg. 12929047"

PAGE 7

Under Part Description, delete: "Fuze Body Assembly ...9387100 ...20"

PAGE 13

Table I, delete:
"Fuze Body Assembly
(Dwg. 9387100)
Examination for defects ...10ea ...3.2 ...4.4.2.23
Combined welded and mechanical
joint test ...10ea ...3.2 ...Test/4.5.13.2"

AMSC N/A FSC 1390
DISTRIBUTION STATEMENT A. **Approved for public release; distribution is unlimited.**

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:21Z
Check the source to verify that this is the current version before use.