INCH-POUND

MIL-F-71127 (AR)
AMENDMENT 2
09 November 1994
SUPERSEDING
AMENDMENT 1
09 NOVEMBER 1993

MILITARY SPECIFICATION

FUZE, POINT DETONATING, PRACTICE, M775
WITH PYROTECHNIC SIGNATURE CARTRIDGE

This Amendment forms a part of MIL-F-71127 (AR), dated 26 May 1992, and is approved for use by the U.S. Army Armaments, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

3.10, Delete:

"3.10 Ogive weld and mechanical joint test. The ogive shall withstand an axial pulling force of 50 + 5 pounds on the ogive at both the forward and rear section joint and at the rear section joint after it is properly assembled to an M775 fuze body."

and substitute:

"3.10 Ogive weld and mechanical joint test. The ogive shall withstand an axial pulling force of 50 + 5 pounds on the ogive when applied to the forward joint and the rear section joint after it is properly assembled to an M775 fuze body."

PAGE 6

4.1.3.2, Delete: "c. Rivet, dwg MS9403".

and substitute: "c. Rivet, dwg 12929047".

AMSC N/A FSC 1390
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:21Z
Check the source to verify that this is the current version before use.

PAGE 7

* 4.3.1, under Part Description:

Delete: "Packing preformed AMS 3303 O-Ring ...2929048 ...10".

Delete: "Fuze Body Assembly ...9387100 ...20".

PAGE 8

* Under Body, fuze:

Delete: "9343991", and substitute: "12944162".

PAGE 12

* Section pertaining to the Packing Preformed AMSD 3303 O-Ring.

Delete in its entirety.

PAGE 13

* Table I, Under Loading Assy, Fuze M775, delete:

"Fuze chamber operation test",

and substitute:

"Fuze sleeve and chamber operation test".

Under Conformance Criteria, delete:

"25", and substitute: "50".

Source: https://assist.dla.mil Downloaded: 2026-10-23T04:21Z
Check the source to verify that this is the current version before use.

PAGE 13 (cont)

* Delete in its entirety:

"Fuze body assembly (Dwg. 9387100)

Examination for defects ...10 ea ...3.2 ...4.4.2.23

Combined welded and mechanical joint test ...10 ea ...3.2 ...Test/4.5.13.2".

* Under Fuze, PD, Practice, M775, delete:

"Fuze sleeve and chamber operation test ...50 ea ...3.9 ... Test/4.5.16".

Under last line, add:

"Combined welded and mechanical joint test ...10 ea ...3.2 ... Test/4.5.13.2".

PAGE 21

* 4.4.2.2, Minor 203 and Minor 204: Delete in their entirety.

PAGE 37

4.4.2.18: Add the following:

"Major 111 Distance between forward face and forward face of rear flange ...III ...3.2 ...Gage".

PAGE 38

4.4.2.18, Minor 203: Delete in its entirety.

PAGE 41

* 4.4.2.21: Delete in its entirety.

PAGE 43

* 4.4.2.22, Major 102: Delete in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:21Z
Check the source to verify that this is the current version before use.

PAGE 51

4.5.11, line 5: Change the word "clot" to "clip".

4.5.12, line 3: Change the word "clot" to "clip".

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-0812)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:21Z
Check the source to verify that this is the current version before use.