INCH-POUND

MIL-F-71127 (AR)
AMENDMENT 7
31 August 2000
SUPERSEDING
AMENDMENT 6
13 January 1999

MILITARY SPECIFICATION

FUZE, POINT DETONATING, PRACTICE, M775 WITH PYROTECHNIC SIGNATURE CARTRIDGE

This amendment forms a part of MIL-F-71127 (AR), dated 26 May 1992, and is approved for use by the U.S. Army Armament Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

3.10, Delete:

"3.10 Ogive weld and mechanical joint test. The ogive shall withstand an axial pulling force of 50 + 5 pounds on the ogive at both the forward and rear section joint and at the rear section joint after it is properly assembled to an M775 fuze body."

and substitute:

"3.10 Ogive weld and mechanical joint test. The ogive shall withstand an axial pulling force of 50 + 5 pounds on the ogive when applied to the forward joint and the rear section joint after it is properly assembled to an M775 fuze body."

PAGE 6

4.1.3.2, Delete: "c. Rivet, dwg MS9403".

and substitute: "c. Rivet, dwg 12929047".

AMSC N/A FSC 1390
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:21Z
Check the source to verify that this is the current version before use.

PAGE 7

4.3.1, under Part Description:

Delete: "Packing preformed AMS 3303 O-Ring ... 2929048 ... 10".

Delete: "Fuze Body Assembly ... 9387100 ... 20".

Delete: "Body, Fuze ... 12944162 ... 10".

and substitute: "Body, Fuze ... 9343991 ... 10".

Delete: "Metal Parts Assembly Fuze M775 ... 12944172 ... 20"

and substitute: "Metal Parts Assembly Fuze M779/M775 ... 12953583 ... 20".

Add the following:

Under Part Description: "Ball, Setback"

Under Drawing: "12988976"

Under Quantity (EA): "10"

*

Under	Part Description	Drawing	Quantity(ea)
Delete:	"Chamber"	"12944178"	"10"
Substitute:	"Thin Bottom Chamber	"12957043"	"10"

PAGE 8

Table I, under Examination or test: Delete: "Body, Fuze ... (Dwg. 12944172)"

And substitute: "Body, Fuze ... (Dwg. 9343991)".

PAGE 11

* TABLE I: Under Examination or Test, Delete: "<u>Chamber, Fuze</u>
(Dwg. 12944178)"

And substitute: "<u>Thin Bottom Chamber</u>
(Dwg.12957043)"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:21Z
Check the source to verify that this is the current version before use.

PAGE 12

Section pertaining to the Packing Preformed AMSD 3303 O-Ring: Delete in its entirety.

Table I, under Examination or test: Delete: "Metal Parts Assembly Fuze M775 ... 12944172"

and substitute: "Metal Parts Assembly Fuze M779/M775 ... 12953583".

PAGE 13

Table I, Under Loading Assy, Fuze M775, delete:

"Fuze chamber operation test",

and substitute:

"Fuze sleeve and chamber operation test".

Under Conformance Criteria, delete: "25", substitute: "50"

Delete in its entirety:

Fuze body assembly (Dwg. 9387100)

Examination for defects ... 10 ea ... 3.2 ... 4.4.2.23

Combined welded and mechanical joint test ... 10 ea ... 3.2 ... Test/4.5.13.2".

Under Fuze, PD, Practice, M775, delete:

"Fuze sleeve and chamber operation test ... 50 ea ... 3.9 ... Test/4.5.16".

Under last line, add:

"Combined welded and mechanical joint test ... 10 ea ... 3.2 ... Test/4.5.13.2".

Table I: Add the following:

Under Examination or Test: "Ball, Setback
(Dwg. 12988976)
Examination for defects"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:21Z
Check the source to verify that this is the current version before use.

(PAGE 13 Continued)

Under Conformance Criteria: "10 ea"

Under Requirement Paragraph: "3.2"

Under Inspection Method Reference: "4.4.2.26"

PAGE 14

Add the following:

"TABLE I. First article inspection
CLASSIFICATION OF CHARACTERISTICS MIL-F-71127 (AR)

PARAGRAPH	TITLE Fuze, Point Detonating, Practice M775	SHEET 7 OF 7		DRAWING NUMBER See below / NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Spring Ball			
	(Dwg. 9344006)			
	Examination for defects	10 units	3.2	4.4.2.11
	Spring embrittlement test	10(a) units	3.8	4.5.3
	Pin, Packing Clip			
	(Dwg. 9344001)			
	Examination for defects	10 units	3.2	4.4.2.12
	Clip, Packing			
	(Dwg. 9344004)			
	Examination for defects	10 units	3.2	4.4.2.13
	Packing Clip Assembly			
	(Dwg. 9344005)			
	Examination for defects	10 units	3.2	4.4.2.14
	Packing clip pull test	10(a) units	3.2	4.5.9

NOTES:
(a) Only 10 units are required if non destructive examination is followed by destructive tests.

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:21Z
Check the source to verify that this is the current version before use.

PAGE 18

4.4.2.1, Sheet 1 of 3, Drawing Number: Delete existing drawing number and substitute "9343991".

Under Next Higher Assembly: Delete existing drawing number and substitute "12953583".

Major 111: Delete "True position of minor striker hole to rear cavity" and substitute: "Location of minor striker hole".

PAGE 19

4.4.2.1, Sheet 2 of 3, Drawing Number: Delete existing drawing number and substitute "9343991".

Under Next Higher Assembly: Delete existing drawing number and substitute "12953583".

Delete Major 120 in its entirety.

PAGE 20

4.4.2.1, Sheet 3 of 3, Drawing Number: Delete existing drawing number and substitute "9343991".

Under Next Higher Assembly: Delete existing drawing number and substitute "12953583".

* Delete Minor 206 in its entirety.

PAGE 21

4.4.2.2, Minor 203 and Minor 204: Delete in their entirety.

PAGE 27

4.4.2.8, Sheet 1 of 1, Under Next Higher Assembly: Delete existing drawing number and substitute "12953583".

PAGE 28

4.4.2.9, Sheet 1 of 1, Under Next Higher Assembly: Delete existing drawing number and substitute "12953583".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:21Z
Check the source to verify that this is the current version before use.

PAGE 29

4.4.2.10, Sheet 1 of 1, Under Next Higher Assembly: Delete existing drawing number and substitute "12953583".

PAGE 30

4.4.2.11, Sheet 1 of 1, Under Next Higher Assembly: Delete existing drawing number and substitute "12953583".

PAGE 33

4.4.2.14, Sheet 1 of 1, Under Next Higher Assembly: Delete existing drawing number and substitute "12953583".

PAGE 34

* 4.4.2.15, Delete the title and substitute: "Thin Bottom Chamber"

Delete the drawing number and substitute: "12957043"

Delete the classification "Special A"
And substitute "Major 107"

PAGE 35

4.4.2.16, Sheet 1 of 1, Under Next Higher Assembly: Delete existing drawing number and substitute "12953583".

PAGE 36

4.4.2.17, Sheet 1 of 1, Under Next Higher Assembly: Delete existing drawing number and substitute "12953583".

PAGE 37

4.4.2.18: Add the following:

"Major 111 Distance between forward face and forward face of rear flange ... III ... 3.2 ... Gage".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:21Z
Check the source to verify that this is the current version before use.

PAGE 38

4.4.2.18, Minor 203: Delete in its entirety.

PAGE 39

4.4.2.19, Sheet 1 of 1, Under Next Higher Assembly: Delete existing drawing number and substitute "12953583".

PAGE 40

4.4.2.20, Sheet 1 of 1, Under Next Higher Assembly: Delete existing drawing number and substitute "12953583".

PAGE 41

4.4.2.21: Delete in its entirety.

PAGE 42

4.4.2.22, Sheet 1 of 2, Under Title: Delete current entry and substitute: "Metal Parts Assembly Fuze M779/M775".

Under Drawing Number: Delete existing drawing number and substitute "12953583".

PAGE 43

4.4.2.22, Major 102: Delete in its entirety.

4.4.2.22, Sheet 2 of 2, Under Title: Delete current entry and substitute: "Metal Parts Assembly".

Under Drawing Number: Delete existing drawing number and substitute "12953583".

Add Minor 203 as follows:

"203... Setback hole seal missing or not adhering... V...
3.2... Visual"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:21Z
Check the source to verify that this is the current version before use.

PAGE 46

Add paragraph 4.4.2.26 as follows:

PARAGRAPH 4.4.2.26	TITLE Ball, Setback	SHEET 1 OF 1		DRAWING NUMBER 12988976 NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Diameter of ball (Two places. See Note 1.)	III	3.2	Gage
102	Hardness of Ball	III	3.2	Gage
Minor				
201	Poor workmanship	V	3.16	Visual

NOTES:
1. The second diameter of ball measurement shall be taken 90° (normal) to the axis of the first diameter of ball measurement.
2. Contractor shall certify that surface finish and density of the setback ball conform to Dwg. 12988976."

PAGE 48

4.5.5, Line 2, after the word "fuzes" add the following: "(For lot acceptance testing, primed hulls with inert filler may be substituted for the full-up spotting cartridge. Primed hulls shall not be dropped more than one time before being discarded.)".

PAGE 50

4.5.9, Line 3, delete: “of 10 +/- 2 pounds” and substitute: “in accordance with drawing 9344005”.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:21Z
Check the source to verify that this is the current version before use.

PAGE 51

4.5.11, line 5: Change the word "clot" to "clip".

4.5.12, line 3: Change the word "clot" to "clip".

The margins of this amendment are marked with an asterisk, or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-0877)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:21Z
Check the source to verify that this is the current version before use.