MILITARY SPECIFICATION

FUZE, IMPACT, ATOMIC WEAPON: M1139

This amendment forms a part of Military Specification MIL-F-48306 (AR) dated 19 February 1976.

PAGE 2

Paragraph 3.7 Output Voltage; Change title and requirements to read: Output Voltage During Low Level Vibration - The minimum output voltage (peak to peak) of the impact fuze shall be 15 millivolts. The sinewave applied to the fuze shall be 20 gravities (g) zero to peak at a frequency of 330± 30 hertz. This test shall be conducted as specified in para. 4.4.3.

PAGE 4

Paragraph 3.8.6 Impact Shock; Delete requirement and replace with: 3.8.6.1 Low Impact Shock - The fuze shall be subjected to a shock of 50 gravity units (g's) ± 5g, three times in each direction, along its longitudinal and transverse axis (2 planes) (see Figure 1) for a total of 12 shocks. The duration of each shock shall last for 11 milliseconds (ms) ± 1 ms as measured between points which are 10 percent of the peak level. The time to peak shall be 5.5 ms ± 1 ms. Upon completion of this test, the fuze assembly shall comply with the requirements of 3.5, 3.6 and 3.7, when tested as specified in 4.4.4.6.

Paragraph 3.8.6.2 High Impact Shock; The impact fuze shall be subjected to a shock of 3,000 g's ± 300 g's for a duration of 0.1 milliseconds while loaded by a parallel network of a 0.1 microfarad capacitor and a 1000 ohm resistor. The minimum output voltage shall be 1.0 volts during the initial impulse. Testing shall be as specified in para. 4.4.4.6.

PAGE 5

Paragraph 4.2.2 Table II Test 10 Impact Shock; Change (see 3.8.6) to read (see 3.8.6.2) and transfer "X" from column titled "non-Dest" to "Dest".

FSC 1135

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

PAGE 13

Paragraph 4.3.3 Testing, Test d; Change Impact Shock to read Low Impact Shock.

Paragraph 4.3.3.2 Impact Shock; Change last sentence to read: If any item fails to comply with 3.8.6.1, the lot shall be rejected.

PAGE 15

Paragraph 4.4.3 Output Voltage; Change title and test method to read: Output Voltage During Low Level Vibration - The impact fuze shall be mounted on a government approved test fixture capable of being readily positioned such that it can be vibrated along a vertical axis which is perpendicular to the cover plate. The impact fuze shall be subjected to a sinewave vibration for 2 minutes and the output voltage measured across a 1000 ohm (± 1 percent) load, shunted by a 0.1 microfarad capacitor (± 2 percent). The fuze shall comply with the requirements of 3.7 during this test. Test code shall be 050 001.

CUSTODIAN:
ARMY-AR

PREPARING ACTIVITY:
ARMY-AR

PROJECT NUMBER:1135-A248

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.