MIL-H-60132(MU)
AMENDMENT 3
28 April 1972
SUPERSEDING
AMENDMENT 2
29 November 1968

MILITARY SPECIFICATION

HEAD ASSEMBLY, TANK PERISCOPE: 10513625

This amendment forms a part of Military Specification MIL-H-60132(MU), dated 2 November 1964.

Paragraph 3.4: Delete and substitute:

"3.4 Sealing.- The head assembly shall show no evidence of leakage when subjected to an internal air pressure of 5 psig (constant) and while submerged, inverted from its normal mode, in 5 ± 1 inches of water."

Add the following new paragraphs:

"4.1.2 First Article (Initial Production) Approval.- The requirement for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of three head assemblies plus 3 each of all items covered by SQAP. The sample shall be manufactured in the same manner, using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing shall be obtained from the same source of supply as used in regular production.

4.1.2.1 Government testing.- When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it conforms to all the requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials.

4.1.2.2 Contractor testing.- When the contractor is responsible for conducting first article approval tests, the sample shall be inspected by the contractor for all the requirements of the contract. The sample and a record of this inspection, including certificates of conformance for materials, shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection."

Paragraph 4.2.2, Table 1: Add the following:

"104.	Sealing	3.4	4.5.3"

* Paragraph 4.3.2: Delete "304. Sealing 3.4 4.5.3"

FSC 6650

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:11Z
Check the source to verify that this is the current version before use.

Paragraph 4.5.3: Delete and substitute:

"4.5.3 Sealing.- An adapter that is capable of sealing the lower cavity of the head assembly shall be utilized in this test. The adapter shall be equipped with a valve, or port, that is capable of accepting an air hose for pressurizing the lower cavity of the head assembly. Affix the adapter to the head assembly. Pressurize the lower cavity of the head assembly with clean dry air to the value specified in 3.4. Invert the pressurized head assembly (prism down) and immerse it in water to the required depth for a period of 3 minutes ± 15 seconds. During this time period the head assembly shall be observed for evidence of leakage that will be in the form of air bubbles coming from within the assembly. The head assembly shall conform to the requirements specified in 3.4. The temperature of the water for this test shall be between 60° and 90°F. Upon completion of this test the head assembly shall be thoroughly dried and cleaned."

Paragraph 6.2: Add: "(e) Requirement for first article testing"

*"The margin of this specification is marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and The Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue."

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 6650-A058

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:11Z
Check the source to verify that this is the current version before use.