MILITARY SPECIFICATION
INITIATOR, CARTRIDGE ACTUATED, XM107
METAL PARTS ASSEMBLY

This amendment forms a part of Military Specification MIL-I-60595(MU) dated 25 October 1966.

Paragraph 2.1 Under STANDARD delete the following:

"MIL-STD-639 - Surface Roughness Values Preferred for Army Ordnance Materiel"
"MIL-STD-1167 - Ammunition Data Card"

Following the parenthetical note of paragraph 2.1, add the following:

"2.2 Other publications.- The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

ASA B46.1 - Surface Texture

(Application for copies should be addressed to the American Standards Association, 10 East 40th Street, New York, N.Y. 10016)"

Paragraph 3.2: Delete in its entirety.

Paragraph 4.1: Delete and substitute:

"4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements."

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:47Z
Check the source to verify that this is the current version before use.

Paragraph 4.3.2, lines 8 and 9: delete "The Ordnance Standard Finish Blocks prescribed in MIL-STD-639" and substitute: "The roughness comparison specimens prescribed in ASA B46.1"

Paragraph 4.3.2.3 Delete and substitute:

"4.3.2.3 Pin, Initiator, Drawing C11730531, covering a detail of Drawing F10535977.

CRITICAL

None defined

MAJOR

101.	Concentricity of groove in head with body	Gage
102.	Concentricity of head with body	Gage
103.	Pitch diameter, max.	Gage
104.	Diameter of body	Gage
105.	Diameter of head (front)	Gage
106.	Diameter of head (rear)	Gage
107.	Diameter of groove in body	Gage
108.	Diameter of groove in head	Gage
109.	Diameter of pin hole	Gage
110.	Width of head groove	Gage
111.	Width of slot in head	Gage
112.	Location of pin hole from rear head	Gage
113.	Location of pin hole from front head	Gage
114.	Location of body groove	Gage
115.	Thickness of head (rear)	Gage
116.	Hardness	Gage
117.	Metal defective	Visual
118.	Protective finish inadequate	Visual
119.	Surface finish improper	Visual/Gage
120.	Burr	Visual
121.	Foreign matter	Visual

MINOR

201.	Pitch diameter, min.	Gage
202.	Minor diameter, max.	Gage
203.	Width across head flats	Gage
204.	Total length	Gage
205.	Radius of body groove	Visual
206.	Radii or chamfer missing or incorrect	Visual
207.	Surface finish improper except as otherwise classified	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:47Z
Check the source to verify that this is the current version before use.

Add paragraph 4.3.2.13:

"4.3.2.13 Screw Pin, Drawing C11730532, covering a detail of Drawing F10535977."

Defect		Method of Inspection
CRITICAL		
	None defined	
MAJOR		
101.	Pitch diameter, min.	Gage
102.	Locking element missing or incorrect	Visual/Gage
MINOR		
201.	Pitch diameter, max.	Gage
202.	Major diameter, max.	Gage
203.	Diameter of head	Gage
204.	Length of body	Gage
205.	Thickness of head	Gage
206.	Depth of slot	Gage
207.	Width of slot	Gage
208.	Profile of head	Visual
209.	Radius or chamfer missing or incorrect	Visual
210.	Protective finish inadequate	Visual
211.	Surface finish improper	Visual

Paragraph 5.2: Delete in its entirety.

Custodian:

Army - MU

Preparing Activity:

Army - MU

Project No. 1377-A385

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:47Z
Check the source to verify that this is the current version before use.