MILITARY SPECIFICATION

IGNITER, ELECTRIC MATCH PARTS FOR AND LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-I-70534(AR), dated 27 September 1985, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.2.1: Change "... igniting a standard a 155MM..." to read "... igniting a standard 155MM ...".

3.5.1, Line 1 and Line 2: Change "low" to "cold".

3.5.2, Line 1 and Line 2: Change "high" to "hot".

PAGE 4

3.5.5: Change "4.5.4.5" to "4.5.4.6".

PAGE 7

Table I: Delete Sheet 2 and replace with the following:

"Igniter Assy (Cont'd)

Sequential Test

Leakage test	1 box/128		3.5.4	4.5.4.4
Jumble	32		3.5.5	4.5.4.6
Leak	96		3.5.3	4.5.4.3
Hot, Note 1	32	4.4.5.1	3.5.2	4.5.4.2/4.5.3
Cold, Note 1	32	4.4.5.2	3.5.1	4.5.4.1/4.5.3
Ambient, Note 1	32	4.4.5.1	3.5.2	4.5.4.2/4.5.3"

PAGE 12

4.4.2.4: Change "composition" to "content".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:38Z
Check the source to verify that this is the current version before use.

PAGE 13

4.4.2.5, Under Paragraph Reference/Inspection Method: Add ", 4.5.5" after "ohmmeter".

PAGE 14

4.4.2.6:

Major 105: Change "182" to "150".

Major 106: Change "4.5.4.5" to "4.5.4.6".

Major 107, 108 and 109: Delete in their entirety and substitute with the following:

"Major 107, Hot-Note 1, 50, 4.4.5.1, 3.5.2, 4.5.4.2,4.5.3
Major 108, Cold-Note 1, 50, 4.4.5.2, 3.5.1, 4.5.4.1,4.5.3
Major 109, Ambient-Note 1, 50, 4.4.5.1, 3.5.2, 4.5.4.2,4.5.3"

PAGE 18

4.4.5.1, Line 3: Delete "of 4.4.2.6".

4.4.5.2, Line 3: Delete "of 4.4.2.6".

PAGE 20

4.5.3: Delete in its entirety.

4.5.3.1: Change "4.5.3.1" to "4.5.3".

4.5.4.1: Delete paragraph in its entirety and replace with the following:

"4.5.4.1 Cold temperature (minus 32 ± 3°C, minus 25 ± 5°F). This test shall be conducted in accordance with Method 502.2, Procedure I of MIL-STD-810, except that the simulator shall be conditioned at a temperature of minus 25 ± 5°F until thermal stabilization is reached and maintained for a period of 6 hours (min.). The test specimens shall be removed from the conditioning cabinet, set-up, and fired within 5 minutes. Observations shall be made for compliance with the applicable requirement."

Source: https://assist.dla.mil -- Downloaded: 20261O-23T03:38Z
Check the source to verify that this is the current version before use.

4.5.4.2: Delete paragraph in its entirety and replace with the following:

"4.5.4.2 Hot (51.5 ± 3°C, 125 ± 5°F) and ambient (21 ± 3°C, 70 ± 5°F) temperature. This test shall be conducted in accordance with Method 501.2, Procedure 1 of MIL-STD-810 except that the igniters shall be exposed to the specified temperatures until thermal stabilization is reached, and maintained at that temperature for a period of 6 hours (min.). The test specimens shall be removed from the conditioning cabinet; set up, and fired within 5 minutes. Observations shall be made for compliance with the applicable requirement."

4.5.4.3: Add the following new paragraph:

"4.5.4.3 Leak test. The igniter assemblies shall be immersed under twelve (12) inches of water at 70 ± 10°F (21 ± 6°C) for a minimum of one hour. Observation for evolution of air bubbles shall be made. Bubbles which appear on the surface of the test samples but are not released, or are released at a slowly decreasing rate are not to be contrived as indication of failure (Non-destructive Test). The test samples shall be removed, wiped off and subjected to the functioning tests of 4.5.4.1 and 4.5.4.2."

4.5.4.3: Change "4.5.4.3" to "4.5.4.4".

4.5.4.4: Change "4.5.4.4" to "4.5.4.5".

4.5.4.5:

Change "4.5.4.5" to "4.5.4.6".

Line 5: Change "3.5.4" to "3.5.5".

4.5.6, Line 1 and Line 2:

Change "4.5.6" to "4.5.5".

Change "Bridge" to "Electrical".

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1370-A199)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.