MIL-E-1/172G
24 November 1978
SUPERSEDING
MIL-E-1/172H
4 February 1971
(See note 9)

MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 5718

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

DESCRIPTION: Triode, subminiature, 500 MHz, medium Mu

Outline	---	3-1 (EIA)
Base	---	E8-10 (tinned leads)
Envelope	---	T3
Cathode	---	Coated unipotential

Base connections:

Pin No.	---	1	2	3	4	5	6	7	8
Element	---	g	nc	h	nc	k	h	nc	a

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Eb	Ec	Ehk	Rk	Rg	Ib	Ic	Pp	TE	Alt
Unit:	V	Vdc	Vdc	v	Ohms	Meg	mAdc	mAdc	W	°C	ft
Maximum:	6.6	165	0,-55	200	---	1.2	22.0	5.5	3.3	+220	Note 1
Minimum:	6.0	---	---	---	---	---	---	---	---	---	---
TEST CONDITIONS:	6.3	100	0	0	150	---	---	---	---	---	---

GENERAL:

Qualification - Required

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:00Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS		UNIT
						MIN	MAX	
	Quality conformance inspection, part 1							
1256	Electrode current (1) (anode)		0.4	II	Ib	6.0	11.0	mAdc
1256	Electrode current (2) (anode)	Ec = 7.0 Vdc; Rk = 0	0.4	II	Ib	---	100	µAdc
1266	Total grid current	Eb = 150 Vdc; Rk = 380 ohms; Rg = 1.0 Meg (see note 2)	0.4	II	Ic	0	-0.4	µAdc
1301	Heater current		0.4	II	If	140	160	mA
1306	Transconductance (1)		0.4	II	Sm	4,800	6,800	µmhos
1336	Heater-cathode leakage		0.4	II	Ihk	---	5	µAdc
1201	Short and discontinuity detection		0.4	II	---	---	---	---
	Quality conformance inspection, part 2							
1211	Insulation of electrodes		2.5	I	---	---	---	---
1031	Low-frequency vibration	15 G; Rp = 10,000 ohms; F = 40 Hz	2.5	I	Ep	---	25	mVac
1236	Power oscillation	F = 500 MHz; Eb = 150 Vdc; Rg/Ib = 20 mAdc	---	---	Po	600	---	mW
1246	Audio frequency noise	Ecal = 50 mVac; Ec = -4.0 Vdc; Rk = 0; Rg = 0.1 Meg; Rp = 0.01 Meg	2.5	I	EB	---	17	vu
1256	Electrode current (3) (anode)	Ec = -4.0 Vdc; Rk = 0	2.5	I	Ib	20	---	µAdc
1266	Grid emission	Ef = 7.5 V; Ec = -7.0 Vdc; Rg = 1.0 Meg (see note 4)	2.5	I	Ic	0	-0.4	µAdc
1306	Transconductance	Ef = 5.7 V	2.5	I	ΔSm Ef	---	10	%
1316	Amplification factor		---	---	Mu	23	31	---
1331	Direct-interelectrode capacitance	No shield	6.5	Code F	Cgp Cin Cout	1.1 1.6 0.5	1.8 2.8 0.9	pF pF pF

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:00Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 2 -Continued							
1116	Lead fatigue		2.5	Code F	---	---	---	---
2126	Envelope strain		6.5	I	---	---	---	---
1041	Shock	450 G; Ehk = +100 Vdc (see note 5)	---	---	---	---	---	---
1031	Vibration fatigue	2.5 G; fixed frequency; F=25 min, 60 max	6.5	See note 6	---	---	---	---
---	Post-shock and vibration-fatigue test end points:							
1031	Low-frequency vibration		---	---	Ep	---	100	mVac
1336	Heater cathode leakage		---	---	Ihk	---	15	µAdc
1306	Change in transconductance (1) of individual tubes		---	---	ΔSmt	---	15	%
1105	Permanence of marking		---	---	---	---	---	---

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSP LEVEL OR CODE	ALLOWABLE DEFECTIVES PER CHARACTERISTIC 1ST SAMPLE	ALLOWABLE DEFECTIVES PER CHARACTERISTIC COMBINED SAMPLES	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 3									
1506	Heater-cycling life	Ef = 7.0 V; 1 min "on", 4 min "off"; Ehk=140 Vac; Ec = Eb = 0	---	---	---	---	---	---	---	---
1516	Stability life	Ehk = +200 Vdc; Rg = 1.0 Meg; TA = room	---	---	---	---	---	---	---	---
---	Stability life-test end point:									
1306	Change in transconductance (1) of individual tubes		---	---	---	---	ΔSmt	---	10	%
1501	Intermittent life (room temperature)	Stability life-test, or equivalent conditions; TA=room (see notes 7 and 8)	---	---	---	---	---	---	---	---
---	Intermittent life-test end point (room temperature) (500 hours):									
1211	Insulation of electrodes		---	---	1	3	R	50	---	Meg

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:00Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSP LEVEL OR CODE	ALLOWABLE DEFECTIVES PER CHARACTERISTIC		SYMBOL	LIMITS		UNIT
					1 ST SAMPLE	COMBINED SAMPLES		MIN	MAX	
	Quality conformance inspection, part 3 -Continued									
---	Intermittent life-test end point (room temperature) (1,000 hours):									
1211	Insulation of electrodes		---	---	1	3	R	25	---	Meg
1501	Intermittent life (high temperature)	Stability life-test conditions; TE=+220°C (min)± (see note 3)	---	---	---	---	---	---	---	---
---	Intermittent life-test end points (500 hours) (high temperature):									
---	Inoperatives		---	---	1	3	---	---	---	---
1266	Total grid current		---	---	1	3	Ic	0	-0.6	µAdc
1301	Heater current		---	---	1	3	If	138	164	mA
1306	Change in trans-conductance (1) of individual tubes		---	---	1	3	ΔSm t	---	20	%
1306	Transconductance (2)		---	---	1	3	ΔSm Ef	---	15	%
1336	Heater-cathode leakage		---	---	1	3	Ihk	---	10	µAdc
1211	Insulation of electrodes		---	---	1	3	R	50	---	Meg
1306	Transconductance (1), average change		---	---	---	---	Avg ΔSm t	---	15	%
---	Total defectives		---	---	3	6	---	---	---	---
---	Intermittent life-test end points (1,000 hours)(high temperature):									
---	Inoperatives		---	---	1	3	---	---	---	---
1266	Total grid current		---	---	1	3	Ic	0	-0.6	µAdc
1301	Heater current		---	---	1	3	If	138	164	MA
1306	Change in trans-conductance (1) of individual tubes		---	---	1	3	ΔSm t	---	25	%
1306	Transconductance (2)		---	---	1	3	ΔSM Ef	---	20	%
1336	Heater-cathode leakage		---	---	1	3	Ihk	---	10	µAdc
1211	Insulation of electrodes		---	---	1	3	R	25	---	Meg
---	Total defectives		---	---	4	8	---	---	---	---

Source: https://assist.dla.mil -- Downloaded: 2026l0-15T13:00Z
Check the source to verify that this is the current version before use.

NOTES:

1. See "Reduced pressure (altitude) rating", and altitude, maximum peak voltage.

2. This test to be performed at the conclusion of the holding period.

3. Envelope temperature (TE) requirements, when measured in accordance with the temperature by conduction-band measurement (method 1226), will be satisfied if a tube having bogey Ib (±5 percent) under normal test conditions, is determined to operate at or above minimum specified temperature at any position in the life-test rack.

4. Prior to this test, tubes shall be preheated a minimum of 5 minutes at the conditions specified below. The 3-minute test is not permitted. Test at specified conditions within 3 seconds after preheating. Grid emission shall be the last performed on the sample selected for grid-emission test.

EF	EC	EB	Rk	RG
V	Vdc	Vdc	Ohms	Meg
7.5	0	100	150	1.0

5. A grid resistor of 0.1 megohm shall be added; however, this resistor shall not be used when a thyratron-type short indicator is used.

6. This test shall be conducted on the initial lot and thereafter on a lot approximately every 6 months. When one lot has passed, the 6-month rule shall apply. In the event of lot failure, the lot shall be rejected and the succeeding lots shall be subjected to this test until a lot passes. MIL-STD-105, sample size code letter E, shall apply.

7. The life-test sample shall consist of 20 tubes per lot and not more than 1 tube failure shall be permitted. In the event of rejection of the first sample, due to failure of more than 1 tube, a second sample of 40 tubes shall be selected from the lot. Acceptance shall then be based on the combined first and second samples. The total tube failures from the combined first and second samples shall not exceed three.

8. Early release may be made at 500 hours providing no lot failure due to this life test or the 1,000-hour intermittent life test (high temperature) has ocured in the preceding 3 consecutive lots, and the lot under consideration is acceptable at 500 hours. One lot failing the 1,000-hour intermittent (high temperature) or the 1,000-hour intermittent (room temperature) life test shall result in loss of eligibility for the early release procedure. All intermittent (room temperature) life-test samples shall be operated to 1,000 hours.

9. Revision letters are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army -
Air Force - 99
DLA - ES

User activities:
Navy - AS, MC, CG, SH , OS
Air Force - 11

Preparing activity:
Navy - EC

Agent: DLA - ES

(Project 5960-3183)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:00Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:00Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
NAVAL ELECTRONIC SYSTEMS COMMAND
WASHINGTON, D.C. 20360

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
NAVY DEPARTMENT
DOD 316

U.S.MAIL

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D.C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:00Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER (Number) AND TITLE MIL-E-1/172G, Electron Tube, Receiving Type 5718

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY (Printed or typed name and address — Optional)

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JUN 72 MAY BE USED UNTIL EXHAUSTED

Source: https://assist.dla.mil -- Downloaded: 202640-15T13:00Z
Check the source to verify that this is the current version before use.