MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 6F5[1/]

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the electron tube described herein shall consist of this specification and the latest issue of MIL-E-1.

DESCRIPTION: Triode, high-Mu

Outline	---	8-4(EIA)
Base	---	B7-22
Envelope	---	MT-8
Cap	---	C1-4
Cathode	---	Coated unipotential

Base connections:

Pin No.	---	1	2	3	4	5	7	8	Cap
Element	---	sh	h	nc	a	nc	h	k	g

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Eb	Ec	Ehk	Alt
Unit:	V	Vdc	Vdc	v	ft
Maximum:	6.9	330	---	100	10,000
Minimum:	5.7	---	---	---	---
TEST CONDITIONS:	6.3	250	-2	---	---

GENERAL:

(B) Qualification - Not required

1/ Formerly 6F5, 6F5GT
(See note 1)

(B) denotes change

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 202610-15T13:02Z
Check the source to verify that this is the current version before use.

Method	Requirement or test	Notes	Conditions	Symbol	Limits Min	Limits Max	Unit
	Quality conformance inspection, part 1	2					
1266	Total grid current	3		Ic	0	-0.6	µAdc
1231	Emission	3	Eb = Ec = 30 Vdc	Is	35	---	mAdc
1256	Electrode current (anode)			Ib	0.4	1.7	mAdc
1321	AC amplification		Esig = 0.2 Vac; Ebb = 100 Vdc; Ecc = 0	Ep	8.4	---	Vac
1246	Audio frequency noise	4	Esig = 100 mVac; Rp = 0.2 Meg	---	---	---	---
1201	Short and discontinuity detection	5		---	---	---	---
	Quality conformance inspection, part 2						
1211	Insulation of electrodes			---	---	---	---
1031	Low-frequency vibration		Rp = 10,000 ohms	Ep	---	250	mVac
1301	Heater current			If	275	325	mA
1336	Heater-cathode leakage			Ihk	---	20	µAdc
1111	Base pin solder depth			---	---	---	---
1316	Amplification factor			Mu	85	115	---
1306	Transconductance			Sm	1,100	2,000	µmhos
1101	Secureness of base, cap, or insert			---	---	---	---
1105	Permanence of marking			---	---	---	---
	Quality conformance inspection, part 3						
1501	Intermittent life		Group A; Ehk = 100 V	---	---	---	---
---	Intermittent life-test end point (500 hours)						
1321	AC amplification		Esig = 0.2 Vac; Ebb = 100 Vdc; Ecc = 0	Ep	7.0	---	Vac

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:02Z
Check the source to verify that this is the current version before use.

NOTES:

1. Tube type 6F5GT was deleted from this TSS in the A revision. Tubes for replacement purposes shall be procured to this specification sheet.
2. Unless otherwise specified, the AQL (percent defective) for each test listed under QCI, part 1, shall be 0.65, inspection level II.
3. This test shall be performed at the conclusion of the holding period.
4. The rejection level shall be set at the VU meter reading obtained during calibration.
5. The AQL (percent defective) shall be 0.4, inspection level II.

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Air Force - 99
DLA - ES

User activities:
Army - ME
Navy - AS, CG, MC, OS
Air Force - 19

Agent:
DLA - ES

Preparing activity:
Army - ER

(Project 5960-3352)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:02Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:02Z
Check the source to verify that this is the current version before use.