INCH-POUND
MIL-PRF-1/191D
20 March 2007
SUPERSEDING
MIL-E-1/191C
14 July 1970

PERFORMANCE SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 6B4G 1/

Inactive for new design
after 21 July 1997

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the electron tube described herein shall consist of this document and the latest issue of MIL-PRF-1.

DESCRIPTION: Triode, power amplifier.

Outline - - - 16-3 (EIA), 12-15 (EIA).

Base - - - B8-11 (phenolic), B8-110 (phenolic) or B8-118 (phenolic).

Envelope - - - ST16, T-12.

Cathode - - - Coated filament.

Base connections:

PIN No.	---	1	2	3	4	5	6	7	8
Element	---	nc	f	a	nc	g	nc	f (see note 3)	nc

ABSOLUTE RATINGS:

Parameter:	Ef	Eb	Ec	Pp	Ik	Alt
Unit:	V	V dc	V dc	W	mA dc	ft
Maximum:	6.9	360	---	15	100	10,000
Minimum:	5.7	---	---	---	---	---
Test conditions:	6.3 V ac	300	-62	---	---	---

GENERAL:

Qualification - Not required.

1/ See note 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:02Z
Check the source to verify that this is the current version before use.

TABLE I. Testing and Inspection.

Method MIL-STD-1311	Requirement or test	Conditions	Acceptance level (see note 4)	Symbol	Limits		Unit
					Min	Max	
	Qualification inspection						
1216	Base material insulating quality		---	---	---	---	---
	Conformance inspection, part 1						
1266	Total grid current	See note 2	0.65	Ic	0	-3.0	μA dc
1256	Electrode current (anode)			Ib	22.5	57.5	mA dc
1341	Power output	Esig = 40 V ac; Rp = 1,100 ohms (see note 2)	0.65	Po	4.3	---	W
1246	Audio frequency noise	Esig = 700 mV ac; Rp - 2,000 ohms; Ef = 6.3 V dc	0.65	EB	---	17	vu
1231	Emission	Eb = Ec = 30 V dc	0.65	Is	140	---	mA dc
1201	Short and discontinuity detection		0.4	---	---	---	---
	Conformance inspection, part 2						
1031	Low-frequency vibration	Ec = 70 V dc; Rp = 2,000 ohms	---	Ep	---	500	mV ac
1301	Filament current		---	If	1.08	1.32	A
1306	Transconductance		---	Sm	3,200	4,800	μmhos
1316	Amplification factor		---	Mu	3.7	4.3	---
1211	Insulation of electrodes		4.0	---	---	---	---
1101	Secureness of base, cap, or insert		---	---	---	---	---
1111	Base pin solder depth		---	---	---	---	---
1105	Permanence of marking		---	---	---	---	---
	Conformance inspection, part 3						
---	Life-test provisions	Group A	---	---	---	---	---
---	Life-test end point (500 hours)	Power output	---	Po	2.75	---	W

NOTES:

1. Tube types 2A3 and 6A3 are hereby deleted from this tube specification sheet.

2. This test to be performed at the conclusion of the holding period.

3. Pin 7 is to be connected to ground for equipment application.

4. This specification sheet uses accept on zero defect sampling plan in accordance with MIL-PRF-1, table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:02Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-PRF-1, this document references MIL-STD-1311.

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5960-2007-009)

Review activities:
Army - AR, CR4
Navy - AS, CG, MC, OS, SH
Air Force - 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:02Z
Check the source to verify that this is the current version before use.