MIL-A-6752A(ASG)
AMENDMENT-3
3 MARCH 1958
Superseding
Amendment -2
15 November 1955

MILITARY SPECIFICATION

AMMETERS, VOLTMETERS, AND LOADMETERS; DIRECT CURRENT

This amendment forms a part of Military Specification MIL-A-6752A(ASG), dated 24 December 1953, and has been approved by the Department of the Air Force and by the Navy Bureau of Aeronautics.

Page 1, paragraph 2.1:

Under Specifications add the following:

"MIL-L-25142 Luminescent Material, Fluorescent"

Delete the following:

"Air Force-Navy Aeronautical

AN-L-1 Luminescent Material; Fluorescent"

Under Standards in the title of "MS25025" delete "Type J-1", and add the following standards:

"MS33558 Numerals and Letters, Aircraft Instrument Dial, Standard Form of
MS91586 Shunts, Instrument, External, 50-Millivolt, Style MSA
MS91587 Shunts, Instrument, External, 50-Millivolt, Style MSB
MS91588 Shunts, Instrument, External, 50-Millivolt, Style MSC"

Under Air Force-Navy Aeronautical Standard Drawings delete the following:

"AN3200 Shunt-Ammeter, External, 50 Millivolt
AND10400 Numerals and Letters - Aircraft Instrument Dial, Standard Form of"

Page 2, paragraph 3.3.4: In the last line delete "AN-L-1" and substitute "MIL-L-25142."

Page 3, paragraph 3.3.11: Add the following at the end of the first sentence "unless otherwise specified."

Page 3, paragraph 3.3.14: Delete, and substitute the following paragraph:

"3.3.14 Adjustment.- The ammeters shall be adjusted to provide full-scale reading at 50 millivolts with a shunt lead resistance of 0.5 ohm in series with the meter. Loadmeters shall be adjusted to provide the 1.0 reading at 50 millivolts and shunt lead resistance of 0.5 ohm. The shunt shall conform to Standards MS91586, MS91587, and MS91588".

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:24Z
Check the source to verify that this is the current version before use.

Page 4, paragraph 3.9: Add the following sentence to end of paragraph: "Temperature influence is the change (percentage of full-scale value) in the indication caused by a difference in ambient temperature of ±10°C from a reference temperature."

Page 5, paragraph 3.18: Delete the paragraph in its entirety.

Page 5, paragraph 3.19: In the second line delete "insert nut" and substitute "mounting screw".

Page 5, paragraph 3.21.1: In the second line delete "Drawing AND10400" and substitute "Standard MS33558".

Page 5, paragraph 3.21.1.1: In the last line delete "AN-L-1" and substitute "MIL-L-25142".

Page 5, paragraph 3.21.2: Delete, and substitute the following paragraph:

"3.21.2 The following note in letters of 0.075 inch minimum height shall be marked on the back of each ammeter:

'USE WITH 50 MV SHUNT'"

Page 8, FIGURE 3:

(a) Delete the numerals "-.1" and "1.25" from the dial.

(b) Add the following note:

"MS PART NUMBER MAY BE PLACED ON EITHER THE DIAL OR ON THE MASK."

(c) In the table after "MINOR GRADS", delete "0.031" and "0.015" and substitute "0.062" and "0.010", respectively.

Page 11, paragraph 4.3.1: Add ", as applicable" immediately following "tests".

Page 11, paragraph 4.3.3: In the third line between "the" and "tests" add the word "applicable".

Page 12, paragraphs 4.5.5 and 4.5.5.1: Delete, and substitute:

"4.5.5 Temperature influence.- Meter readings shall be taken with the meter at a reference temperature of 25° ±2°C. Readings shall be taken at not less than five points (approximately equidistant) on the scale, such readings to include the maximum scale value. The meter shall then be subjected to a temperature 20°C above the reference temperature for not less than 2 hours, until thermal stability is attained, and the readings repeated. The same procedure shall be repeated at a temperature 20°C below the reference temperature. One-half of the difference between each reading at the high temperature and the corresponding reading at the reference temperature shall be expressed as a percentage of full-scale value. A similar computation shall be made for the readings at the low temperature. If the influences above and below the reference temperature are not equal, the greater value shall be considered the temperature influence. (See 3.9.)"

Page 14, paragraph 4.5.14: Delete the paragraph in its entirety.

Page 14, paragraph 4.5.15: In the fourth line delete "hole in the mounting nut" and substitute "mounting hole".

Custodians:
Navy - Bureau of Aeronautics
Air Force

-oOo-

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:24Z
Check the source to verify that this is the current version before use.