BBB-T-001054(GSA-FSS)
August 27, 1965

INTERIM FEDERAL SPECIFICATION

TROUSERS, DRESS, MEN'S

This Interim Federal Specification was developed by the General Services Administration Federal Supply Service, Washington, D. C. 20406, based on currently available technical data. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers requirements for cuffed dress trousers of wool worsted, or wool worsted and polyester blend, or wool worsted and acrylic blend primarily intended for use by male corpsmen of the Job Corps centers.

1.2 Classification.

1.2.1 Type and style. Trousers covered by this specification shall be of one type and style.

1.2.2 Sizes. Unless otherwise specified the finished trousers shall be furnished in waist sizes of 28, 29, 30, 31, 32, 33, 34, 36, 38, 40, 42, 44, and 48 and inseam sizes of 28, 29,30, 31, 32, 33, 34, 36 and 38.

2. APPLICABLE SPECIFICATIONS, STANDARDS, AND OTHER PUBLICATIONS

2.1 Specifications and standards. The following specifications and standards of the issues in effect on date of invitations for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specification:

R-N- 91 -- Naphthaline, technical.
V-B-871 -- Button, Sewing Hole, and Button Staple (Plastic and Pearl).
V-F-106 -- Fasteners, Slide, Interlocking.
V-T-276 -- Thread, Cotton.
CCC-T-191 -- Textile Test Methods.
CCC-C-438 -- Cloth, Cotton, Buckram.
PPP-B-636 -- Box, Fiberboard.
UU-P-268 -- Paper, Kraft, Untreated, Wrapping.

Federal Standards:

Fed. Std. No. 751 -- Stitches, Seams, and Stitching.
Fed. Std. No. 102 -- Preservation, Packaging, and Packing Levels.
Fed. Std. No. 123 -- Marking for Domestic Shipment (Civilian agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C., 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

FSC 8405

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:28Z
Check the source to verify that this is the current version before use.

Military Standards:

MIL-STD-105 -- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 -- Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

Rules and Regulations Under the Textile Fiber Products Identification Act.

(Copies may be obtained free of charge from the Federal Trade Commission, Washington, D. C.)

ASTM-D-1375-59T (Method "c")

(Copies may be obtained from the American Society for Testing and Materials, 1916 Race Street, Philadelphia 3, Pennsylvania).

3. REQUIREMENTS

3.1 Sample. Samples when furnished are solely for guidance and information to the contractor (see 6.2).

3.2 Preproduction sample approval. When specified (see 6.3), before production is commenced, a pair of trousers covered by this specification shall be submitted or made available to the contracting officer or his authorized representative for inspection as specified in 4.2. The approval of the preproduction sample authorizes the commencement of production, but does not relieve the supplier of responsibility for compliance with all of the applicable provisions and requirements of this specification. The preproduction sample shall be manufactured by the supplier in the same facilities to be used for the manufacture of the production item.

3.3 Materials.

3.3.1 Basic cloth.

3.3.1.1 Fiber content. The basic cloth shall be 100 percent wool worsted; or a blend of 55 ± 1 percent polyester fiber and 45 ± 1 percent wool worsted; or a blend of 70 ± 1 percent acrylic fiber and 30 ± 1 percent wool worsted. The fibers shall be of virgin quality and of a grade and staple length suitable to meet the requirements of this specification.

3.3.1.2 Weight. The weight of cloth shall be not less than 6.0 or more than 7.5 ounces per square yard.

3.3.1.3 Yarns per inch. The yarns per inch shall be not less than 50 in the warp direction and not less than 38 in the filling direction. Warp and filling yarns may be plied or single.

3.3.1.4 Weave. The weave shall be plain.

3.3.1.5 Color. The color shall be bankers grey produced by a blend of stock dyed fibers or solution dyed fibers of black and white. Fibers of a natural color suitable to produce the desired color of cloth are acceptable. (see 6.2).

3.3.1.5.1 Matching. The color shall match the standard sample swatch under natural (morth sky) daylight, or artificial daylight having a color temperature of 7500° Kelvin and shall be a good approximation to the standard sample under incandescent lamplight at 2800° Kelvin (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:28Z
Check the source to verify that this is the current version before use.

3.3.1.5.2 Colorfastness. The cloth shall show good colorfastness to wet dry cleaning, crocking, perspiration and light when tested as specified in 4.3.

3.3.1.6 Finish. The cloth shall have a clear finish, and so finished to provide both stability of color and finish. The use of chemical compounds for all wool cloth to impart permanent press retention is acceptable.

3.3.1.6.1 Shrinkage. The cloth shall be preshrunk so as not to exceed a residual shrinkage of more than 2 percent in the warp direction and 2 percent in the filling direction when tested as specified in 4.3.

3.3.1.6.2 The use of dyestuffs, detergents, or other chemicals or finishing agents which would cause deterioration under normal warehouse storage conditions or cause dermatitis on prolonged intimate skin contact is prohibited.

3.3.1.7 Pilling. The pilling resistance of the cloth shall have a rating of not less than 3-medium (moderate pilling) when tested as specified in 4.3.

3.3.1.8 Breaking strength. The breaking strength of the cloth shall be not less than 100 pounds in the warp direction and not less than 80 pounds in the filling direction when tested as specified in 4.3.

3.3.1.9 Seam efficiency. The cloth shall have a seam efficiency of not less than 80 percent when tested as specified in 4.3.

3.3.2 Waistband interlining. The interlining of the waistband shall be continuous and shall be buckram superimposed on nonwoven cloth. The nonwoven cloth shall weigh not less than 6.2 ounces per square yard and shall be not less than .050 inch in thickness, measuring 1-1/4 ± 1/16 inch in width. The stiffness of the nonwoven cloth shall be suitably rigid for the purpose intended, shall be dimensionally stable, and the bonding agents shall be unaffected by wet drycleaning agents. The buckram shall be in accordance with type II, class 2 of CCC-C-438. The color shall be bleached white and the width shall be 2 ± 1/4 inches. The interlining composed of the above two components shall be stitched together with one or more rows of stitch type 101 or equal, having not less than 6 stitches per inch. As an alternate for nonwoven cloth the interlining may consist of a nylon scrim cloth sufficiently rigid to be equal or better than the nonwoven cloth.

3.3.3 Pocketing, waistband, fly and crotch lining (curtain). Cloth used for the pocketing, waistband lining, fly lining and crotch curtain shall be of a twill or plain weave having not less than 148 total yarns per inch in the warp and filling providing there are not less than 65 yarns per inch in either the warp or filling direction. The cloth shall be 100 percent cotton, or a blend of cotton-nylon, cotton-polyester, or cotton-acrylic. Cloth shall weigh not less than 5.0 ounces per square yard, and shall be preshrunk to 1 percent residual shrinkage when tested as specified in 4.3.

3.3.3.1 Color. The cloth shall be dyed black; however, when aniline black is used it shall be properly oxidized and rinsed free of uncombined metallic salts. The use of sulphur dyes is prohibited.

3.3.3.1.1 Colorfastness. The cloth shall show good colorfastness to wet dry cleaning, perspiration, and crocking when tested as specified in 4.3.

3.3.3.2 Seam efficiency. The cloth shall have a seam efficiency of not less than 80 percent when tested as specified in 4.3.

3.3.3.3 Finish. The cloth shall be desized, and residual sizing, finishing, and nonfibrous materials shall not exceed 2 percent when tested as specified in 4.3.

3.3.4 Gimp. The gimp for reinforcing buttonholes shall be not less than commercial No. 8, 3 cord soft or glazed finish cotton having a breaking strength of not less than 6.5 pounds. The color shall be black.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:28Z
Check the source to verify that this is the current version before use.

3.3.5 Sewing thread. The sewing thread used in fabrication of the trousers for the following operations shall be cotton in accordance with V-T-276: Where suitable, mercerized thread, type IC of V-T-276 is permissable in lieu of type IA:

Pocketing, seaming and stitching	— Type IA3 - Ticket No. 30 or 50 — 3 ply minimum.
Bartacking and buttonholes	— Type IA3 - Ticket No. 70 — 2 ply minimum.
Inside stitching	— Type IA3 - Ticket No. 70 — 2 ply minimum.
Button sewing	— Type IA3 - Ticket No. 20 — 4 ply minimum.
Attacking waistband interlining	— Type IA3, IA1, or IA2 - Ticket No. 50 — 2 ply minimum.

3.3.5.1 Color and colorfastness. The color of the sewing thread, except type IA1 and IA2, shall be black and shall meet the same colorfastness requirements of the base cloth, except that there is no colorfastness requirements for perspiration and crocking.

3.3.6 Buckle. The buckle or buckles shall be of noncorrosive metal or metal treated to be noncorrosive, for securing the top of the fly opening, and shall be a two prong center bar type with a 1/2 inch opening. The buckle or buckles shall be of a one hook catch device attached by staple and plate, and a corresponding bar-catch secured on right waistband facing (see 4.2.2.5).

3.3.7 Buttons. The button for the tab at the top of the trouser opening shall be type II, line 20, class "D", any 4 hole style conforming to V-B-871. The button for the left back pocket shall be type II, line 18-20, class "D", any style. Buttons shall be black or grey approximately matching the color of the base cloth, and shall have a glossy finish.

3.3.8 Slide fasteners. The slide fasteners shall be type I, style 1 with cam lock, short pull tab, size LM, with brass, aluminum or zinc chain conforming to V-F-106. The tape for the fastener shall be in accordance with V-F-106 and shall be black in color or closely match the color of the base cloth. The colorfastness requirements shall be the same as the base cloth. The length of the slide fastness shall be proportinate with the size of the trousers.

3.4 Design. The trousers shall be of single needle construction with separate interlined waistband inverted side seams, back pocket darts, cuffed leg bottoms, seat seam outlets, slide fastener closure, plain front, two side pockets and two back pockets, and belt loops.

3.5 Patterns. Patterns shall be furnished by the manufacturer and shall be graded in accordance with good commercial practice. Patterns shall provide a minimum allowance of 3/8 inch for all seams, except top of seat seam which shall provide a minimum of 1-1/8 inch outlet.

3.6 Construction.

3.6.1 Body. The body of the trousers shall be constructed of two front and two back panels joined by side and seat seams and inseams using stitch type 301 or 401, seam type SSa-1, with an overedge stitch type 502 or 503 and stitching type EFd-1. There shall be 10-12 stitches per inch used in joining the panels and not less than 6 stitches per inch for overedging. The top of the trousers shall be fashioned with a vertical dart, joining two edges of the basic cloth, between the top of each back pocket and the bottom edge of the waistband.

3.6.2 Pockets. There shall be two back pockets made with not more than 2 pieces of cloth specified in 3.3.3, and shall measure not less than 6 ± 1/8 inches deep when finished. The pocketing cloth shall extend into the waistband and shall be secured at that point by operations in construction of the waistband. The width of the finished pockets shall measure 6-1/2 ± 1/8 inches. The bottom and sides of the pocket shall have 1/4 ± 1/16 inch gauge seams, single stitched, using stitch type 301 or 401, stitching type SSc-1 or equal using 10-12 stitches per inch. The opening of the back pockets shall measure 5-1/4 ± 1/8 inches and shall have pocket bearers on both edges of pocket made of basic cloth measuring not less than 3/4 inch. A welt of not less than 1/8 inch made of the basic cloth shall be placed on the pocket facing on each edge of the pocket opening. There shall be a button, 3.3.7 centered on the bearer of the left hand back pocket with an opposing buttonhole, 3.6.8. There shall be two straight or 1/4 cut side pockets with buttons cut on the radius, made from single or 2 pieces of cloth, 3.3.3, measuring 6-1/2 ± 1/4 inches wide, 12-1/2 ± 1/4 inches long. There shall be a pocket opening of 6 ± 1/4 inches with pocket bearers not less than 1-1/2 inches in width. The top of the pockets shall extend not less than 1/2 inch into the waistband and caught in the stitching of the waistband. The pockets shall be formed by one continuous stitch 1/4 ± 1/16 inch gauge using stitch type 301 or 401, seam type SSc-1 or equal with 10-12 stitches per inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:28Z
Check the source to verify that this is the current version before use.

3.6.3 Waistband. The waistband shall be made of basic cloth, 3.3.1, having a lining, 3.3.3, and interlining, 3.3.2, with all cloth cut on the bias. The finished width of the face waistband shall measure not less than 1-3/4 ± 1/8 inches having all raw edges turned under. The interlining measuring 2 ± 1/8 inches shall have the lining, 3.3.3, overlapping the buckram not less than 1/4 inch and securely stitched thereon. The interior of the waistband shall be composed of two pieces of lining, the lower portion measuring 1-1/4 ± 1/16 inches and the top portion measuring 3/4 ± 1/16 inches. The top portion shall be finished 3/4 inch from the top of the trousers with face material overlapping the waistband to that point and stitched through the top lining piece and interlining. Stitch type 101, 301, or 401 and any suitable seam type using 10 to 12 stitches per inch shall be used. The waistband shall have no less than one buckle, 3.3.6, the plate attached to the waistband overlap at top of fly and the corresponding bar-catch on the right waistband facing. The inside of the waistband may contain antislip patches (grippers) constructed of latex or synthetic latex laminated and stitched to a cotton sheeting. The grippers shall measure 2 inches by 1-1/4 inches and there shall be 4 in number stitched equidistant on the waistband with the rubber face to the outside.

3.6.4 Fly. The fly shall measure 1-1/2 ± 1/8 inches in width and 10 ± 1/8 inches long (size 40 trousers). The right side of the fly shall be constructed of single ply basic cloth lined with cloth, 3.3.3, having a 3/4 inch turnunder, stitched 1/4 ± 1/8 inch gauge to tape of slide fastener. The left fly shall be of double plied basic cloth with outer edge of inner ply stitched to face ply with 1/8 inch gauge inverted stitch but not through to face of basic cloth. Inside edge of inner ply shall be overedge stitched with stitching type EFd-1. The left slide fastener tape with one side of fastener shall be secured to the inner ply of cloth with not less than single stitching of 1/8 inch gauge, using stitch type 301 or 401 and any suitable seam type with stitches 10 to 12 per inch. The right slide fastener tape shall be secured at the inner edge of fly between the front leg panel of cloth and the fly facing by using stitch type 301 or 401, seam type SSa-1 and using 10 to 12 stitches per inch. The right fly shall have a French tab of double plied basic cloth measuring 2 ± 1/4 inches in length and 1-1/2 ± 1/8 inches in width containing an eyelet end taper bar type buttonhole 1/2 inch from the free end of the tab. The edges of each ply of cloth shall be turned in 1/4 inch and secured with an inverted stitch of 1/8 inch gauge, seam type SSa-1, using 10 to 12 stitches per inch. The opposing end of the tab shall be caught between the lining and face of the fly. A 20 line button, 3.3.7, shall be placed approximately 3 inches from the left fly opening on the lower piece of the waistband lining to correspond with the buttonhole on the right fly.

3.6.5 Crotch lining. The crotch, at which point front and back leg pieces of cloth are junctured, there shall be a piece of lining, 3.3.3, single or ply, caught in each inseam of the interior of the trouser legs. The lining pieces or curtains shall extend from the base of the slide fastener downward along each front panel at the inseam for a distance of approximately 6 inches, and shall measure 2 to 2-1/2 inches wide at the crotch juncture and gradually taper to 1/4 inch in width. The edges of the lining shall be pinked if of single ply.

3.6.6 Belt loops. There shall be not less than (7) seven belt loops of basic cloth interlined with buckram, 3.3.2, attached to the waistband and spaced equidistant to each other. Each finished belt loop shall measure 3/8 to 1/2 inch in width and extend the width of the waistband interlining. The loops shall be constructed by folding a piece of the basic cloth to center with the edges turned under on the underside of the loop and the butted edges covered-stitched with stitching type EFh-1 with not less than 6 stitches per inch. The ends of the belt loops shall be turned under not less 3/8 inch and securely stitched to the waistband.

3.6.7 Cuffs. The trousers shall have 2 ply turned-up cuffs, formed by the extremities of the trouser panels, measuring 1-3/4 ± 1/8 inch in width with the raw edge of the cloth overedge stitched using stitching type EFd-1 with not less than 6 stitches per inch. Each finished cuff shall be securely tacked with sewing thread at the top of the cuff at each inseam and outseam of the trouser legs.

3.6.8 Buttonholes. Buttonholes shall be of the eyelet end taper bar type reinforced with gimp, 3.3.4, having a cut opening of 1/2 to 5/8 inch for 20 line buttons and 3/8 to 1/2 inch cut opening for 18-20 line buttons.

3.6.9 Bartacks. The trousers shall have all strain points bartacked using stitch type 304 and not less than 25 stitches per inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:28Z
Check the source to verify that this is the current version before use.

3.6.10 Stitches, seams, and stitchings. Stitch, seam, and stitching types, as specified shall conform to Fed. Std. No. 751. Whenever two or more methods of seams or stitches are given for the same operation any one may be used. Where stitch type 401 is used, the underthread (looper) shall be on the inside of the trousers.

3.6.11 Stitches per inch. The minimum and maximum number of stitches per inch shall be as specified herein.

3.6.12 Thread breaks and ends of seams. Ends of all seams and stitchings produced with 301 stitch type, when not caught in other seams or stitchings shall be backtacked not less than 1/4 inch. Thread breaks (all stitch types) shall be secured by stitching back of the break not less than 1/2 inch. Skipped stitches or thread breaks (401 stitch type) may be repaired using 301 stitch type.

3.7 Size measurements. The finished measurements for waist, rise, seat, and inseams for sizes, 1.2.2, shall be in accordance with good commercial practice.

3.8 Fiber identification. Each trouser shall be labeled or ticketed for fiber content in accordance with the Rules and Regulations under the Textile Fiber Products Identification Act.

3.9 Labels. Each trouser shall have a "size" label applied by decalcomania, printing, stamping or stenciling or a ticket securely attached to the waistband of the trousers, or a woven cotton or synthetic cloth label securely attached to the trousers. The contents of the size label shall include the waist and inseam size or the stock number. A cloth label or a ticket shall contain the fiber information and in addition may include the size information. When a printing method is used for the size information a separate ticket or woven label shall be used for the fiber content information. Markings shall not show off setting, smearing, or bleeding. In addition each trouser shall have a label with the name of the manufacturer permanently marked thereon.

3.10 Pressing and cleaning. Trousers shall be pressed smooth, free of wrinkles. Pin tickets, spots and stains shall be removed.

3.11 Workmanship. The finished trousers shall conform to the quality and grade of product established by this specification. The occurrence of defects shall not exceed the applicable acceptable quality level.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Inspection. Inspection shall be in accordance with provisions of MIL-STD-105, except where otherwise indicated hereinafter.

4.2.1 Testing of components. Testing of components shall be in accordance with applicable subsidiary specifications referenced herein to the extent applicable, except that this specification shall govern in the event of conflict. The unit for expressing lot sizes and the sample unit for testing each component shall be in accordance with applicable subsidiary specifications.

4.2.1.1 Sampling for testing. The sample unit for testing of each component not covered by subsidiary specifications referenced herein shall be the amount of material required to perform all required determinations for all test characteristics once. Unless otherwise specified in subsidiary specifications, the inspection level for each component shall be S-1 of MIL-STD-105. The acceptable quality level (AQL) for each characteristic tested shall be 6.5 defects per 100 units. The lot size and sample unit for testing shall be as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:28Z
Check the source to verify that this is the current version before use.

Component:	Lot size expressed as:	Sample unit for testing:
Lining	Yard	1 continuous yard, full width
Gimp	Pound	Spool or tube
Basic cloth	Yard	2 continuous yards, full width
Interlining:		
Nonwoven cloth	Yard	1/2 yard, full width
Nylon scrim	Yard	1/4 yard, full width

4.2.2 Examination of end item. The classification of defects found during examination shall be in accordance with list shown in 4.2.2.1. The applicable inspection levels and acceptable quality levels (AQL's) shall be as indicated in 4.2.2.3. The sample unit for these examinations shall be one pair of trousers.

4.2.2.1 Classification of defects. All defects shall be classified as indicated below, except those with an asterisk (*) in classification column which shall be classified as follows:

Major defect -- When seriously affecting appearance or serviceability.

Minor A defect -- When affecting appearance or serviceability but not seriously.

Defect	Classification			
	Major	(*)	Minor	
			A	B
Material defect and damages:				
a. Any hole or weakening defect such as a smash, multiple float, or loose slub		(*)		
b. Shade bar, or unsightly slub		(*)		
c. Needle chew, cut, tear, mend or burn		(*)		
NOTE: Material defects and workmanship damages are to be classified as indicated above only when the condition is one which weakens the cloth or trousers, or when it is conspicuously located as to be clearly noticeable. Non-weakening conditions which are inconspicuous, shall not be classified as defects.				
Shaded parts:				
Any outside part shaded		(*)		
Cleanness:				
a. One or more spots or stains of a permanent nature..		(*)		
b. One or more removable spots or stains clearly noticeable			X	
c. Thread ends not trimmed or loose thread not removed on major portion of trousers				X
Seams, stitching, and stitch types:				
a. General:				
1. Any part of trouser caught in any unrelated operations or stitching		(*)		
2. Seams twisted, puckered, or pleated affecting appearance			X	
3. Wrong shade or two shades of thread used on outside of trousers			X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:28Z
Check the source to verify that this is the current version before use.

Defect	Classification			
	Major	(*)	Minor	
			A	B
Material defect and damages: (cont'd)				
4. Ends of seams when not caught in other seams or stitching backtacked less than 1/4 inch.....			X	
5. Thread breaks (all stitch types) stitched less than 1/2 inch beyond each end of break				X
b. Gage of stitching:				
1. Unevenly gaged or various stitching not uniform, affecting appearance			X	
2. Beyond range or width specified or varies more than 1/16 inch when no range is specified				X
c. Open seams:				
1. Any open seam:				
---up to 1/4 inch inclusive				X
---over 1/4 inch up to 1 inch inclusive			X	
---over 1 inch	X			
2. On hems:				
---more than 1/2 inch				X
NOTE: One or more broken stitches or two or more continuous skipped or run-off stitches constitute an open seam.				
d. Raw edges:				
1. On the outside:				
1/4 inch up to 3/4 inch inclusive			X	
---over 3/4 inch	X			
2. On the inside:				
---1 inch up to 2 inches inclusive				X
---over 2 inches	X			
e. Seams and stitch types:				
1. Not specified seam or stitch type			X	
2. Looper thread exposed on the outside of trousers when 401 stitch type is used	X			
f. Stitch tension:				
1. Loose tension resulting in a loose seam	X			
2. Tight tension - (stitches break when normal tension is applied)	X			
g. Stitches per inch (to be scored only when the condition exists on major portion of seam):				
1. Less than minimum specified			X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:28Z
Check the source to verify that this is the current version before use.

Defect	Classification			
	Major	(*)	Minor	
			A	B
Material defect and damages: (cont'd)				
Buttonholes:				
a. Stitching not securely caught in cloth causing stitches to pull away from cloth	X			
b. Buttonholes not corresponding to size of button so that they do not button properly	X			
c. Buttonholes missing			X	
Buttons:				
a. Missing, loose, or broken				X
Bartacks:				
a. Not bartacked				X
b. Not required stitches per bartack				X
Waistband:				
a. Excessive fullness, twist, pleats or any other distortion seriously affecting appearance			X	
b. Not double plied base cloth			X	
c. Not dimension required				X
d. Lining and/or interlining missing			X	
Waist darts:				
a. Missing, one or more			X	
Fly:				
a. French tab missing			X	
b. Fly uneven				X
c. Seam or slide fastener seam exposed when fly is closed			X	
d. Lining missing			X	
Pockets:				
a. One or more pockets missing	X			
b. Absence of pocket bearers			X	
c. Side pockets not proper cut				X
Labels:				
a. Missing, incorrect, or illegible	X			
Slide fastener:				
a. Missing	X			
b. Inoperative	X			
c. Not properly secured			X	
Belt loops:				
a. Less than 7			X	
b. Incorrectly positioned			X	
c. Incorrect dimensions			X	
Buckle:				
a. Any component missing	X			
b. Not type required			X	
c. Not noncorrosive metal			X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:28Z
Check the source to verify that this is the current version before use.

4.2.2.2 Size measurements. Any measurements deviating from standard commercial dimensions and tolerances (see 1.2.2).

4.2.2.3 Acceptable quality levels and inspection levels:

	AQL's	Inspection level
For 4.2.2.1		II
Major	4.0	
Major and minor A (combined)	15.0	
Totals: major, minor A and B (combined)	40.0	
For 4.2.2.2		S-3
One class defects	4.0	
For 4.2.2.4		S-3
One class defect	4.0	

4.2.2.4 Examination for color and shade. Any pair of trousers deviating from the color and shade (see 3.3.1.5).

4.2.2.5 A certificate of compliance shall be submitted by the supplier to the authoritative representative in the Government stating that he can meet the specification requirements for noncorrosive metal buckles (see 3.3.6).

4.3 Tests. Wherever applicable, tests specified in table I shall be conducted in accordance with methods prescribed in Specification CCC-T-191. Except where otherwise specified, all testing requirements apply to the sample unit.

TABLE I. Test methods

Component	Characteristic	Requirement paragraph	Test method	Results reported as:
Basic cloth	Fiber identification:			
	Wool	3.3.1.1	1100	Pass or fail.
	Acrylic	3.3.1.1	Comm. Std. 1/	_____
	Polyester	3.3.1.1	Comm. Std. 1/	_____
	Yarns per inch	3.3.1.3	5050	Pass or fail.
	Wgt. per. sq. yd.	3.3.1.2	5041	Average of 5 determinations to nearest whole number.
	Weave	3.3.1.4	Visual	Pass or fail.
	Colorfastness to:			
	Light	3.3.1.5.2	5660	Good, fair or poor.
	Crocking	3.3.1.5.2	5651	Good, fair or poor.
	Wet dry cleaning	3.3.1.5.2	5622	Good, fair or poor.
	Perspiration	3.3.1.5.2	5680 or 5682	Good, fair or poor.
	Shrinkage	3.3.1.6.1	5558	_____
	Pilling	3.3.1.7	ASTM-D-1375-59T Method "c"	Excellent, good, medium, poor, very poor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:28Z
Check the source to verify that this is the current version before use.

TABLE I. (cont'd)

Component	Characteristic	Requirement paragraph	Test method	Results reported as:
	Breaking strength:			
	Warp	3.3.1.8	5100	Average of 5 determinations to nearest whole number.
	Filling	3.3.1.8	5100	
	Seam efficiency	3.3.1.9	5110	Pass or fail.
Nonwoven cloth (waistband)	Identification	3.3.2	Visual	Pass or fail.
	Weight	3.3.2	5041	Average of 5 determinations to nearest whole number
	Thickness	3.3.2	5030	Nearest 0.001 inch.
Nylon scrim (waistband)	Identification	3.3.2	1530	Pass or fail.
Pocketing and lining	Identification, cotton	3.3.3	1200	Pass or fail.
	Identification, nylon	3.3.3	1530	Pass or fail.
	Identification, polyester	3.3.3	Comm. Std. 1/	————
	Identification, acrylic	3.3.3	Comm. Std. 1/	————
	Weight	3.3.3	5041	Average of 5 determinations to nearest whole number.
	Shrinkage	3.3.3	5580	Pass or fail.
	Colorfastness:			
	Wet dry cleaning	3.3.3.1.1	5622	Good, fair or poor.
	Perspiration	3.3.3.1.1	5680 or 5682	Good, fair or poor.
	Crocking	3.3.3.1.1	5651	Excellent, good, fair or poor.
	Yarns per inch:			
	Warp	3.3.3	5050	Pass or fail.
	Filling	3.3.3	5050	Pass or fail.
	Seam efficiency	3.3.3.2	5110	Pass or fail.
	Nonfibrous materials	3.3.3.3	2611	Pass or fail.
Gimp	Identification, cotton	3.3.4	1200	Pass or fail.
	Ply	3.3.4	Visual	Pass or fail.
	Finish	3.3.4	Visual	Pass or fail.
	Breaking strength	3.3.4	4100	————

1/ A certificate of compliance shall be submitted by the supplier to the authoritative representative in the Government stating that he can meet the specification requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:28Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

For Civil agency procurement the definitions and applications of levels of packaging and packing shall be in accordance with Fed. Std. No. 102.

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.3).

5.1.1 Level A and B. The trousers shall be individually folded. Five folded garments, of one size only, shall be neatly stacked in a bundle and securely tied with cotton tape or twine approximately 4 inches from each end.

5.1.2 Level C. The pants shall be packaged in accordance with the industry's practice.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.3).

5.2.1 Level A. Trousers of one size only, packaged as specified in 5.1, shall be packed in a box conforming to PPP-B-636, V3c, style FOL. Each box shall have the contents covered on top and bottom with a sheet of 30 pound basis weight paper conforming to UU-P-268, grade B. The box shall be waterproof sealed with tape and reinforced with bands of tape in accordance with the appendix to the box specification. One ounce of flaked naphthalene conforming to R-N-91, or its equivalent shall be evenly distributed throughout the box.

5.2.2 Level B. Trousers of one size only, packaged as specified in 5.1, shall be packed in a box conforming to PPP-B-636, type CF, class domestic, style FOL. Each box shall have the contents covered on top and bottom with a sheet of 30-pound basis weight paper conforming to UU-P-268, grade B. The box shall be sealed and closed in accordance with appendix to the box specification. One ounce of flaked napthalene conforming to R-N-91, or its equivalent shall be evenly distributed throughout the box.

5.2.3 Level C. The trousers shall be packed to insure carrier acceptance and safe delivery to destination in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 Marking.

5.3.1 Civil agencies. In addition to markings specified in the contract or order the packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. In addition to markings specified in the contract or order the packages and shipping containers shall be marked in accordance with standard MIL-STD-129.

6. NOTES

6.1 Intended use. Trousers covered by this specification are primarily intended for use by the Job Corps (OEO), but may be obtained by other Government agencies for appropriate use.

6.2 Standard samples. For access to standard shade samples (swatches), address the procuring office issuing the invitation to bids (see 3.1 and 3.3.1.5).

6.3 Ordering data. Purchasers should exercise any desired options offered herein, and procurement documents should specify the following:

(a) Title, number, and date of specification.
(b) Sizes (1.2.2).
(c) Whether a preproduction sample is required (3.2).
(d) Packaging and Packing (5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:28Z
Check the source to verify that this is the current version before use.